

OpenXM/Risa/Asir-Contrib

OpenXM/Risa/Asir-Contrib User's Manual (ㄱ)
Edition 1.3.2-3 for OpenXM/Asir2000
March 2017 (minor update on 8 June 2017)

by OpenXM Developing Team

1

医 激鴻 asir OpenXM 渦 (Open message eXchange for Mathematics,
<http://www.openxm.org>) 泣若泣若 渦渦若渦 . 泣若若吟 や渦帥 若拷
 違 <や ‘OpenXM/rc/asirrc’ 若 激鴻 粹昭障. Risa/Asir (OpenXM 組) 儀
 <や 茯 障. Risa/Asir (OpenXM 組), ヤ OpenXM/Risa/Asir 若. ヤ
 asir 渦 若区茯 吾医 違渦 若 c i 違茯 .

HEAD branch 亥 asir-contrib ヤ <http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/index-d>
 .

OpenXM 渦 茵荅括完 や , ‘\$(OpenXM_HOME)/doc/OpenXM-specs’ <や
 ‘openxm-jp.tex’ 苟 .
 , 膊罌箏 医 罐純推.

List of contributors:

- Maekawa, Masahide (Oct., 1999 – : CVS server)
- Noro, Masayuki (Jan., 1996 – : OpenXM Protocol OXRFC-100, asir2000)
- Ohara, Katsuyoshi (Jan., 1998 – : ox_math, oxc OXRFC-101)
- Takayama, Nobuki (Jan., 1996 – : OpenXM Protocol OXRFC-100, kan/sm1, asir-contrib)
- Tamura, Yasushi (Nov., 1998 – : OpenMath proxy, tfb)
- Fujimoto, Mitsushi (Windows)
- Iwane, Hidenao (Knapsack factorizer)
- Nakayama, Hiromasa (Gaussian elimination)
- Okutani, Yukio (Oct., 1999 – Feb., 2000 : matrix, diff, ...)
- Stillman, Mike (Macaulay 2 client and server)
- Tsai, Harrison (Macaulay 2 client and server)

Contrib 宴若吾 飯岡 や , OpenXM/Copyright 荀 .
障 > 荐若 .

2 Asir/Contrib 若号.

‘OpenXM/rc/asirrc’ 若 Asir/Contrib 源 達 純 . OpenXM/Risa/Asir
 ASIR_CONFIG 医紊達 <や 莎析 帥 . ‘names.rr’ Asir/Contrib <や .
 <や <や 茯 粹昭障 . 箏 宴若吾 ‘names.rr’ 粹昭障 , 腓桡 粹昭綽荀.

A sample of ‘asirrc’ to use Asir/Contrib.

```
load("gr")$
load("primdec")$
load("katsura")$
load("bfct")$
load("names.rr")$
load("oxrfc103.rr")$
User_asirrc=which(getenv("HOME")+"/.asirrc")$
if (type(User_asirrc)!=0)
  if (!ctrl("quiet_mode")) print("Loading ~/.asirrc")$
  load(User_asirrc)$
else $
end$
```

3 Asir Contrib 醇医 や

Asir Contrib (1) 岡羣 臂 医 醇 (names.rr (2) Asir 岡羣醇遺札素 や 醇 (3) OpenXM 泣若 asir 若吟 醇 障 .

Asir Contrib 醇医 吾ヤ若 障 就 : 眼 _醇医

岡羣 医 醇違 欲吾 若 . sm1.hilbert OpenXM 泣若 sm1 Hilbert 醇違 膊醇 違若喝牙醇違 . 筭 poly_hilbert_polynomial Asir Contrib Hilbert 醇違荐膊 (1) 岡羣 醇医 . 岡羣醇 poly_hilbert_polynomial , 上 sm1.hilbert 若喝牙 Hilbert 醇違荐膊 , ヌ眼 . , Asir 荐茯 菴違 や 醇育 commutativeRing.rr 牙 Hilbert 醇違 膊 醇 commutativeRing_hilbert_polynomial 障 c , 岡羣醇 poly_hilbert_polynomial , commutativeRing_hilbert_polynomial 若喝牙 Hilbert 醇違荐膊 . c , 若吟 違 羣医 醇医 障.

岡羣医 醇医, OpenXM project , 吾 演 簞罕や . , kan/k0 Asir Contrib 罕 羣医 醇医 篋紵 . 上 薑 医 醇違 眼 complex 茲箴 (茲脰違) ヤ kan/k0, asir/contrib 演荅 帥 .

簞ヤ , 岡羣医 醇違 茯 , や 醇, , OpenXM 泣若 や渦帥 若鴻 .

4 Windows Asir-contrib

Windows 筆紘 asir-contrib 箵. 上, 紊 濁濁若濁 sm1 , 紊 濁濁若濁 asir-contrib
 違箵. Cygwin 医 濁濁若濁 sm1, phc 箵. 濁濁若濁 箵 .

罨 < 違 Windows 箵 . Windows cygwin 医 箵翫.

- gnuplot.*
- om.*
- mathematica.*
- phc.*
- print_dvi_form
- print_gif_form
- print_open_math_xml_form
- print_png_form
- print_xdvi_form
- print_xv_form
- tigers_xv_form

5 榲 (罔羣醇)

5.0.1 base_cancel

`base_cancel(S)`
: It simplifies S by canceling the common factors of denominators and numerators.

Example:

```
base_cancel([(x-1)/(x^2-1), (x-1)/(x^3-1)]);
```

5.0.2 base_choose

`base_choose(L,M)`
: It returns the list of the order M subsets of L .

Example:

```
base_choose([1,2,3],2);
```

It outputs all the order 2 subsets of the set $\{1,2,3\}$

5.0.3 base_flatten

`base_flatten(S)`
: It flattens a nested list S .

Example:

```
base_flatten([[1,2,3],4]);
```

5.0.4 base_intersection

`base_intersection(A,B)`
: It returns the intersection of A and B as a set.

Example:

```
base_intersection([1,2,3],[2,3,5,[6,5]]);
```

5.0.5 base_makelist

`base_makelist(Obj,K,B,T)`
: `base_makelist` generate a list from `Obj` where K runs in $[B,T]$. Options are `qt=1` (keep quote data), `step` (step size). When B is a list, T is ignored and K runs in B .

Example 0:

```
base_makelist(k^2,k,1,10);
```

Example 1:

```
map(print_input_form,base_makelist(quote(x^2),x,1,10 | qt=1, step=0.5))
```

Example 2:

```
base_makelist(quote("the "+k),k,["cat","dog"],0);
```

5.0.6 base_memberq

`base_memberq(A,S)`

: It returns 1 if A is a member of the set S else returns 0.

Example:

```
base_memberq(2,[1,2,3]);
```

5.0.7 base_permutation

`base_permutation(L)`

: It outputs all permutations of L . BUG; it uses a slow algorithm.

Example:

```
base_permutation([1,2,3,4]);
```

5.0.8 base_position

`base_position(A,S)`

: It returns the position of A in S .

Example:

```
base_position("cat",["dog","cat","monkey"]);
```

5.0.9 base_product

`base_product(Obj,K,B,T)`

: `base_product` returns the product of Obj where K runs in $[B,T]$. Options are `qt=1` (keep quote data), `step` (step size). When B is a list, K runs in B and T is ignored.

Example 0:

```
base_product(k^2,k,1,10);
```

Example 1:

```
base_product(quote(x^2),x,1,10 | qt=1, step=0.5);
```

Example 2:

```
base_product(quote(x^2),x,[a,b,c],0 | qt=1);
```

5.0.10 base_prune

`base_prune(A,S)`

: It returns a list in which A is removed from S .

Example:

```
base_prune("cat",["dog","cat","monkey"]);
```

5.0.11 base_rebuild_opt

`base_rebuild_opt(Opt)`

: It rebuilt the option list Opt

Example:

```
base_rebuild_opt([[key1,1],[key2,3]] | remove_keys=["key2"]);
it returns [[key1,1]]
```


5.0.12 base_replace`base_replace(S, Rule)`: It rewrites *S* by using the rule *Rule*

Example:

`base_replace(x^2+y^2, [[x,a+1],[y,b]]);`x is replaced by a+1 and y is replaced by b in x^2+y^2 .**5.0.13 base_replace_n**`base_replace_n(S, Rule)`: It rewrites *S* by using the rule *Rule*. It is used only for specializing variables to numbers and faster than `base_replace`.

Example:

`base_replace_n(x^2+y^2, [[x,1/2],[y,2.0+3*@i]]);`x is replaced by 1/2 and y is replaced by 2.0+3*in x^2+y^2 .**5.0.14 base_set_minus**`base_set_minus(A, B)`: $A \setminus B$

Example:

`base_set_minus([1,2,3],[3,4,5]);`**5.0.15 base_set_union**`base_set_union(A, B)`: $A \cup B$

Example:

`base_set_union([1,2,3],[3,4,5]);`**5.0.16 base_subsetq**`base_subsetq(A, B)`: if $A \subseteq B$, then it returns 1 else 0.

Example:

`base_subsetq([1,2],[1,2,3,4,5]);`**5.0.17 base_subsets_of_size**`base_subsets_of_size(K, S)`: It outputs all subsets of *S* of the size *K*. BUG; it uses a slow algorithm. Do not input a large *S*.

Example:

`base_subsets_of_size(2,[3,5,3,2]);`

5.0.18 base_sum

`base_sum(Obj,K,B,T)`

: `base_sum` returns the sum of `Obj` where `K` runs in `[B,T]`. Options are `qt=1` (keep quote data), `step` (step size). When `B` is a list, `K` runs in `B` and `T` is ignored. When `K` is 0, then `Obj` is assumed to be a list or vector and `Obj[B]+...+Obj[T]` is returned.

Example 0:

```
base_sum(k^2,k,1,10);
```

Example 1:

```
base_sum(quote(x^2),x,1,10 | qt=1, step=0.5);
```

Example 2:

```
base_sum(quote(x^2),x,[a,b,c],0 | qt=1);
```

5.0.19 base_var_list

`base_var_list(Name,B,T)`

: `base_var_list` generate a list of variables `Name+Index` where `Index` runs on `[B,T]`.

Example 0:

```
base_var_list(x,0,10);
```

Example 1:

```
base_var_list(x,1,4 | d = 1);
```

Options are `d=1` (add `d` before the name).

6 (岡羣医 醇)

6.0.1 number_abs

`number_abs(X)`
:

Example:

```
number_abs(-3);
```

6.0.2 number_ceiling

`number_ceiling(X)`
:

Example:

```
number_abs(1.5);
```

6.0.3 number_eval

`number_eval(X)`
:

Example:

```
number_eval([1/10^10,@pi,exp(1)]);
```

6.0.4 number_factor

`number_factor(X)`
: It factors the given integer X.

Example:

```
number_factor(20);
```

6.0.5 number_float_to_rational

`number_float_to_rational(X)`
:

Example:

```
number_float_to_rational(1.5234);  
number_float_to_rational(1.5234 | prec=14);
```

6.0.6 number_floor

`number_floor(X)`
:

Example:

```
number_floor(1.5);
```

6.0.7 number_imaginary_part

`number_imaginary_part(X)`
:

Example:

```
number_imaginary_part(1+2*@i);
```

6.0.8 number_is_integer

`number_is_integer(X)`
:

Example:

```
number_is_integer(2/3);
```

6.0.9 number_real_part

`number_real_part(X)`
:

Example:

```
number_real_part(1+2*@i);
```

7 緇 (岡羣医 醇)

8 腔 (罔羣医 醇)

9 号醇 (罔羣医 醇)

障吾 .

10 茵 (罔羣医 醇)

10.0.1 matrix_adjugate

`matrix_adjugate(M)`

: It generates the adjugate matrix of the matrix M .

Example:

```
matrix_adjugate(matrix_list_to_matrix([[a,b],[c,d]]));
```

10.0.2 matrix_clone

`matrix_clone(M)`

: It generates the clone of the matrix M .

Example:

```
matrix_clone(matrix_list_to_matrix([[1,1],[0,1]]));
```

10.0.3 matrix_det

`matrix_det(M)`

: It returns the determinant of the matrix M .

Example:

```
poly_factor(matrix_det([[1,x,x^2],[1,y,y^2],[1,z,z^2]]));
```

10.0.4 matrix_diagonal_matrix

`matrix_diagonal_matrix(L)`

: It returns the diagonal matrix with diagonal entries L .

Example:

```
matrix_diagonal_matrix([1,2,3]);
```

References:

```
matrix_list_to_matrix
```

10.0.5 matrix_eigenvalues

`matrix_eigenvalues(M)`

: It returns the eigenvalues of the matrix M .

Example:

```
matrix_eigenvalues([[x,1],[0,y]]);
```

10.0.6 matrix_gauge_transformation

`matrix_gauge_transformation(M, T, V)`

: It returns $T^{(-1)} M T - T^{(-1)} dT/dV$

Example:

```
matrix_gauge_transformation([[0,x],[1,x]],[[x,0],[0,1]],x);
```


10.0.7 matrix_identity_matrix**matrix_identity_matrix(N)**: It returns the identity matrix of the size N .

Example:

`matrix_identity_matrix(5);`

References:

`matrix_diagonal_matrix`**10.0.8 matrix_image****matrix_image(M)**: It computes the image of M . Redundant vectors are removed.

Example:

`matrix_image([[1,2,3],[2,4,6],[1,0,0]]);`

References:

`matrix_kernel`**10.0.9 matrix_inner_product****matrix_inner_product(A,B)**: It returns the inner product of two vectors A and B .

Example:

`matrix_inner_product([1,2],[x,y]);`**10.0.10 matrix_inverse****matrix_inverse(M)**: It returns the inverse of the matrix M .

Example:

`matrix_inverse([[1,2],[0,1]]);`**10.0.11 matrix_kernel****matrix_kernel(M)**: It returns the basis of the kernel of the matrix M .

Example:

`matrix_kernel([[1,1,1,1],[0,1,3,4]]);`**10.0.12 matrix_list_to_matrix****matrix_list_to_matrix(M)**: It translates the list M to a matrix.

Example:

`print_xdvi_form(matrix_list_to_matrix([[1,1],[0,2]]));`

References:

`matrix_matrix_to_list`

10.0.13 matrix_matrix_to_list

`matrix_matrix_to_list(M)`
: It translates the matrix *M* to a list.

References:

`matrix_list_to_matrix`

10.0.14 matrix_rank

`matrix_rank(M)`
: It returns the rank of the matrix *M*.

Example:

```
matrix_rank([[1,1,1,1],[0,1,3,4]]);
```

10.0.15 matrix_solve_linear

`matrix_solve_linear(M,X,B)`
: It solves the system of linear equations $M X = B$

Example:

```
matrix_solve_linear([[1,2],[0,1]],[x,y],[1,2]);
```

10.0.16 matrix_submatrix

`matrix_submatrix(M,Ind)`
: It returns the submatrix of *M* defined by the index set *Ind*.

Example:

```
matrix_submatrix([[0,1],[2,3],[4,5]],[1,2]);
```

10.0.17 matrix_transpose

`matrix_transpose(M)`
: It returns the transpose of the matrix *M*.

References:

`matrix_list_to_matrix`

11 Graphic(岡羣医 醇)

障吾 .

12 茵 ず (岡羣医 醇)

12.0.1 print_dvi_form

`print_dvi_form(S)`

: It outputs S to a dvi file.

Example:

```
print_dvi_form(x^2-1);
```

References:

`print_xdvi_form`, `print_tex_form`

12.0.2 print_em

`print_em(S)`

: It outputs S by a font to emphasize it.

Example:

```
print_em(x^2-1);
```

12.0.3 print_gif_form

`print_gif_form(S)`

: It outputs S to a file of the gif format.

`print_gif_form(S | table=key0)`

: This function allows optional variables *table*

Example:

```
print_gif_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));
```

References:

`print_tex_form`

12.0.4 print_input_form

`print_input_form(S)`

: It transforms S to a string which can be parsed by asir.

Example:

```
print_input_form(quote(x^3-1));
```

12.0.5 print_open_math_tfb_form

`print_open_math_tfb_form(S)`

: It transforms S to a tfb format of OpenMath XML.

Description:

It is experimental. You need to load `taka_print_tfb.rr` to call it.

Example:

```
print_open_math_tfb_form(quote(f(x,1/(y+1))+2));
```

12.0.6 print_open_math_xml_form

`print_open_math_xml_form(S)`

: It transforms S to a string which is compliant to OpenMath(1999).

Example:

```
print_open_math_xml_form(x^3-1);
```

References:

www.openmath.org

12.0.7 print_output

`print_output(Obj)`

: It outputs the object Obj to a file. If the optional variable *file* is set, then it outputs the Obj to the specified file, else it outputs it to "asir_output_tmp.txt". If the optional variable *mode* is set to "w", then the file is newly created. If the optional variable is not set, the Obj is appended to the file.

`print_output(Obj | file=key0, mode=key1)`

: This function allows optional variables *file*, *mode*

Example:

```
print_output("Hello"|file="test.txt");
```

References:

`glib_tops`, (,)

12.0.8 print_ox_rfc100_xml_form

`print_ox_rfc100_xml_form(S)`

: It transforms S to a string which is compliant to OpenXM RFC 100.

Example:

```
print_ox_rfc100_xml_form(x^3-1);
```

References:

www.openxm.org

12.0.9 print_png_form

`print_png_form(S)`

: It transforms S to a file of the format png. dvi png should be installed.

Example:

```
print_png_form(x^3-1);
```

References:

`print_tex_form`

12.0.10 print_terminal_form

`print_terminal_form(S)`

: It transforms S to the terminal form???

12.0.11 print_tex_form

`print_tex_form(S)`

: It transforms S to a string of the LaTeX format.

`print_tex_form(S | table=key0,raw=key1)`

: This function allows optional variables *table*, *raw*

Description:

The global variable `Print_tex_form_fraction_format` takes the values "auto", "frac", or "/". The global variable `Print_tex_form_no_automatic_subscript` takes the values 0 or 1. BUG; A large input S cannot be translated.

Example:

```
print_tex_form(x*dx+1 | table=["dx","\\partial_x"]]);
```

The optional variable *table* is used to give a translation table of asir symbols and tex symbols. when `AMSTeX = 1`, "begin pmatrix" and "end pmatrix" will be used to output matrix.

References:

`print_xdvi_form`

12.0.12 print_tfb_form

`print_tfb_form(S)`

: It transforms S to the tfb format.

Example:

```
print_tfb_form(x+1);
```

12.0.13 print_xdvi_form

`print_xdvi_form(S)`

: It transforms S to a xdvi file and previews the file by xdvi.

Example 0:

```
print_xdvi_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));
```

Example 1:

```
print_xdvi_form(print_tex_form(1/2));
```

References:

`print_tex_form`, `print_dvi_form`

12.0.14 print_xv_form

`print_xv_form(S)`

: It transforms S to a gif file and previews the file by xv.

`print_xv_form(S | input=key0,format=key1)`

: This function allows optional variables *input*, *format*

Example 0:

```
print_xv_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));
```

Example 1:

```
print_xv_form(x+y | format="png");
```

If the optional variable `format="png"` is set, png format will be used to generate an input for xv.

References:

```
print_tex_form , print_gif_form
```

13 素数 (冢田医 醇)

13.0.1 poly_coefficient

`poly_coefficient(F, Deg, V)`

: It returns the coefficient of V^{Deg} in F . F may be rational or list or vector.

Example:

```
F=[(x+y+z)^10/z^2,(x-y+z)^10/z^3]$
poly_coefficient(F,10,x);
```

13.0.2 poly_degree

`poly_degree(F)`

: It returns the degree of F with respect to the given weight vector.

`poly_degree(F | weight=key0, v=key1)`

: This function allows optional variables *weight*, v

Description:

The weight is given by the optional variable *weight* w . It returns $\text{ord}_w(F)$

Example:

```
poly_degree(x^2+y^2-4 |weight=[100,1],v=[x,y]);
```

13.0.3 poly_elimination_ideal

`poly_elimination_ideal(I, VV)`

: It computes the intersection of the ideal I and the subring $K[VV]$.

`poly_elimination_ideal(I, VV |`

`grobner_basis=key0, v=key1, homo=key2, grace=key3, strategy=key4)`

: This function allows optional variables *grobner_basis*, v , *homo*, *grace*, *strategy*

Description:

If *grobner_basis* is "yes", I is assumed to be a Grobner basis. The optional variable v is a list of variables which defines the ring of polynomials.

Example 0:

```
poly_elimination_ideal([x^2+y^2-4,x*y-1],[x]);
```

Example 1:

```
A = poly_grobner_basis([x^2+y^2-4,x*y-1]|order=2,v=[y,x]);
poly_elimination_ideal(A,[x]|grobner_basis="yes");
```

When *strategy*=1(default),

`nd_gr` is used when *trace*=0(default),

`nd_gr_trace` is used when *trace*=1.

References:

`gr`, `hgr`, `gr_mod`, `dp_*`

13.0.4 poly_expand

`poly_expand(F)`

: This is an alias of `poly_sort`.

References:

`poly_sort`

13.0.5 poly_factor

`poly_factor(F)`

: It factorizes the polynomial F .

Example:

```
poly_factor(x^10-y^10);
```

13.0.6 poly_gcd

`poly_gcd(F,G)`

: It computes the polynomial GCD of F and G .

Example:

```
poly_gcd(x^10-y^10,x^25-y^25);
```

13.0.7 poly_gr_w

`poly_gr_w(F,V,W)`

: It returns the Grobner basis of F for the weight vector W . It is the second interface for `poly_grobner_basis`.

Example:

```
poly_gr_w([x^2+y^2-1,x*y-1],[x,y],[1,0]);
```

References:

`poly_in_w`, `poly_grobner_bais`

13.0.8 poly_grobner_basis

`poly_grobner_basis(I)`

: It returns the Grobner basis of I .

`poly_grobner_basis(I | order=key0,v=key1)`

: This function allows optional variables `order`, `v`

Description:

The optional variable `v` is a list of variables which defines the ring of polynomials.

Example:

```
A = poly_grobner_basis([x^2+y^2-4,x*y-1] | order=2,v=[y,x],str=1);
A->Generators;
A->Ring->Variables;
A->Ring->Order;
B = poly_grobner_basis([x^2+y^2-4,x*y-1] | order=[[10,1]],v=[y,x]);
C = poly_grobner_basis([x^2+y^2-4,x*y-1] | order=[block,[0,1],[0,1]],v=[y,x]);
```

13.0.9 poly_hilbert_polynomial

`poly_hilbert_polynomial(I)`
: It returns the Hilbert polynomial of the ideal I .

`poly_hilbert_polynomial(I | s=key0, v=key1)`
: This function allows optional variables s , v

Description:

The optional variable v is a list of variables.

Example:

```
poly_hilbert_polynomial([x1*y1,x1*y2,x2*y1,x2*y2] | s=k, v=[x1,x2,y1,y2]);
```

13.0.10 poly_ideal_colon

`poly_ideal_colon(I, J, V)`
: It computes the colon ideal of I by J V is the list of variables.

Example:

```
B=[(x+y+z)^50,(x-y+z)^50]$
V=[x,y,z]$
B=poly_ideal_colon(B, [(x+y+z)^49,(x-y+z)^49], V);
```

13.0.11 poly_ideal_intersection

`poly_ideal_intersection(I, J, V, Ord)`
: It computes the intersection of the ideal I and J V is the list of variables.
 Ord is the order.

Example:

```
A=[j*h*g*f*e*d*b,j*i*g*d*c*b,j*i*h*g*d*b,j*i*h*e*b,i*e*c*b,z]$
B=[a*d-j*c,b*c,d*e-f*g*h]$
V=[a,b,c,d,e,f,g,h,i,j,z]$
poly_ideal_intersection(A,B,V,0);
```

13.0.12 poly_ideal_saturation

`poly_ideal_saturation(I, J, V)`
: It computes the saturation ideal of I by J . V is the list of variables.

Example:

```
B=[(x+y+z)^50,(x-y+z)^50]$
V=[x,y,z]$
B=poly_ideal_saturation(B, [(x+y+z)^49,(x-y+z)^49], V);
```

13.0.13 poly_in`poly_in(I)`: It is an alias of `poly_initial()`.`poly_in(I | order=key0, v=key1)`: This function allows optional variables `order`, `v`

Example:

`poly_in([x^2+y^2-4, x*y-1] | order=0, v=[x, y]);`**13.0.14 poly_in_w**`poly_in_w(F, V, W)`: It returns the initial term or the initial ideal `in_w(F)` for the weight vector given by `order`. `F` is a single polynomial or a list of polynomials.`poly_in_w(F, V, W | gb=key0)`: This function allows optional variables `gb`

Example:

`poly_in_w([x^2+y^2-1, x*y-x] | v=[x, y], weight=[1, 0]);`

References:

`poly_weight_to_omatrix`, `(, W, V,)`, `poly_grobner_basis`, `poly_gr_w`,
`poly_in_w`**13.0.15 poly_in_w_**`poly_in_w_(F)`: It returns the initial term or the initial ideal `in_w(F)` for the weight vector given by `order`. `F` is a single polynomial or a list of polynomials. This is a new interface of `poly_in_w` with shorter args.`poly_in_w_(F | v=key0, weight=key1, gb=key2)`: This function allows optional variables `v`, `weight`, `gb`

Example:

`poly_in_w_([x^2+y^2-1, x*y-x] | v=[x, y], weight=[1, 0]);`

References:

`poly_weight_to_omatrix`, `(, W, V,)`, `poly_grobner_basis`, `poly_gr_w`**13.0.16 poly_initial**`poly_initial(I)`: It returns the initial ideal of `I` with respect to the given order.`poly_initial(I | order=key0, v=key1)`: This function allows optional variables `order`, `v`

Description:

The optional variable `v` is a list of variables. This function computes $\text{in}_{\prec}(I)$

Example:

`poly_initial([x^2+y^2-4, x*y-1] | order=0, v=[x, y]);`
`poly_initial([x^2+y^2-4, x*y-1] | order=0, v=[x, y], gb=1);`

13.0.17 poly_initial_coefficients**poly_initial_coefficients(*I*)**: It computes the coefficients of the initial ideal of *I* with respect to the given order.**poly_initial_coefficients(*I* | order=key0, v=key1)**: This function allows optional variables *order*, *v*

Description:

The optional variable *v* is a list of variables. The order is specified by the optional variable *order*

Example:

```
poly_initial_coefficients([x^2+y^2-4,x*y-1]|order=0,v=[x,y]);
```

13.0.18 poly_initial_term**poly_initial_term(*F*)**: It returns the initial term of a polynomial *F* with respect to the given weight vector.**poly_initial_term(*F* | weight=key0, order=key1, v=key2)**: This function allows optional variables *weight*, *order*, *v*

Description:

The weight is given by the optional variable *weight* *w*. It returns $\text{in}_w(F)$

Example:

```
poly_initial_term(x^2+y^2-4 |weight=[100,1],v=[x,y]);
```

13.0.19 poly_ord_w**poly_ord_w(*F*, *V*, *W*)**: It returns the order with respect to *W* of *F*.

Example:

```
poly_ord_w(x^2+y^2-1,[x,y],[1,3]);
```

References:

```
poly_in_w
```

13.0.20 poly_prime_dec**poly_prime_dec(*I*, *V*)**: It computes the prime ideal decomposition of the radical of *I*. *V* is a list of variables.

Example:

```
B=[x00*x11-x01*x10,x01*x12-x02*x11,x02*x13-x03*x12,x03*x14-x04*x13,
-x11*x20+x21*x10,-x21*x12+x22*x11,-x22*x13+x23*x12,-x23*x14+x24*x13];
V=[x00,x01,x02,x03,x04,x10,x11,x12,x13,x14,x20,x21,x22,x23,x24];
poly_prime_dec(B,V | radical=1);
```

13.0.21 poly_r_omatrix**poly_r_omatrix(N)**: It gives a weight matrix, which is used to compute a Grobner basis in $K(x)\langle dx \rangle$, $|x|=|dx|=N$.

Example:

`poly_r_omatrix(3);`

References:

`poly_weight_to_omatrix, (, W, V,), ;`**13.0.22 poly_solve_linear****poly_solve_linear(Eqs, V)**: It solves the system of linear equations Eqs with respect to the set of variables V .

Example:

`poly_solve_linear([2*x+3*y-z-2, x+y+z-1], [x,y,z]);`**13.0.23 poly_sort****poly_sort(F)**: It expands F with a given variables $v=V$ and a given weight $w=W$. It returns a quote object. If *truncate* option is set, the expansion is truncated at the given degree.**poly_sort($F \mid v=key0, w=key1, truncate=key2$)**: This function allows optional variables v , w , *truncate*

Example:

`poly_sort((x-y-a)^3 | v=[x,y], w=[-1,-1])`
returns a series expansion in terms of x and y .**13.0.24 poly_toric_ideal****poly_toric_ideal(A, V)**: It returns generators of the affine toric ideal defined by the matrix(list) A . V is the list of variables.

Example:

`poly_toric_ideal([[1,1,1,1],[0,1,2,3]],base_var_list(x,0,3));`**13.0.25 poly_weight_to_omatrix****poly_weight_to_omatrix(W, V)**: It translates the weight vector W into a matrix, which is used to set the order in asir Grobner basis functions. V is the list of variables.

Example:

`M=poly_weight_to_omatrix([2,1,0],[x,y,z]);`
`nd_gr([x^3+z^3-1,x*y*z-1,y^2+z^2-1],[x,y,z],0,M);`

14 茲箴 (岡羣医 醇)

15 違 c や (2 罫)

16 Graphic Library (2 dimensional)

や glib, Risa/Asir 違 c 堺 (draw_obj), BASIC 膾 や鴻帥 若鴻箴.

16.0.1 glib_clear

`glib_clear()`
: Clear the screen.

16.0.2 glib_flush

`glib_flush()`
: ; Flush the output. (Cfep only. It also set initGL to 1.).

16.0.3 glib_line

`glib_line(X0,Y0,X1,Y1)`
: It draws the line $[X0,Y0]$ – $[X1,Y1]$ with *color* and *shape*

`glib_line(X0,Y0,X1,Y1 | color=key0,shape=key1)`
: This function allows optional variables *color*, *shape*

Example:

```
glib_line(0,0,5,3/2 | color=0xff00ff);
glib_line(0,0,10,0 | shape=arrow);
```

16.0.4 glib_open

`glib_open()`
: It starts the ox_plot server and opens a canvas. The canvas size is set to *Glib_canvas_x* X *Glib_canvas_y* (the default value is 400). This function is automatically called when the user calls glib functions.

16.0.5 glib_plot

`glib_plot(F)`
: It plots an object *F* on the glib canvas.

Example 0:

```
glib_plot([[0,1],[0.1,0.9],[0.2,0.7],[0.3,0.5],[0.4,0.8]]);
```

Example 1:

```
glib_plot(tan(x));
```

16.0.6 glib_print

`glib_print(X,Y,Text)`
: It put a string *Text* at $[X,Y]$ on the glib canvas.

`glib_print(X,Y,Text | color=key0)`
: This function allows optional variables *color*

Example:

```
glib_print(100,100,"Hello Worlds" | color=0xff0000);
```


16.0.7 glib_ps_form**glib_ps_form(*S*)**: It returns the PS code generated by executing *S* (experimental).

Example 0:

```
glib_ps_form(quote( glib_line(0,0,100,100) ));
```

Example 1:

```
glib_ps_form(quote([glib_line(0,0,100,100),glib_line(100,0,0,100)]));
```

References:

`glib_tops`**16.0.8 glib_putpixel****glib_putpixel(*X,Y*)**: It puts a pixel at [*X,Y*] with *color***glib_putpixel(*X,Y* | *color=key0*)**: This function allows optional variables *color*

Example:

```
glib_putpixel(1,2 | color=0xffff00);
```

16.0.9 glib_remove_last**glib_remove_last()**: Remove the last object. `glib_flush()` should also be called to remove the last object. (cfep only).**16.0.10 glib_set_pixel_size****glib_set_pixel_size(*P*)**: Set the size of putpixel to *P*. 1.0 is the default. (cfep only).**16.0.11 glib_tops****glib_tops()**: If `Glib_ps` is set to 1, it returns a postscript program to draw the picture on the canvas.

References:

`print_output`**16.0.12 glib_window****glib_window(*Xmin,Ymin,Xmax,Ymax*)**: It generates a window with the left top corner [*Xmin,Ymin*] and the right bottom corner [*Xmax,Ymax*]. If the global variable *Glib_math_coordinate* is set to 1, mathematical coordinate system will be employed, i.e., the left top corner will have the coordinate [*Xmin,Ymax*].

Example:

```
glib_window(-1,-1,10,10);
```

17 OpenXM-Contrib 箏 醇

17.1 醇遺荀

17.1.1 ox_check_errors2

ox_check_errors2(p)

:: 荔ヨ p 泣若 鴻帥 若 吾 鴻 祉.

return 鴻

p

- 荔ヨ p 泣若 鴻帥 若 吾 鴻 祉.

- 若 吾 .

```
[219] P=sm1.start();
```

```
0
```

```
[220] sm1.sm1(P," 0 get ");
```

```
0
```

```
[221] ox_check_errors2(P);
```

```
[error([7,4294967295,executeString: Usage:get])]
```

```
Error on the server of the process number = 1
```

```
To clean the stack of the ox server,
```

```
type in ox_pops(P,N) (P: process number, N: the number of data you need to pop)
out of the debug mode.
```

```
If you like to automatically clean data on the server stack,
set XM_debug=0;
```

18 OXshell

OXshell 激鴻 渦渦 ox server 紘茵篁脰帥 . 荅渦 OpenXM/src/kan96xx/Doc/oxshell.oxw
OpenXM/doc/Papers/rims-2003-12-16-ja.tex 荀.

18.0.1 oxshell.get_value

`oxshell.get_value(NAME, V)`

: It get the value of the variable *NAME* on the server *ox_shell*.

Example:

```
oxshell.set_value("abc", "Hello world!");
oxshell.oxshell(["cp", "stringIn://abc", "stringOut://result"]);
oxshell.get_value("result");
```

What we do is a file `$TMP/abc*` is generated with the contents `Hello world!` and `c`
The contents of the file is stored in the variable `result` on `ox_sm1`.

References:

`oxshell.oxshell` , `oxshell.set_value`

18.0.2 oxshell.oxshell

`oxshell.oxshell(L)`

: It executes command *L* on a *ox_shell* server. *L* must be an array. The result is the outputs to stdout and stderr. A temporary file will be generated under `$TMP`. cf. `oxshell.keep-tmp()`

Example:

```
oxshell.oxshell(["ls"]);
```

References:

`ox_shell` , `oxshell.set_value` , `oxshell.get_value` , `oxshell` , `of` , `sm1`.

18.0.3 oxshell.set_value

`oxshell.set_value(NAME, V)`

: It set the value *V* to the variable *Name* on the server *ox_shell*.

Example:

```
oxshell.set_value("abc", "Hello world!");
oxshell.oxshell(["cat", "stringIn://abc"]);
```

References:

`oxshell.oxshell` , `oxshell.get_value`

19 Asir 激鴻膊

19.0.1 asir_contrib_update

`asir_contrib_update()`

: It updates the asir-contrib library and/or some other files to the HEAD branch. The usage will be shown by `asir_contrib_update()` without the option `update`. Options are `update`, `clean`, `url`, `install_dir`, `zip_files`, `tmp`. Default values `update=0`, `clean=0`, `url="http://www.math.kobe-u.ac.jp/OpenXM/Current"`, `install_dir=%APPDATA%/OpenXM` (win) or `install_dir=$OpenXM_tmp/OpenXM` (others) `zip_files=["lib-asir-contrib.zip"]`

Example:

```
asir_contrib_update();  
asir_contrib_update(|update=1);    update the library  
asir_contrib_update(|update=3);    update the library and the documents  
asir_contrib_update(|clean=1);  
asir_contrib_update(|zip_files=["lib-asir-contrib.zip","doc-asir2000.zip","doc-a
```

20 箴水

激鴻 羣 祉鴻恰統 梢 違 .

20.0.1 util_damepathq

`util_damepathq(S)`

: When *S* is a string by the ShiftJIS code and *S* contains dame-moji with respect to \, it returns [a non-zero number, the string].

Example:

```
T = [0x5c,0xe4,0x5c,0x41,0x42]$
T2=asciitostr(T)$
util_damepathq(T2);
```

20.0.2 util_file_exists

`util_file_exists(Fname)`

: It returns 1 when *Fname* exists. It returns 0 when *Fname* does not exist.

20.0.3 util_filter

`util_filter(Command,Input)`

: It executes the filter program *Command* with the *Input* and returns the output of the filter as a string.

`util_filter(Command,Input | env=key0)`

: This function allows optional variables *env*

Example:

```
util_filter("sort","cat\ndog\ncentipede\n");
```

20.0.4 util_find_and_replace

`util_find_and_replace(W,S,Wnew)`

: It replaces *W* in *S* by *Wnew*. Arguments must be a list of ascii codes.

20.0.5 util_find_start

`util_find_start()`

: It tries to find the gnome-open command or an installed browser in unix systems. It returns "open" on MacOS X and returns "start" on Windows.

`util_find_start(| browser=key0)`

: This function allows optional variables *browser*

20.0.6 util_find_substr

`util_find_substr(W,S)`

: It returns the position of *W* in *S*. If *W* cannot be found, it returns -1. Arguments must be a list of ascii codes.

20.0.7 util_index

`util_index(V)`

: It returns the name part and the index part of V .

Example:

```
util_index(x_2_3)
```

References:

`util_v`

20.0.8 util_load_file_as_a_string

`util_load_file_as_a_string(F)`

: It reads a file F as a string.

20.0.9 util_part

`util_part(S,P,Q)`

: It returns from P th element to Q th element of S .

20.0.10 util_read_file_as_a_string

`util_read_file_as_a_string(F)`

: It reads a file F as a string.

20.0.11 util_remove_cr

`util_remove_cr(S)`

: It removes `cr`/`lf`/`tabs` from S . Arguments must be a list of ascii codes.

20.0.12 util_timing

`util_timing(Q)`

: Show the timing data to execute Q .

Example:

```
util_timing( quote( fctr(x^50-y^50) ));
```

20.0.13 util_v

`util_v(V,L)`

: It returns a variable indexed by L .

Example:

```
util_v("x",[1,3]);
```

References:

`util_index`

20.0.14 util_write_string_to_a_file

`util_write_string_to_a_file(Fname,S)`

: It writes a string S to a file $Fname$.

21 ヤ

asir-contrib ヤ 腔剛.
 障尊 c 違茹 h . 違 ヤ ヤ 膀悟 篋紘 .

21.0.1 dsolv (Solving the initial ideal for holonomic systems)

../dsolv-html/dsolv-ja.html

21.0.2 ok_diff (Okutani's library for differential operators)

../ok_diff-html/ok_diff-ja.html

21.0.3 ok_dmodule (Okutani's library for D-modules)

../ok_dmodule-html/ok_dmodule-ja.html

21.0.4 (Plucker relations)

../plucker-html/plucker-ja.html

21.0.5 pfpcoh (Ohara's library for homology/cohomology groups for $p \leq q$)

../pfpcoh-html/pfpcoh-ja.html

21.0.6 (gnuplot ox server for graphics)

../gnuplot-html/gnuplot-ja.html

21.0.7 mathematica (Mathematica (TM) ox server)

../mathematica-html/mathematica-ja.html

21.0.8 om (om (java) ox server for translating CMO and OpenMath)

../om-html/om-ja.html

21.0.9 phc (PHC ox server for solving systems of algebraic equations by the homotopy method)

../phc-html/phc-ja.html

21.0.10 sm1 (Kan/sm1 ox server for the ring of differential operators)

../sm1-html/sm1-ja.html

21.0.11 tigers (tigers ox server for toric universal Grobner bases)

../tigers-html/tigers-ja.html

21.0.12 f_res (Comuting resultant)

../f_res-html/f_res-ja.html

21.0.13 mt_graph (3D grapher)

../mk_graph-html/mk_graph-ja.html

21.0.14 noro_mwl (Mordel Weil Lattice)

../noro_mwl-html/noro_mwl-ja.html

21.0.15 nn_ndbf (local b-function)

../nn_ndbf-html/nn_ndbf-ja.html

21.0.16 noro_pd (New Primary Ideal Decomposition)

../noro_pd-html/noro_pd-ja.html

21.0.17 ns_twistedlog (twisted logarithmic cohomology group)

../ns_twistedlog-html/ns_twistedlog-ja.html

21.0.18 nk_fb_gen_c (Fisher Bingham MLE)

../nk_fb_gen_c-html/nk_fb_gen_c-ja.html

21.0.19 gtt_ekn (Two way contingency tables by HGM)

../gtt_ekn-html/gtt_ekn-ja.html

21.0.20 noro_module_syz (syzygies for modules)

../noro_module_syz-html/noro_module_syz-ja.html

21.0.21 n_wishartd (restriction of matrix 1F1)

../n_wishartd-html/n_wishartd-ja.html

21.0.22 todo_parametrize

../todo_parametrize-html/todo_parametrize-ja.html

宴若 todo_parametrize/todo_parametrize.rr 若 , 牙 < 若
粹; 腓牙苟篁 違 , paramerize . 荅湍 See section “网苟” in
Risa/Asir 篁 f 井牙茫 宴若梧 苟 (Web Risa/Asir 篁 f 井牙茫 宴若梧
(http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/asir-contrib/html-ja/todo_parametrize/todo_parametrize_ja_toc.html)). 宴若吾 ヤ 吾 輝 障 . 宴
若吾 障 module 罕 , や 腦 醇 .

```
[1205] load("todo_parametrize/todo_parametrize.rr");
1
[1425] parametrize(y^2-x^3);
[155*t^2+20*t+1,720*t^4+1044*t^3+580*t^2,155*t^4+20*t^3+t^2,(-x)/(y)]
[1426] parametrize(y^2+x^3);
[-t,1,t^3,(-x)/(y)]
```


21.0.23 taji_alc

../taji_alc-html/taji_alc-ja.html

宴若 taji_alc.rr 若 , 箏素遣撮亥渦 悟召 c 違 若 . (Web Risa/Asir 箏素遣撮亥絮渦 吾守 Risa/Aisir 宴若梧 (http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/asir-contrib-alc-html/taji_alc-ja_toc.html)).

```
import("taji_alc.rr");
taji_alc.laurent_expansion(x,(x-1)^3);
```

21.0.24 Texinfo ヤ , 茫膈.

OpenXM documents (<http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/index-doc-ja.html>).

texinfo 吾 asir-contrib <や 違 ヤ , h 吾 渦 .

(yang, fj-curve, nk_mora 膈)

脰

(Index is nonexistent)

(Index is nonexistent)

Short Contents

1	^^81 ^^81^^98^^82^^81^^81	1
2	Asir/Contrib ^^81 ^^83 ^^83 若^^83^^89^^96 号^^95.	3
3	Asir Contrib ^^81 ^^87 醇^^95 医^^90^^8d^^81 ^^81や ^^81^^84^^81.....	4
4	Windows ^^89^^88 Asir-contrib	5
5	^^9f 榊^^8e(罔^^99 羣^^96^^87 醇^^95)	6
6	^^95(罔^^99 羣^^96^^95 医 ^^87 醇^^95).....	10
7	緇 ^^8d^^88^^86(罔^^99 羣^^96^^95 医 ^^87 醇^^95)	12
8	脛^^9a^^95(罔^^99 羣^^96^^95 医 ^^87 醇^^95)	13
9	^^89 号^^8a^^87 醇^^95(罔^^99 羣^^96^^95 医 ^^87 醇^^95) ..	14
10	茵^^8c^^88^^97(罔^^99 羣^^96^^95 医 ^^87 醇^^95)	15
11	Graphic(罔^^99 羣^^96^^95 医 ^^87 醇^^95)	18
12	茵 ず(罔^^99 羣^^96^^95 医 ^^87 醇^^95).....	19
13	糸^^9a^^a0^^85 縋^^8f(罔^^99 羣^^96^^95 医 ^^87 醇^^95) ..	23
14	茲^^87 箴^^93(罔^^99 羣^^96^^95 医 ^^87 醇^^95)	29
15	^^82 遑^^83 ^^83^^95^^82 c^^83^^83^^82 ^^83 ^^82や ^^83^^96^^83 ^^83(2 罫 ^^85^^83).....	30
16	Graphic Library (2 dimensional)	31
17	OpenXM-Contrib 箏^^80^^88 ^^87 醇^^95	33
18	OXshell ^^81 ^^96 ^^95.....	34
19	Asir ^^82 激^^82 鴻^^83^^86^^83^^a0 膊 ^^90^^86^^96 ^^95	35
20	箴水^^88 ^^81 ^^96 ^^95	36
21	^^81^^9d^^81 ^^96^^81 ^^83^^9e^^83^^8b^^83ヤ^^82 ^^83	38
脛	^^95.....	41

Table of Contents

1	^^81 ^^81^^98^^82^^81^^81	1
2	Asir/Contrib ^^81 ^^83 ^^83 若^^83^^89^^96 号 ^^95.....	3
3	Asir Contrib ^^81 ^^87 醇^^95 医^^90^^8d^^81 ^^81ゃ^^81^^84^^81.....	4
4	Windows ^^89^^88 Asir-contrib.....	5
5	^^9f 榊^^8e(岡^^99 羣^^96^^87 醇^^95).....	6
	5.0.1 base_cancel.....	6
	5.0.2 base_choose.....	6
	5.0.3 base_flatten.....	6
	5.0.4 base_intersection.....	6
	5.0.5 base_makelist.....	6
	5.0.6 base_memberq.....	7
	5.0.7 base_permutation.....	7
	5.0.8 base_position.....	7
	5.0.9 base_product.....	7
	5.0.10 base_prune.....	7
	5.0.11 base_rebuild_opt.....	7
	5.0.12 base_replace.....	8
	5.0.13 base_replace_n.....	8
	5.0.14 base_set_minus.....	8
	5.0.15 base_set_union.....	8
	5.0.16 base_subsetq.....	8
	5.0.17 base_subsets_of_size.....	8
	5.0.18 base_sum.....	9
	5.0.19 base_var_list.....	9
6	^^95(岡^^99 羣^^96^^95 医 ^^87 醇^^95).....	10
	6.0.1 number_abs.....	10
	6.0.2 number_ceiling.....	10
	6.0.3 number_eval.....	10
	6.0.4 number_factor.....	10
	6.0.5 number_float_to_rational.....	10
	6.0.6 number_floor.....	10
	6.0.7 number_imaginary_part.....	11
	6.0.8 number_is_integer.....	11
	6.0.9 number_real_part.....	11

7	縊 (岡^99 羣^96^95 医 ^87 醇^95)	12
8	脛 (岡^99 羣^96^95 医 ^87 醇^95) ..	13
9	号^8a^87 醇^95 (岡^99 羣^96^95 医 ^87 醇^95)	14
10	茵^8c^88^97 (岡^99 羣^96^95 医 ^87 醇^95)	15
10.0.1	matrix_adjugate	15
10.0.2	matrix_clone	15
10.0.3	matrix_det	15
10.0.4	matrix_diagonal_matrix	15
10.0.5	matrix_eigenvalues	15
10.0.6	matrix_gauge_transformation	15
10.0.7	matrix_identity_matrix	16
10.0.8	matrix_image	16
10.0.9	matrix_inner_product	16
10.0.10	matrix_inverse	16
10.0.11	matrix_kernel	16
10.0.12	matrix_list_to_matrix	16
10.0.13	matrix_matrix_to_list	17
10.0.14	matrix_rank	17
10.0.15	matrix_solve_linear	17
10.0.16	matrix_submatrix	17
10.0.17	matrix_transpose	17
11	Graphic (岡^99 羣^96^95 医 ^87 醇^95) ...	18
12	茵 ず (岡^99 羣^96^95 医 ^87 醇^95)	19
12.0.1	print_dvi_form	19
12.0.2	print_em	19
12.0.3	print_gif_form	19
12.0.4	print_input_form	19
12.0.5	print_open_math_tfb_form	19
12.0.6	print_open_math_xml_form	20
12.0.7	print_output	20
12.0.8	print_ox_rfc100_xml_form	20
12.0.9	print_png_form	20
12.0.10	print_terminal_form	20
12.0.11	print_tex_form	21
12.0.12	print_tfb_form	21
12.0.13	print_xdvi_form	21
12.0.14	print_xv_form	21

13	素^{9a}a⁰85 纒^{8f}(岡⁹⁹羣⁹⁶95 医 ⁸⁷醇⁹⁵)	23
13.0.1	poly_coefficient	23
13.0.2	poly_degree	23
13.0.3	poly_elimination_ideal	23
13.0.4	poly_expand	24
13.0.5	poly_factor	24
13.0.6	poly_gcd	24
13.0.7	poly_gr_w	24
13.0.8	poly_grobner_basis	24
13.0.9	poly_hilbert_polynomial	25
13.0.10	poly_ideal_colon	25
13.0.11	poly_ideal_intersection	25
13.0.12	poly_ideal_saturation	25
13.0.13	poly_in	26
13.0.14	poly_in_w	26
13.0.15	poly_in_w_	26
13.0.16	poly_initial	26
13.0.17	poly_initial_coefficients	27
13.0.18	poly_initial_term	27
13.0.19	poly_ord_w	27
13.0.20	poly_prime_dec	27
13.0.21	poly_r_omatrix	28
13.0.22	poly_solve_linear	28
13.0.23	poly_sort	28
13.0.24	poly_toric_ideal	28
13.0.25	poly_weight_to_omatrix	28
14	茲⁸⁷箴⁹³(岡⁹⁹羣⁹⁶95 医 ⁸⁷醇⁹⁵)	29
15	⁸²違⁸³ ⁸³95⁸² c⁸³83⁸² ⁸³ ⁸²ゃ⁸³96⁸³ ⁸³(2 電 ⁸⁵83)	30
16	Graphic Library (2 dimensional)	31
16.0.1	glib_clear	31
16.0.2	glib_flush	31
16.0.3	glib_line	31
16.0.4	glib_open	31
16.0.5	glib_plot	31
16.0.6	glib_print	31
16.0.7	glib_ps_form	32
16.0.8	glib_putpixel	32
16.0.9	glib_remove_last	32
16.0.10	glib_set_pixel_size	32
16.0.11	glib_tops	32
16.0.12	glib_window	32

17	OpenXM-Contrib 箏⁸⁰ 醇⁸⁷ 遺⁹⁵ ..	33
17.1	醇 ⁸⁷ 遺 ⁹⁵ 筍	33
17.1.1	ox_check_errors2	33
18	OXshell 箏⁸¹ 醇⁹⁶ 遺⁹⁵	34
18.0.1	oxshell.get_value	34
18.0.2	oxshell.oxshell	34
18.0.3	oxshell.set_value	34
19	Asir 激⁸² 鴻⁸³ 膊⁸³ 醇⁹⁰ 筍⁸⁶ 遺⁹⁶ 醇⁹⁵	35
19.0.1	asir_contrib_update	35
20	箏水⁸⁸ 箏⁸¹ 醇⁹⁶ 遺⁹⁵	36
20.0.1	util_damepathq	36
20.0.2	util_file_exists	36
20.0.3	util_filter	36
20.0.4	util_find_and_replace	36
20.0.5	util_find_start	36
20.0.6	util_find_substr	36
20.0.7	util_index	37
20.0.8	util_load_file_as_a_string	37
20.0.9	util_part	37
20.0.10	util_read_file_as_a_string	37
20.0.11	util_remove_cr	37
20.0.12	util_timing	37
20.0.13	util_v	37
20.0.14	util_write_string_to_a_file	37
21	箏⁸¹ 醇^{9d} 箏⁸¹ 醇⁹⁶ 箏⁸¹ 筍⁸³ 醇^{9e} 筍⁸³ 筍^{8b} 筍⁸³ 醇⁸² 筍⁸³	38
21.0.1	dsolv (Solving the initial ideal for holonomic systems) ...	38
21.0.2	ok_diff (Okutani's library for differential operators)	38
21.0.3	ok_dmodule (Okutani's library for D-modules)	38
21.0.4	(Plucker relations)	38
21.0.5	pfpcoh (Ohara's library for homology/cohomology groups for p F q)	38
21.0.6	(gnuplot ox server for graphics)	38
21.0.7	mathematica (Mathematica (TM) ox server)	38
21.0.8	om (om (java) ox server for translating CMO and OpenMath)	38
21.0.9	phc (PHC ox server for solving systems of algebraic equations by the homotopy method)	38
21.0.10	sm1 (Kan/sm1 ox server for the ring of differential operators)	38

21.0.11	tigers (tigers ox server for toric universal Grobner bases)	38
21.0.12	f_res (Comuting resultant).....	38
21.0.13	mt_graph (3D grapher).....	39
21.0.14	noro_mwl (Mordel Weil Lattice)	39
21.0.15	nn_ndbf (local b-function)	39
21.0.16	noro_pd (New Primary Ideal Decomposition)	39
21.0.17	ns_twistedlog (twisted logarithmic cohomology group) ..	39
21.0.18	nk_fb_gen_c (Fisher Bingham MLE).....	39
21.0.19	gtt_ekn (Two way contingency tables by HGM)	39
21.0.20	noro_module_syz (syzygies for modules)	39
21.0.21	n_wishartd (restriction of matrix 1F1).....	39
21.0.22	todo_parametrize	39
21.0.23	taji_alc	40
21.0.24	Texinfo 81 81 8184839e838b83ヤ 82 83, 茫969687 膈89.....	40
膾 95	41