

# OpenXM/Risa/Asir-Contrib

---

OpenXM/Risa/Asir-Contrib User's Manual (日本語版)  
Edition 1.3.1-15 for OpenXM/Asir2000  
April 2014

by OpenXM Developing Team

---

## 1 はじめに

数式処理システム asir は OpenXM プロトコル (Open message eXchange for Mathematics, <http://www.openxm.org>) をサポートしたサーバをコンポーネントとして利用できる. これらのサーバを呼ぶためのインタフェース関数はファイル ‘OpenXM/rc/asirrc’ をロードすることによりシステムに読み込まれる. Risa/Asir (OpenXM 配布版) では起動時に自動的にこのファイルが読まれる. Risa/Asir (OpenXM 配布版) は, このマニュアルでは OpenXM/Risa/Asir と呼ぶ. このマニュアルでは asir 用のこれらの関数およびユーザ言語で書かれた数学関数およびユーティリティ関数を説明する.

HEAD branch に同期した最新版の asir-contrib マニュアルは <http://www.math.kobe-u.ac.jp/OpenXM/Cur> を参照.

OpenXM プロトコルの技術的詳細については, ‘\$(OpenXM\_HOME)/doc/OpenXM-specs’ にあるファイル ‘openxm-jp.tex’ を見て下さい.

それでは, あなたの計算機上で数学をお楽しみ下さい.

List of contributors:

- Maekawa, Masahide (Oct., 1999 – : CVS server)
- Noro, Masayuki (Jan., 1996 – : OpenXM Protocol OXRFC-100, asir2000)
- Ohara, Katsuyoshi (Jan., 1998 – : ox\_math, oxc OXRFC-101)
- Takayama, Nobuki (Jan., 1996 – : OpenXM Protocol OXRFC-100, kan/sm1, asir-contrib)
- Tamura, Yasushi (Nov., 1998 – : OpenMath proxy, tfb)
- Fujimoto, Mitsushi (Windows)
- Iwane, Hidenao (Knapsack factorizer)
- Nakayama, Hiromasa (Gaussian elimination)
- Okutani, Yukio (Oct., 1999 – Feb., 2000 : matrix, diff, ...)
- Stillman, Mike (Macaulay 2 client and server)
- Tsai, Harrison (Macaulay 2 client and server)

この Contrib パッケージの著作権については, `OpenXM/Copyright` を見て下さい.  
有用だともいますが無保証です.

## 2 Asir/Contrib のロード方法.

‘OpenXM/rc/asirrc’ をロードすることにより Asir/Contrib の主な関数が利用可能となる. OpenXM/Risa/Asir では ASIR\_CONFIG 環境変数によりこのファイルを起動時に読みこんでいる. ‘names.rr’ が Asir/Contrib のトップレベルのファイルである. このファイルよりその他のファイルが読み込まれている. 一部のパッケージは ‘names.rr’ からは読み込まれないので, 明示的に読み込む必要がある.

A sample of ‘asirrc’ to use Asir/Contrib.

```
load("gr")$
load("primdec")$
load("katsura")$
load("bfct")$
load("names.rr")$
load("oxrffc103.rr")$
User_asirrc=which(getenv("HOME")+"/.asirrc")$
if (type(User_asirrc)!=0)
  if (!ctrl("quiet_mode")) print("Loading ~/.asirrc")$
  load(User_asirrc)$
else $
end$
```

### 3 Asir Contrib の関数名について

Asir Contrib には (1) 標準的な名前 で定義された数学函数 (`names.rr` および (2) Asir 標準函数以外の有用なライブラリ函数および (3) OpenXM サーバを `asir` から呼ぶための函数が含まれている。

Asir Contrib の関数名はモジュール化されているかまたは次の形をしている: カテゴリ名\_関数名

標準的な数学函数は実体へのラッパーである。たとえば `sm1.hilbert` は OpenXM サーバ `sm1` の Hilbert 函数の計算函数を呼び出す函数である。一方 `poly_hilbert_polynomial` は Asir Contrib の Hilbert 函数を計算するための (1) に属する標準的な関数名である。標準函数 `poly_hilbert_polynomial` は、現在 `sm1.hilbert` を呼び出して Hilbert 函数を計算しているが、これは将来変更されるかもしれない。たとえば、Asir 言語で記述された有用なライブラリ函数集 `commutativeRing.rr` が開発されて Hilbert 函数の計算函数 `commutativeRing_hilbert_polynomial` が含まれるようになったら、標準函数 `poly_hilbert_polynomial` は、`commutativeRing_hilbert_polynomial` を呼び出して Hilbert 函数を計算するようになるかもしれない。したがって、ユーザプログラムは標準数学函数名を用いるのが望ましい。

標準数学函数名は、OpenXM project において、全てのプロジェクトで共通の仕様を持つように努力している。たとえば、`kan/k0` も Asir Contrib と同様の標準数学函数名を持つ予定である。現在実験的に数学函数のカテゴリ `complex` 複体 (複素数でない) のマニュアルを `kan/k0`, `asir/contrib` で共通化を試みている。

以下の章は、標準数学函数の解説をおこない、それからライブラリ函数、それから、OpenXM サーバのインタフェースの説明をおこなう。

## 4 Windows 版 Asir-contrib

Windows でも不完全ながら asir-contrib が動作する。現在, 外部コンポーネント sm1 および, 外部コンポーネント を利用しない asir-contrib の関数が動作する。Cygwin 環境では外部コンポーネント sm1, phc が動作する。その他の外部コンポーネントは動作しない。

次の関数は Windows では動作しない。Windows での cygwin 環境では動作する場合がある。

- gnuplot.\*
- om.\*
- mathematica.\*
- phc.\*
- print\_dvi\_form
- print\_gif\_form
- print\_open\_math\_xml\_form
- print\_png\_form
- print\_xdvi\_form
- print\_xv\_form
- tigers\_xv\_form

## 5 基礎 (標準函数)

### 5.0.1 base\_cancel

`base_cancel(S)`

: It simplifies  $S$  by canceling the common factors of denominators and numerators.

Example:

```
base_cancel([(x-1)/(x^2-1), (x-1)/(x^3-1)]);
```

### 5.0.2 base\_choose

`base_choose(L,M)`

: It returns the list of the order  $M$  subsets of  $L$ .

Example:

```
base_choose([1,2,3],2);
```

It outputs all the order 2 subsets of the set  $\{1,2,3\}$

### 5.0.3 base\_flatten

`base_flatten(S)`

: It flattens a nested list  $S$ .

Example:

```
base_flatten([[1,2,3],4]);
```

### 5.0.4 base\_intersection

`base_intersection(A,B)`

: It returns the intersection of  $A$  and  $B$  as a set.

Example:

```
base_intersection([1,2,3],[2,3,5,[6,5]]);
```

### 5.0.5 base\_makelist

`base_makelist(Obj,K,B,T)`

: `base_makelist` generate a list from  $Obj$  where  $K$  runs in  $[B,T]$ . Options are `qt=1` (keep quote data), `step` (step size). When  $B$  is a list,  $T$  is ignored and  $K$  runs in  $B$ .

Example 0:

```
base_makelist(k^2,k,1,10);
```

Example 1:

```
map(print_input_form,base_makelist(quote(x^2),x,1,10 | qt=1, step=0.5))
```

Example 2:

```
base_makelist(quote("the "+k),k,["cat","dog"],0);
```

### 5.0.6 base\_memberq

`base_memberq(A,S)`

: It returns 1 if  $A$  is a member of the set  $S$  else returns 0.

Example:

```
base_memberq(2,[1,2,3]);
```

### 5.0.7 base\_permutation

`base_permutation(L)`

: It outputs all permutations of  $L$ . BUG; it uses a slow algorithm.

Example:

```
base_permutation([1,2,3,4]);
```

### 5.0.8 base\_position

`base_position(A,S)`

: It returns the position of  $A$  in  $S$ .

Example:

```
base_position("cat",["dog","cat","monkey"]);
```

### 5.0.9 base\_product

`base_product(Obj,K,B,T)`

: `base_product` returns the product of  $Obj$  where  $K$  runs in  $[B,T]$ . Options are `qt=1` (keep quote data), `step` (step size). When  $B$  is a list,  $K$  runs in  $B$  and  $T$  is ignored.

Example 0:

```
base_product(k^2,k,1,10);
```

Example 1:

```
base_product(quote(x^2),x,1,10 | qt=1, step=0.5);
```

Example 2:

```
base_product(quote(x^2),x,[a,b,c],0 | qt=1);
```

### 5.0.10 base\_prune

`base_prune(A,S)`

: It returns a list in which  $A$  is removed from  $S$ .

Example:

```
base_prune("cat",["dog","cat","monkey"]);
```

### 5.0.11 base\_rebuild\_opt

`base_rebuild_opt(Opt)`

: It rebuilt the option list  $Opt$

Example:

```
base_rebuild_opt([[key1,1],[key2,3]] | remove_keys=["key2"]);
it returns [[key1,1]]
```



**5.0.12 base\_replace**`base_replace(S, Rule)`: It rewrites  $S$  by using the rule  $Rule$ 

Example:

`base_replace(x^2+y^2, [[x,a+1],[y,b]]);` $x$  is replaced by  $a+1$  and  $y$  is replaced by  $b$  in  $x^2+y^2$ .**5.0.13 base\_replace\_n**`base_replace_n(S, Rule)`: It rewrites  $S$  by using the rule  $Rule$ . It is used only for specializing variables to numbers and faster than `base_replace`.

Example:

`base_replace_n(x^2+y^2, [[x,1/2],[y,2.0+3*@i]]);` $x$  is replaced by  $1/2$  and  $y$  is replaced by  $2.0+3*i$  in  $x^2+y^2$ .**5.0.14 base\_set\_minus**`base_set_minus(A, B)`:  $A \setminus B$ 

Example:

`base_set_minus([1,2,3],[3,4,5]);`**5.0.15 base\_set\_union**`base_set_union(A, B)`:  $A \cup B$ 

Example:

`base_set_union([1,2,3],[3,4,5]);`**5.0.16 base\_subsetq**`base_subsetq(A, B)`: if  $A \subseteq B$ , then it returns 1 else 0.

Example:

`base_subsetq([1,2],[1,2,3,4,5]);`**5.0.17 base\_subsets\_of\_size**`base_subsets_of_size(K, S)`: It outputs all subsets of  $S$  of the size  $K$ . BUG; it uses a slow algorithm. Do not input a large  $S$ .

Example:

`base_subsets_of_size(2,[3,5,3,2]);`

### 5.0.18 base\_sum

`base_sum(Obj, K, B, T)`

: `base_sum` returns the sum of `Obj` where `K` runs in `[B,T]`. Options are `qt=1` (keep quote data), `step` (step size). When `B` is a list, `K` runs in `B` and `T` is ignored. When `K` is 0, then `Obj` is assumed to be a list or vector and `Obj[B]+...+Obj[T]` is returned.

Example 0:

```
base_sum(k^2,k,1,10);
```

Example 1:

```
base_sum(quote(x^2),x,1,10 | qt=1, step=0.5);
```

Example 2:

```
base_sum(quote(x^2),x,[a,b,c],0 | qt=1);
```

### 5.0.19 base\_var\_list

`base_var_list(Name, B, T)`

: `base_var_list` generate a list of variables `Name+Index` where `Index` runs on `[B,T]`.

Example 0:

```
base_var_list(x,0,10);
```

Example 1:

```
base_var_list(x,1,4 | d = 1);
```

Options are `d=1` (add `d` before the name).

## 6 数 (標準数学函数)

### 6.0.1 number\_abs

`number_abs(X)`  
:

Example:

```
number_abs(-3);
```

### 6.0.2 number\_ceiling

`number_ceiling(X)`  
:

Example:

```
number_abs(1.5);
```

### 6.0.3 number\_factor

`number_factor(X)`  
: It factors the given integer X.

Example:

```
number_factor(20);
```

### 6.0.4 number\_float\_to\_rational

`number_float_to_rational(X)`  
:

Example:

```
number_float_to_rational(1.5234);  
number_float_to_rational(1.5234 | prec=14);
```

### 6.0.5 number\_floor

`number_floor(X)`  
:

Example:

```
number_floor(1.5);
```

### 6.0.6 number\_imaginary\_part

`number_imaginary_part(X)`  
:

Example:

```
number_imaginary_part(1+2*i);
```

**6.0.7 number\_is\_integer**

`number_is_integer(X)`  
:

Example:

`number_is_integer(2/3);`

**6.0.8 number\_real\_part**

`number_real_part(X)`  
:

Example:

`number_real_part(1+2*i);`

## 7 微積分 (標準数学函数)

## 8 級数 (標準数学函数)

## 9 特殊函数 (標準数学函数)

まだ書いてない.

## 10 行列 (標準数学函数)

### 10.0.1 matrix\_adjugate

`matrix_adjugate( $M$ )`

: It generates the adjugate matrix of the matrix  $M$ .

Example:

```
matrix_adjugate(matrix_list_to_matrix([[a,b],[c,d]]));
```

### 10.0.2 matrix\_clone

`matrix_clone( $M$ )`

: It generates the clone of the matrix  $M$ .

Example:

```
matrix_clone(matrix_list_to_matrix([[1,1],[0,1]]));
```

### 10.0.3 matrix\_det

`matrix_det( $M$ )`

: It returns the determinant of the matrix  $M$ .

Example:

```
poly_factor(matrix_det([[1,x,x^2],[1,y,y^2],[1,z,z^2]]));
```

### 10.0.4 matrix\_diagonal\_matrix

`matrix_diagonal_matrix( $L$ )`

: It returns the diagonal matrix with diagonal entries  $L$ .

Example:

```
matrix_diagonal_matrix([1,2,3]);
```

References:

```
matrix_list_to_matrix
```

### 10.0.5 matrix\_eigenvalues

`matrix_eigenvalues( $M$ )`

: It returns the eigenvalues of the matrix  $M$ .

Example:

```
matrix_eigenvalues([[x,1],[0,y]]);
```

### 10.0.6 matrix\_identity\_matrix

`matrix_identity_matrix( $N$ )`

: It returns the identity matrix of the size  $N$ .

Example:

```
matrix_identity_matrix(5);
```

References:

```
matrix_diagonal_matrix
```



### 10.0.7 matrix\_image

`matrix_image(M)`

: It computes the image of  $M$ . Redundant vectors are removed.

Example:

```
matrix_image([[1,2,3],[2,4,6],[1,0,0]]);
```

References:

`matrix_kernel`

### 10.0.8 matrix\_inner\_product

`matrix_inner_product(A,B)`

: It returns the inner product of two vectors  $A$  and  $B$ .

Example:

```
matrix_inner_product([1,2],[x,y]);
```

### 10.0.9 matrix\_inverse

`matrix_inverse(M)`

: It returns the inverse of the matrix  $M$ .

Example:

```
matrix_inverse([[1,2],[0,1]]);
```

### 10.0.10 matrix\_kernel

`matrix_kernel(M)`

: It returns the basis of the kernel of the matrix  $M$ .

Example:

```
matrix_kernel([[1,1,1,1],[0,1,3,4]]);
```

### 10.0.11 matrix\_list\_to\_matrix

`matrix_list_to_matrix(M)`

: It translates the list  $M$  to a matrix.

Example:

```
print_xdvi_form(matrix_list_to_matrix([[1,1],[0,2]]));
```

References:

`matrix_matrix_to_list`

### 10.0.12 matrix\_matrix\_to\_list

`matrix_matrix_to_list(M)`

: It translates the matrix  $M$  to a list.

References:

`matrix_list_to_matrix`

**10.0.13 matrix\_rank****matrix\_rank( $M$ )**: It returns the rank of the matrix  $M$ .

Example:

`matrix_rank([[1,1,1,1],[0,1,3,4]]);`**10.0.14 matrix\_solve\_linear****matrix\_solve\_linear( $M, X, B$ )**: It solves the system of linear equations  $M X = B$ 

Example:

`matrix_solve_linear([[1,2],[0,1]], [x,y], [1,2]);`**10.0.15 matrix\_submatrix****matrix\_submatrix( $M, Ind$ )**: It returns the submatrix of  $M$  defined by the index set  $Ind$ .

Example:

`matrix_submatrix([[0,1],[2,3],[4,5]], [1,2]);`**10.0.16 matrix\_transpose****matrix\_transpose( $M$ )**: It returns the transpose of the matrix  $M$ .

References:

`matrix_list_to_matrix`

## 11 Graphic(標準数学函数)

まだ書いてない.

## 12 表示 (標準数学函数)

### 12.0.1 print\_dvi\_form

`print_dvi_form(S)`

: It outputs  $S$  to a dvi file.

Example:

```
print_dvi_form(x^2-1);
```

References:

```
print_xdvi_form , print_tex_form
```

### 12.0.2 print\_em

`print_em(S)`

: It outputs  $S$  by a font to emphasize it.

Example:

```
print_em(x^2-1);
```

### 12.0.3 print\_gif\_form

`print_gif_form(S)`

: It outputs  $S$  to a file of the gif format.

`print_gif_form(S | table=key0)`

: This function allows optional variables *table*

Example:

```
print_gif_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));
```

References:

```
print_tex_form
```

### 12.0.4 print\_input\_form

`print_input_form(S)`

: It transforms  $S$  to a string which can be parsed by asir.

Example:

```
print_input_form(quote(x^3-1));
```

### 12.0.5 print\_open\_math\_tfb\_form

`print_open_math_tfb_form(S)`

: It transforms  $S$  to a tfb format of OpenMath XML.

Description:

It is experimental. You need to load `taka_print_tfb.rr` to call it.

Example:

```
print_open_math_tfb_form(quote(f(x,1/(y+1))+2));
```

### 12.0.6 print\_open\_math\_xml\_form

`print_open_math_xml_form(S)`

: It transforms  $S$  to a string which is compliant to OpenMath(1999).

Example:

```
print_open_math_xml_form(x^3-1);
```

References:

[www.openmath.org](http://www.openmath.org)

### 12.0.7 print\_output

`print_output(Obj)`

: It outputs the object  $Obj$  to a file. If the optional variable  $file$  is set, then it outputs the  $Obj$  to the specified file, else it outputs it to "asir\_output\_tmp.txt". If the optional variable  $mode$  is set to "w", then the file is newly created. If the optional variable is not set, the  $Obj$  is appended to the file.

`print_output(Obj | file=key0, mode=key1)`

: This function allows optional variables  $file$ ,  $mode$

Example:

```
print_output("Hello"|file="test.txt");
```

References:

`glib_tops`, ( , )

### 12.0.8 print\_ox\_rfc100\_xml\_form

`print_ox_rfc100_xml_form(S)`

: It transforms  $S$  to a string which is compliant to OpenXM RFC 100.

Example:

```
print_ox_rfc100_xml_form(x^3-1);
```

References:

[www.openxm.org](http://www.openxm.org)

### 12.0.9 print\_png\_form

`print_png_form(S)`

: It transforms  $S$  to a file of the format png. dvi png should be installed.

Example:

```
print_png_form(x^3-1);
```

References:

`print_tex_form`

### 12.0.10 print\_terminal\_form

`print_terminal_form(S)`

: It transforms  $S$  to the terminal form???

### 12.0.11 print\_tex\_form

`print_tex_form(S)`

: It transforms  $S$  to a string of the LaTeX format.

`print_tex_form(S | table=key0,raw=key1)`

: This function allows optional variables *table*, *raw*

Description:

The global variable `Print_tex_form_fraction_format` takes the values "auto", "frac", or "/". The global variable `Print_tex_form_no_automatic_subscript` takes the values 0 or 1. BUG; A large input  $S$  cannot be translated.

Example:

```
print_tex_form(x*dx+1 | table=[["dx","\partial_x"]]);
```

The optional variable *table* is used to give a translation table of asir symbols and tex symbols. when `AMSTeX = 1`, "begin pmatrix" and "end pmatrix" will be used to output matrix.

References:

`print_xdvi_form`

### 12.0.12 print\_tfb\_form

`print_tfb_form(S)`

: It transforms  $S$  to the tfb format.

Example:

```
print_tfb_form(x+1);
```

### 12.0.13 print\_xdvi\_form

`print_xdvi_form(S)`

: It transforms  $S$  to a xdvi file and previews the file by xdvi.

Example 0:

```
print_xdvi_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));
```

Example 1:

```
print_xdvi_form(print_tex_form(1/2));
```

References:

`print_tex_form`, `print_dvi_form`

### 12.0.14 print\_xv\_form

`print_xv_form(S)`

: It transforms  $S$  to a gif file and previews the file by xv.

`print_xv_form(S | input=key0,format=key1)`

: This function allows optional variables *input*, *format*

Example 0:

```
print_xv_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));
```

Example 1:

```
print_xv_form(x+y | format="png");
```

If the optional variable `format="png"` is set, png format will be used to generate an input for xv.

References:

```
print_tex_form , print_gif_form
```

## 13 多項式 (標準数学函数)

### 13.0.1 poly\_coefficient

`poly_coefficient(F, Deg, V)`

: It returns the coefficient of  $V^{\text{Deg}}$  in  $F$ .  $F$  may be rational or list or vector.

Example:

```
F=[(x+y+z)^10/z^2,(x-y+z)^10/z^3]$
poly_coefficient(F,10,x);
```

### 13.0.2 poly\_degree

`poly_degree(F)`

: It returns the degree of  $F$  with respect to the given weight vector.

`poly_degree(F | weight=key0, v=key1)`

: This function allows optional variables *weight*, *v*

Description:

The weight is given by the optional variable *weight*  $w$ . It returns  $\text{ord}_w(F)$

Example:

```
poly_degree(x^2+y^2-4 |weight=[100,1],v=[x,y]);
```

### 13.0.3 poly\_elimination\_ideal

`poly_elimination_ideal(I, VV)`

: It computes the intersection of the ideal  $I$  and the subring  $K[VV]$ .

`poly_elimination_ideal(I, VV |`

`grobner_basis=key0, v=key1, homo=key2, grace=key3, strategy=key4)`

: This function allows optional variables *grobner\_basis*, *v*, *homo*, *grace*, *strategy*

Description:

If *grobner\_basis* is "yes",  $I$  is assumed to be a Grobner basis. The optional variable *v* is a list of variables which defines the ring of polynomials.

Example 0:

```
poly_elimination_ideal([x^2+y^2-4,x*y-1],[x]);
```

Example 1:

```
A = poly_grobner_basis([x^2+y^2-4,x*y-1]|order=2,v=[y,x]);
poly_elimination_ideal(A,[x]|grobner_basis="yes");
```

When *strategy*=1(default),

*nd\_gr* is used when *trace*=0(default),

*nd\_gr\_trace* is used when *trace*=1.

References:

*gr*, *hgr*, *gr\_mod*, *dp\_\**



### 13.0.4 poly\_expand

`poly_expand(F)`

: This is an alias of `poly_sort`.

References:

`poly_sort`

### 13.0.5 poly\_factor

`poly_factor(F)`

: It factorizes the polynomial  $F$ .

Example:

```
poly_factor(x^10-y^10);
```

### 13.0.6 poly\_gcd

`poly_gcd(F,G)`

: It computes the polynomial GCD of  $F$  and  $G$ .

Example:

```
poly_gcd(x^10-y^10,x^25-y^25);
```

### 13.0.7 poly\_gr\_w

`poly_gr_w(F,V,W)`

: It returns the Grobner basis of  $F$  for the weight vector  $W$ . It is the second interface for `poly_grobner_basis`.

Example:

```
poly_gr_w([x^2+y^2-1,x*y-1],[x,y],[1,0]);
```

References:

`poly_in_w`, `poly_grobner_bais`

### 13.0.8 poly\_grobner\_basis

`poly_grobner_basis(I)`

: It returns the Grobner basis of  $I$ .

`poly_grobner_basis(I | order=key0,v=key1)`

: This function allows optional variables `order`, `v`

Description:

The optional variable `v` is a list of variables which defines the ring of polynomials.

Example:

```
A = poly_grobner_basis([x^2+y^2-4,x*y-1] | order=2,v=[y,x],str=1);
A->Generators;
A->Ring->Variables;
A->Ring->Order;
B = poly_grobner_basis([x^2+y^2-4,x*y-1] | order=[[10,1]],v=[y,x]);
C = poly_grobner_basis([x^2+y^2-4,x*y-1] | order=[block,[0,1],[0,1]],v=[y,x]);
```

### 13.0.9 poly\_hilbert\_polynomial

`poly_hilbert_polynomial(I)`  
: It returns the Hilbert polynomial of the ideal  $I$ .

`poly_hilbert_polynomial(I | s=key0, v=key1)`  
: This function allows optional variables  $s$ ,  $v$

Description:

The optional variable  $v$  is a list of variables.

Example:

```
poly_hilbert_polynomial([x1*y1,x1*y2,x2*y1,x2*y2] | s=k, v=[x1,x2,y1,y2]);
```

### 13.0.10 poly\_ideal\_colon

`poly_ideal_colon(I, J, V)`  
: It computes the colon ideal of  $I$  by  $J$   $V$  is the list of variables.

Example:

```
B=[(x+y+z)^50,(x-y+z)^50]$
V=[x,y,z]$
B=poly_ideal_colon(B, [(x+y+z)^49,(x-y+z)^49], V);
```

### 13.0.11 poly\_ideal\_intersection

`poly_ideal_intersection(I, J, V, Ord)`  
: It computes the intersection of the ideal  $I$  and  $J$   $V$  is the list of variables.  
 $Ord$  is the order.

Example:

```
A=[j*h*g*f*e*d*b,j*i*g*d*c*b,j*i*h*g*d*b,j*i*h*e*b,i*e*c*b,z]$
B=[a*d-j*c,b*c,d*e-f*g*h]$
V=[a,b,c,d,e,f,g,h,i,j,z]$
poly_ideal_intersection(A,B,V,0);
```

### 13.0.12 poly\_ideal\_saturation

`poly_ideal_saturation(I, J, V)`  
: It computes the saturation ideal of  $I$  by  $J$ .  $V$  is the list of variables.

Example:

```
B=[(x+y+z)^50,(x-y+z)^50]$
V=[x,y,z]$
B=poly_ideal_saturation(B, [(x+y+z)^49,(x-y+z)^49], V);
```

**13.0.13 poly\_in****poly\_in(*I*)**: It is an alias of `poly_initial()`.**poly\_in(*I* | *order*=key0, *v*=key1)**: This function allows optional variables *order*, *v*

Example:

`poly_in([x^2+y^2-4,x*y-1] | order=0, v=[x,y]);`**13.0.14 poly\_in\_w****poly\_in\_w(*F*, *V*, *W*)**: It returns the initial term or the initial ideal `in_w(F)` for the weight vector given by *order*. *F* is a single polynomial or a list of polynomials.**poly\_in\_w(*F*, *V*, *W* | *gb*=key0)**: This function allows optional variables *gb*

Example:

`poly_in_w([x^2+y^2-1,x*y-x] | v=[x,y], weight=[1,0]);`

References:

`poly_weight_to_omatrix`, `( , W , V , )`, `poly_grobner_basis`, `poly_gr_w`,  
`poly_in_w_`**13.0.15 poly\_in\_w\_****poly\_in\_w\_(*F*)**: It returns the initial term or the initial ideal `in_w(F)` for the weight vector given by *order*. *F* is a single polynomial or a list of polynomials. This is a new interface of `poly_in_w` with shorter args.**poly\_in\_w\_(*F* | *v*=key0, *weight*=key1, *gb*=key2)**: This function allows optional variables *v*, *weight*, *gb*

Example:

`poly_in_w_([x^2+y^2-1,x*y-x] | v=[x,y], weight=[1,0]);`

References:

`poly_weight_to_omatrix`, `( , W , V , )`, `poly_grobner_basis`, `poly_gr_w`**13.0.16 poly\_initial****poly\_initial(*I*)**: It returns the initial ideal of *I* with respect to the given order.**poly\_initial(*I* | *order*=key0, *v*=key1)**: This function allows optional variables *order*, *v*

Description:

The optional variable *v* is a list of variables. This function computes `in_<(I)`

Example:

`poly_initial([x^2+y^2-4,x*y-1] | order=0, v=[x,y]);`  
`poly_initial([x^2+y^2-4,x*y-1] | order=0, v=[x,y], gb=1);`

**13.0.17 poly\_initial\_coefficients****poly\_initial\_coefficients( $I$ )**: It computes the coefficients of the initial ideal of  $I$  with respect to the given order.**poly\_initial\_coefficients( $I$  | order=key0, v=key1)**: This function allows optional variables *order*, *v*

Description:

The optional variable *v* is a list of variables. The order is specified by the optional variable *order*

Example:

```
poly_initial_coefficients([x^2+y^2-4,x*y-1]|order=0,v=[x,y]);
```

**13.0.18 poly\_initial\_term****poly\_initial\_term( $F$ )**: It returns the initial term of a polynomial  $F$  with respect to the given weight vector.**poly\_initial\_term( $F$  | weight=key0, order=key1, v=key2)**: This function allows optional variables *weight*, *order*, *v*

Description:

The weight is given by the optional variable *weight* *w*. It returns  $\text{in}_w(F)$ 

Example:

```
poly_initial_term(x^2+y^2-4 |weight=[100,1],v=[x,y]);
```

**13.0.19 poly\_ord\_w****poly\_ord\_w( $F, V, W$ )**: It returns the order with respect to  $W$  of  $F$ .

Example:

```
poly_ord_w(x^2+y^2-1,[x,y],[1,3]);
```

References:

```
poly_in_w
```

**13.0.20 poly\_prime\_dec****poly\_prime\_dec( $I, V$ )**: It computes the prime ideal decomposition of the radical of  $I$ .  $V$  is a list of variables.

Example:

```
B=[x00*x11-x01*x10,x01*x12-x02*x11,x02*x13-x03*x12,x03*x14-x04*x13,
  -x11*x20+x21*x10,-x21*x12+x22*x11,-x22*x13+x23*x12,-x23*x14+x24*x13];
V=[x00,x01,x02,x03,x04,x10,x11,x12,x13,x14,x20,x21,x22,x23,x24];
poly_prime_dec(B,V | radical=1);
```

**13.0.21 poly\_r\_omatrix**`poly_r_omatrix(N)`

: It gives a weight matrix, which is used to compute a Grobner basis in  $K(x)\langle dx \rangle$ ,  $|x|=|dx|=N$ .

Example:

```
poly_r_omatrix(3);
```

References:

```
poly_weight_to_omatrix( , W, V, ) , ;
```

**13.0.22 poly\_solve\_linear**`poly_solve_linear(Eqs,V)`

: It solves the system of linear equations *Eqs* with respect to the set of variables *V*.

Example:

```
poly_solve_linear([2*x+3*y-z-2, x+y+z-1], [x,y,z]);
```

**13.0.23 poly\_sort**`poly_sort(F)`

: It expands *F* with a given variables *v*=*V* and a given weight *w*=*W*. It returns a quote object. If *truncate* option is set, the expansion is truncated at the given degree.

```
poly_sort(F | v=key0,w=key1,truncate=key2)
```

: This function allows optional variables *v*, *w*, *truncate*

Example:

```
poly_sort((x-y-a)^3 | v=[x,y], w=[-1,-1])
returns a series expansion in terms of x and y.
```

**13.0.24 poly\_toric\_ideal**`poly_toric_ideal(A,V)`

: It returns generators of the affine toric ideal defined by the matrix(list) *A*. *V* is the list of variables.

Example:

```
poly_toric_ideal([[1,1,1,1],[0,1,2,3]],base_var_list(x,0,3));
```

**13.0.25 poly\_weight\_to\_omatrix**`poly_weight_to_omatrix(W,V)`

: It translates the weight vector *W* into a matrix, which is used to set the order in asir Grobner basis functions. *V* is the list of variables.

Example:

```
M=poly_weight_to_omatrix([2,1,0],[x,y,z]);
nd_gr([x^3+z^3-1,x*y*z-1,y^2+z^2-1],[x,y,z],0,M);
```

## 14 複体 (標準数学函数)

## 15 グラフィックライブラリ (2 次元)

## 16 Graphic Library (2 dimensional)

ライブラリ `glib` は, Risa/Asir の グラフィック基本関数 (`draw_obj`) に対する, 昔の BASIC のような単純なインタフェースを提供する.

### 16.0.1 `glib_clear`

`glib_clear()`  
: Clear the screen.

### 16.0.2 `glib_flush`

`glib_flush()`  
: ; Flush the output. (Cfep only. It also set `initGL` to 1.).

### 16.0.3 `glib_line`

`glib_line(X0,Y0,X1,Y1)`  
: It draws the line  $[X0,Y0]$ –  $[X1,Y1]$  with *color* and *shape*

`glib_line(X0,Y0,X1,Y1 | color=key0,shape=key1)`  
: This function allows optional variables *color*, *shape*

Example:

```
glib_line(0,0,5,3/2 | color=0xff00ff);
glib_line(0,0,10,0 | shape=arrow);
```

### 16.0.4 `glib_open`

`glib_open()`  
: It starts the `ox-plot` server and opens a canvas. The canvas size is set to `Glib_canvas_x` X `Glib_canvas_y` (the default value is 400). This function is automatically called when the user calls `glib` functions.

### 16.0.5 `glib_plot`

`glib_plot(F)`  
: It plots an object *F* on the `glib` canvas.

Example 0:

```
glib_plot([[0,1],[0.1,0.9],[0.2,0.7],[0.3,0.5],[0.4,0.8]]);
```

Example 1:

```
glib_plot(tan(x));
```

### 16.0.6 `glib_print`

`glib_print(X,Y,Text)`  
: It put a string *Text* at  $[X,Y]$  on the `glib` canvas.

`glib_print(X,Y,Text | color=key0)`  
: This function allows optional variables *color*

Example:

```
glib_print(100,100,"Hello Worlds" | color=0xff0000);
```



**16.0.7 glib\_ps\_form****glib\_ps\_form(*S*)**: It returns the PS code generated by executing *S* (experimental).

Example 0:

```
glib_ps_form(quote( glib_line(0,0,100,100) ));
```

Example 1:

```
glib_ps_form(quote([glib_line(0,0,100,100),glib_line(100,0,0,100)]));
```

References:

**glib\_tops****16.0.8 glib\_putpixel****glib\_putpixel(*X,Y*)**: It puts a pixel at [*X,Y*] with *color***glib\_putpixel(*X,Y* | *color=key0*)**: This function allows optional variables *color*

Example:

```
glib_putpixel(1,2 | color=0xffff00);
```

**16.0.9 glib\_remove\_last****glib\_remove\_last()**: Remove the last object. **glib\_flush()** should also be called to remove the last object. (cfep only).**16.0.10 glib\_set\_pixel\_size****glib\_set\_pixel\_size(*P*)**: Set the size of putpixel to *P*. 1.0 is the default. (cfep only).**16.0.11 glib\_tops****glib\_tops()**: If **Glib\_ps** is set to 1, it returns a postscript program to draw the picture on the canvas.

References:

**print\_output****16.0.12 glib\_window****glib\_window(*Xmin,Ymin,Xmax,Ymax*)**: It generates a window with the left top corner [*Xmin,Ymin*] and the right bottom corner [*Xmax,Ymax*]. If the global variable *Glib\_math\_coordinate* is set to 1, mathematical coordinate system will be employed, i.e., the left top corner will have the coordinate [*Xmin,Ymax*].

Example:

```
glib_window(-1,-1,10,10);
```

## 17 OpenXM-Contrib 一般函数

### 17.1 函数一覧

#### 17.1.1 ox\_check\_errors2

`ox_check_errors2(p)`

:: 識別番号  $p$  のサーバのスタック上にあるエラーオブジェクトをリストで戻す.

*return* リスト

$p$  数

- 識別番号  $p$  のサーバのスタック上にあるエラーオブジェクトをリストで戻す.
- エラーオブジェクトのポップはしない.

```
[219] P=sm1.start();
```

```
0
```

```
[220] sm1.sm1(P," 0 get ");
```

```
0
```

```
[221] ox_check_errors2(P);
```

```
[error([7,4294967295,executeString: Usage:get])]
```

```
Error on the server of the process number = 1
```

```
To clean the stack of the ox server,
```

```
type in ox_pops(P,N) (P: process number, N: the number of data you need to pop)
out of the debug mode.
```

```
If you like to automatically clean data on the server stack,
```

```
set XM_debug=0;
```

## 18 OXshell の関数

OXshell はシステムのコマンドを `ox server` より実行する仕組みである。詳しくは `OpenXM/src/kan96xx/Doc/oxshell.oxw` および `OpenXM/doc/Papers/rims-2003-12-16-ja.tex` を見よ。

### 18.0.1 `oxshell.get_value`

`oxshell.get_value(NAME, V)`

: It get the value of the variable *NAME* on the server *ox\_shell*.

Example:

```
oxshell.set_value("abc", "Hello world!");
oxshell.oxshell(["cp", "stringIn://abc", "stringOut://result"]);
oxshell.get_value("result");
```

What we do is a file `$TMP/abc*` is generated with the contents `Hello world!` and `c`  
The contents of the file is stored in the variable `result` on `ox_sm1`.

References:

`oxshell.oxshell` , `oxshell.set_value`

### 18.0.2 `oxshell.oxshell`

`oxshell.oxshell(L)`

: It executes command *L* on a *ox\_shell* server. *L* must be an array. The result is the outputs to `stdout` and `stderr`. A temporary file will be generated under `$TMP`. cf. `oxshell.keep_tmp()`

Example:

```
oxshell.oxshell(["ls"]);
```

References:

`ox_shell` , `oxshell.set_value` , `oxshell.get_value` , `oxshell` , `of` , `sm1`.

### 18.0.3 `oxshell.set_value`

`oxshell.set_value(NAME, V)`

: It set the value *V* to the variable *Name* on the server *ox\_shell*.

Example:

```
oxshell.set_value("abc", "Hello world!");
oxshell.oxshell(["cat", "stringIn://abc"]);
```

References:

`oxshell.oxshell` , `oxshell.get_value`

## 19 Asir システム管理関数

### 19.0.1 asir\_contrib\_update

`asir_contrib_update()`

: It updates the asir-contrib library and/or some other files to the HEAD branch. The usage will be shown by `asir_contrib_update()` without the option `update`. Options are `update`, `clean`, `url`, `install_dir`, `zip_files`, `tmp`. Default values `update=0`, `clean=0`, `url="http://www.math.kobe-u.ac.jp/OpenXM/Current"`, `install_dir=%APPDATA%/OpenXM` (win) or `install_dir=$OpenXM_tmp/OpenXM` (others) `zip_files=["lib-asir-contrib.zip"]`

Example:

```
asir_contrib_update();  
asir_contrib_update(|update=1);    update the library  
asir_contrib_update(|update=3);    update the library and the documents  
asir_contrib_update(|clean=1);  
asir_contrib_update(|zip_files=["lib-asir-contrib.zip","doc-asir2000.zip","doc-a
```

## 20 便利な関数

システムの資源にアクセスするためおよび文字列処理の便利な関数を集めてある。

### 20.0.1 util\_damepathq

`util_damepathq(S)`

: When *S* is a string by the ShiftJIS code and *S* contains dame-moji with respect to \, it returns [a non-zero number, the string].

Example:

```
T = [0x5c,0xe4,0x5c,0x41,0x42]$  
T2=asciitostr(T)$  
util_damepathq(T2);
```

### 20.0.2 util\_file\_exists

`util_file_exists(Fname)`

: It returns 1 when *Fname* exists. It returns 0 when *Fname* does not exist.

### 20.0.3 util\_filter

`util_filter(Command,Input)`

: It executes the filter program *Command* with the *Input* and returns the output of the filter as a string.

`util_filter(Command,Input | env=key0)`

: This function allows optional variables *env*

Example:

```
util_filter("sort","cat\ndog\ncentipede\n");
```

### 20.0.4 util\_find\_and\_replace

`util_find_and_replace(W,S,Wnew)`

: It replaces *W* in *S* by *Wnew*. Arguments must be a list of ascii codes.

### 20.0.5 util\_find\_start

`util_find_start()`

: It tries to find the gnome-open command or an installed browser in unix systems. It returns "open" on MacOS X and returns "start" on Windows.

`util_find_start( | browser=key0)`

: This function allows optional variables *browser*

### 20.0.6 util\_find\_substr

`util_find_substr(W,S)`

: It returns the position of *W* in *S*. If *W* cannot be found, it returns -1. Arguments must be a list of ascii codes.

### 20.0.7 util\_index

`util_index(V)`

: It returns the name part and the index part of  $V$ .

Example:

```
util_index(x_2_3)
```

References:

`util_v`

### 20.0.8 util\_load\_file\_as\_a\_string

`util_load_file_as_a_string(F)`

: It reads a file  $F$  as a string.

### 20.0.9 util\_part

`util_part(S,P,Q)`

: It returns from  $P$ th element to  $Q$ th element of  $S$ .

### 20.0.10 util\_read\_file\_as\_a\_string

`util_read_file_as_a_string(F)`

: It reads a file  $F$  as a string.

### 20.0.11 util\_remove\_cr

`util_remove_cr(S)`

: It removes `cr`/`lf`/`tabs` from  $S$ . Arguments must be a list of ascii codes.

### 20.0.12 util\_timing

`util_timing(Q)`

: Show the timing data to execute  $Q$ .

Example:

```
util_timing( quote( fctr(x^50-y^50) ));
```

### 20.0.13 util\_v

`util_v(V,L)`

: It returns a variable indexed by  $L$ .

Example:

```
util_v("x",[1,3]);
```

References:

`util_index`

### 20.0.14 util\_write\_string\_to\_a\_file

`util_write_string_to_a_file(Fname,S)`

: It writes a string  $S$  to a file  $Fname$ .

## 21 その他のマニュアル

この節では asir-contrib のその他のマニュアルを紹介する。

それからまだ分類がおわっていない関数を解説する。これらの関数は将来は別の独立した節へ移す予定である。

### 21.0.1 dsolv (Solving the initial ideal for holonomic systems)

../dsolv-html/dsolv-ja.html

### 21.0.2 ok\_diff (Okutani's library for differential operators)

../ok\_diff-html/ok\_diff-ja.html

### 21.0.3 ok\_dmodule (Okutani's library for D-modules)

../ok\_dmodule-html/ok\_dmodule-ja.html

### 21.0.4 (Plucker relations)

../plucker-html/plucker-ja.html

### 21.0.5 pfpcoh (Ohara's library for homology/cohomology groups for $p$ F $q$ )

../pfpcoh-html/pfpcoh-ja.html

### 21.0.6 (gnuplot ox server for graphics)

../gnuplot-html/gnuplot-ja.html

### 21.0.7 mathematica (Mathematica (TM) ox server)

../mathematica-html/mathematica-ja.html

### 21.0.8 om (om (java) ox server for translating CMO and OpenMath)

../om-html/om-ja.html

### 21.0.9 phc (PHC ox server for solving systems of algebraic equations by the homotopy method)

../phc-html/phc-ja.html

### 21.0.10 sm1 (Kan/sm1 ox server for the ring of differential operators)

../sm1-html/sm1-ja.html

### 21.0.11 tigers (tigers ox server for toric universal Grobner bases)

../tigers-html/tigers-ja.html

**21.0.12 f\_res (Comuting resultant)**

../f\_res-html/f\_res-ja.html

**21.0.13 mt\_graph (3D grapher)**

../mk\_graph-html/mk\_graph-ja.html

**21.0.14 noro\_mwl (Mordel Weil Lattice)**

../noro\_mwl-html/noro\_mwl-ja.html

**21.0.15 nn\_ndbf (local b-function)**

../nn\_ndbf-html/nn\_ndbf-ja.html

**21.0.16 noro\_pd (New Primary Ideal Decomposition)**

../noro\_pd-html/noro\_pd-ja.html

**21.0.17 ns\_twistedlog (twisted logarithmic cohomology group)**

../ns\_twistedlog-html/ns\_twistedlog-ja.html

**21.0.18 nk\_fb\_gen\_c (Fisher Bingham MLE)**

../nk\_fb\_gen\_c-html/nk\_fb\_gen\_c-ja.html

**21.0.19 todo\_parametrize**

../todo\_parametrize-html/todo\_parametrize-ja.html

パッケージ `todo_parametrize/todo_parametrize.rr` をロードすることにより、有理曲線のパラメータ表示を見付ける関数である、`parametrize` が利用できるようになる。詳しくは See Section “概要” in *Risa/Asir* 代数曲線論用パッケージ説明書を見よ (Web 版 *Risa/Asir* 代数曲線論用パッケージ説明書 ([http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/asir-contrib/html-ja/todo\\_parametrize/todo\\_parametrize\\_ja\\_toc.html](http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/asir-contrib/html-ja/todo_parametrize/todo_parametrize_ja_toc.html))). このパッケージのマニュアルへの統合はまだできていない。このパッケージはまだ module 構造を利用していないので、既存のライブラリと名前の衝突の可能性がある。

```
[1205] load("todo_parametrize/todo_parametrize.rr");
1
[1425] parametrize(y^2-x^3);
[155*t^2+20*t+1,720*t^4+1044*t^3+580*t^2,155*t^4+20*t^3+t^2,(-x)/(y)]
[1426] parametrize(y^2+x^3);
[-t,1,t^3,(-x)/(y)]
```

**21.0.20 taji\_alc**

../taji\_alc-html/taji\_alc-ja.html

パッケージ `taji_alc.rr` をロードすることにより、一変数代数的コホモロジ群に関連する関数をロードできる。(Web 版 *Risa/Asir* 一変数代数的局所コホモロジ群に関する *Risa/Asir* パッケージ説明書 ([http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/asir-contrib/ja/taji\\_alc-html/taji\\_alc-ja\\_toc.html](http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/asir-contrib/ja/taji_alc-html/taji_alc-ja_toc.html))).



```
import("taji_alc.rr");  
taji_alc.laurent_expansion(x,(x-1)^3);
```

### 21.0.21 Texinfo でないマニュアル, 論文等.

OpenXM documents (<http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/index-doc-ja.html>).  
には texinfo で書かれていない asir-contrib のファイルや関数のマニュアル, および関連論文へのリンクがある.

(yang, fj\_curve, nk\_mora 等)

索引

(Index is nonexistent)

(Index is nonexistent)

## Short Contents

1	はじめに .....	1
2	Asir/Contrib のロード方法.....	3
3	Asir Contrib の関数名について .....	4
4	Windows 版 Asir-contrib .....	5
5	基礎 (標準関数) .....	6
6	数 (標準数学関数) .....	10
7	微積分 (標準数学関数) .....	12
8	級数 (標準数学関数) .....	13
9	特殊関数 (標準数学関数) .....	14
10	行列 (標準数学関数) .....	15
11	Graphic(標準数学関数) .....	18
12	表示 (標準数学関数) .....	19
13	多項式 (標準数学関数) .....	23
14	複体 (標準数学関数) .....	29
15	グラフィックライブラリ (2 次元) .....	30
16	Graphic Library (2 dimensional) .....	31
17	OpenXM-Contrib 一般関数 .....	33
18	OXshell の関数 .....	34
19	Asir システム管理関数 .....	35
20	便利な関数 .....	36
21	その他のマニュアル .....	38
	索引 .....	41

# Table of Contents

<b>1</b>	<b>はじめに</b> .....	<b>1</b>
<b>2</b>	<b>Asir/Contrib のロード方法</b> .....	<b>3</b>
<b>3</b>	<b>Asir Contrib の関数名について</b> .....	<b>4</b>
<b>4</b>	<b>Windows 版 Asir-contrib</b> .....	<b>5</b>
<b>5</b>	<b>基礎 (標準関数)</b> .....	<b>6</b>
5.0.1	base_cancel .....	6
5.0.2	base_choose .....	6
5.0.3	base_flatten .....	6
5.0.4	base_intersection .....	6
5.0.5	base_makelist .....	6
5.0.6	base_memberq .....	7
5.0.7	base_permutation .....	7
5.0.8	base_position .....	7
5.0.9	base_product .....	7
5.0.10	base_prune .....	7
5.0.11	base_rebuild_opt .....	7
5.0.12	base_replace .....	8
5.0.13	base_replace_n .....	8
5.0.14	base_set_minus .....	8
5.0.15	base_set_union .....	8
5.0.16	base_subsetq .....	8
5.0.17	base_subsets_of_size .....	8
5.0.18	base_sum .....	9
5.0.19	base_var_list .....	9
<b>6</b>	<b>数 (標準数学関数)</b> .....	<b>10</b>
6.0.1	number_abs .....	10
6.0.2	number_ceiling .....	10
6.0.3	number_factor .....	10
6.0.4	number_float_to_rational .....	10
6.0.5	number_floor .....	10
6.0.6	number_imaginary_part .....	10
6.0.7	number_is_integer .....	11
6.0.8	number_real_part .....	11
<b>7</b>	<b>微積分 (標準数学関数)</b> .....	<b>12</b>

<b>8</b>	<b>級数 (標準数学函数)</b>	<b>13</b>
<b>9</b>	<b>特殊函数 (標準数学函数)</b>	<b>14</b>
<b>10</b>	<b>行列 (標準数学函数)</b>	<b>15</b>
10.0.1	matrix_adjugate	15
10.0.2	matrix_clone	15
10.0.3	matrix_det	15
10.0.4	matrix_diagonal_matrix	15
10.0.5	matrix_eigenvalues	15
10.0.6	matrix_identity_matrix	15
10.0.7	matrix_image	16
10.0.8	matrix_inner_product	16
10.0.9	matrix_inverse	16
10.0.10	matrix_kernel	16
10.0.11	matrix_list_to_matrix	16
10.0.12	matrix_matrix_to_list	16
10.0.13	matrix_rank	17
10.0.14	matrix_solve_linear	17
10.0.15	matrix_submatrix	17
10.0.16	matrix_transpose	17
<b>11</b>	<b>Graphic (標準数学函数)</b>	<b>18</b>
<b>12</b>	<b>表示 (標準数学函数)</b>	<b>19</b>
12.0.1	print_dvi_form	19
12.0.2	print_em	19
12.0.3	print_gif_form	19
12.0.4	print_input_form	19
12.0.5	print_open_math_tfb_form	19
12.0.6	print_open_math_xml_form	20
12.0.7	print_output	20
12.0.8	print_ox_rfc100_xml_form	20
12.0.9	print_png_form	20
12.0.10	print_terminal_form	20
12.0.11	print_tex_form	21
12.0.12	print_tfb_form	21
12.0.13	print_xdvi_form	21
12.0.14	print_xv_form	21

<b>13</b>	<b>多項式 (標準数学函数)</b>	<b>23</b>
13.0.1	poly_coefficient	23
13.0.2	poly_degree	23
13.0.3	poly_elimination_ideal	23
13.0.4	poly_expand	24
13.0.5	poly_factor	24
13.0.6	poly_gcd	24
13.0.7	poly_gr_w	24
13.0.8	poly_grobner_basis	24
13.0.9	poly_hilbert_polynomial	25
13.0.10	poly_ideal_colon	25
13.0.11	poly_ideal_intersection	25
13.0.12	poly_ideal_saturation	25
13.0.13	poly_in	26
13.0.14	poly_in_w	26
13.0.15	poly_in_w_	26
13.0.16	poly_initial	26
13.0.17	poly_initial_coefficients	27
13.0.18	poly_initial_term	27
13.0.19	poly_ord_w	27
13.0.20	poly_prime_dec	27
13.0.21	poly_r_omatrix	28
13.0.22	poly_solve_linear	28
13.0.23	poly_sort	28
13.0.24	poly_toric_ideal	28
13.0.25	poly_weight_to_omatrix	28
<b>14</b>	<b>複体 (標準数学函数)</b>	<b>29</b>
<b>15</b>	<b>グラフィックライブラリ (2次元)</b>	<b>30</b>
<b>16</b>	<b>Graphic Library (2 dimensional)</b>	<b>31</b>
16.0.1	glib_clear	31
16.0.2	glib_flush	31
16.0.3	glib_line	31
16.0.4	glib_open	31
16.0.5	glib_plot	31
16.0.6	glib_print	31
16.0.7	glib_ps_form	32
16.0.8	glib_putpixel	32
16.0.9	glib_remove_last	32
16.0.10	glib_set_pixel_size	32
16.0.11	glib_tops	32
16.0.12	glib_window	32

<b>17</b>	<b>OpenXM-Contrib 一般函数</b>	<b>33</b>
17.1	函数一覧	33
17.1.1	ox_check_errors2	33
<b>18</b>	<b>OXshell の関数</b>	<b>34</b>
18.0.1	oxshell.get_value	34
18.0.2	oxshell.oxshell	34
18.0.3	oxshell.set_value	34
<b>19</b>	<b>Asir システム管理関数</b>	<b>35</b>
19.0.1	asir_contrib_update	35
<b>20</b>	<b>便利な関数</b>	<b>36</b>
20.0.1	util_damepathq	36
20.0.2	util_file_exists	36
20.0.3	util_filter	36
20.0.4	util_find_and_replace	36
20.0.5	util_find_start	36
20.0.6	util_find_substr	36
20.0.7	util_index	37
20.0.8	util_load_file_as_a_string	37
20.0.9	util_part	37
20.0.10	util_read_file_as_a_string	37
20.0.11	util_remove_cr	37
20.0.12	util_timing	37
20.0.13	util_v	37
20.0.14	util_write_string_to_a_file	37
<b>21</b>	<b>その他のマニュアル</b>	<b>38</b>
21.0.1	dsolv (Solving the initial ideal for holonomic systems)	38
21.0.2	ok_diff (Okutani's library for differential operators)	38
21.0.3	ok_dmodule (Okutani's library for D-modules)	38
21.0.4	(Plucker relations)	38
21.0.5	pfpcoh (Ohara's library for homology/cohomology groups for $p \neq q$ )	38
21.0.6	(gnuplot ox server for graphics)	38
21.0.7	mathematica (Mathematica (TM) ox server)	38
21.0.8	om (om (java) ox server for translating CMO and OpenMath)	38
21.0.9	phc (PHC ox server for solving systems of algebraic equations by the homotopy method)	38
21.0.10	sm1 (Kan/sm1 ox server for the ring of differential operators)	38
21.0.11	tigers (tigers ox server for toric universal Grobner bases)	38
21.0.12	f_res (Comuting resultant)	39
21.0.13	mt_graph (3D grapher)	39

21.0.14	noro_mwl (Mordel Weil Lattice) .....	39
21.0.15	nn_ndbf (local b-function) .....	39
21.0.16	noro_pd (New Primary Ideal Decomposition) .....	39
21.0.17	ns_twistedlog (twisted logarithmic cohomology group) ..	39
21.0.18	nk_fb_gen_c (Fisher Bingham MLE) .....	39
21.0.19	todo_parametrize .....	39
21.0.20	taji_alc .....	39
21.0.21	Texinfo でないマニュアル, 論文等 .....	40
索引 .....		<b>41</b>