

OpenXM/Risa/Asir-Contrib

OpenXM/Risa/Asir-Contrib User's Manual (English Edition)
Edition 1.3.2-3 for OpenXM/Asir2000
March 2017 (minor update on 18 February 2019)

by OpenXM Developing Team

1 Introduction

The computer algebra system `asir` can use servers, which support the `OpenXM` protocols (Open message eXchange for Mathematics, <http://www.openxm.org>), as components. The interface functions to call these servers are loaded by loading the file `OpenXM/rc/asirrc`. This file is automatically loaded in "Risa/Asir(OpenXM distribution)", which we call `OpenXM/Risa/Asir` in this document. This document explains these interface functions for `asir` and several mathematical and utility functions written in the user languages of Risa/Asir. These mathematical and utility functions are outcome of the Asir-contrib project.

The latest asir-contrib manual of the HEAD branch is at <http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/index-doc.html>

As to technical details on the `OpenXM` protocols, see `openxm-en.tex` at `$(OpenXM_HOME)/doc/OpenXM-specs`.

Enjoy mathematics on your computer.

List of contributors:

- Maekawa, Masahide (Oct., 1999 – : CVS server)
- Noro, Masayuki (Jan., 1996 – : OpenXM Protocol OXRFC-100, asir2000)
- Ohara, Katsuyoshi (Jan., 1998 – : ox-math, oxc OXRFC-101)
- Takayama, Nobuki (Jan., 1996 – : OpenXM Protocol OXRFC-100, kan/sm1, asir-contrib)
- Tamura, Yasushi (Nov., 1998 – : OpenMath proxy, tfb)
- Fujimoto, Mitsushi (Windows)
- Iwane, Hidenao (Knapsack factorizer)
- Nakayama, Hiromasa (Gaussian elimination)
- Okutani, Yukio (Oct., 1999 – Feb., 2000 : matrix, diff, ...)
- Stillman, Mike (Macaulay 2 client and server)
- Tsai, Harrison (Macaulay 2 client and server)

See `OpenXM/Copyright` for the copyright notice.

2 How to load Asir/Contrib

With loading `OpenXM/rc/asirrc`, we can use most functions in Asir/Contrib. The `OpenXM/Risa/Asir` reads this file, which is specified by the `ASIR_CONFIG` environmental variable, when it starts. The file `names.rr` is the top level file of the Asir/Contrib. Most other files are loaded from `names.rr`. Some packages are not loaded from `names.rr` and they must be loaded individually.

A sample of `asirrc` to use Asir/Contrib.

```
load("gr")$
load("primdec")$
load("katsura")$
load("bfct")$
load("names.rr")$
load("oxrfc103.rr")$
User_asirrc=which(getenv("HOME")+"/.asirrc")$
if (type(User_asirrc)!=0)
  if (!ctrl("quiet_mode")) print("Loading ~/.asirrc")$
  load(User_asirrc)$
else $
end$
```

3 Function Names in Asir Contrib

Not yet written.

Not yet written.

4 Asir-contrib for Windows

A part of Asir-contrib works on Windows. The following functions and components work on windows; the outer component sm1 and functions in asir-contrib which do not call outer components. In the cygwin environment, the outer components sm1, phc work. The other outer components do not work.

The following functions do not work on Windows. Some of them work in the cygwin environment of Windows.

- gnuplot.*
- om.*
- mathematica.*
- phc.*
- print_dvi_form
- print_gif_form
- print_open_math_xml_form
- print_png_form
- print_xdvi_form
- print_xv_form
- tigers_xv_form

5 Basic (Standard Functions)

5.0.1 base_cancel

`base_cancel(S)`

: It simplifies S by canceling the common factors of denominators and numerators.

Example:

```
base_cancel([(x-1)/(x^2-1), (x-1)/(x^3-1)]);
```

5.0.2 base_choose

`base_choose(L,M)`

: It returns the list of the order M subsets of L .

Example:

```
base_choose([1,2,3],2);
```

It outputs all the order 2 subsets of the set $\{1, 2, 3\}$

5.0.3 base_flatten

`base_flatten(S)`

: It flattens a nested list S .

Example:

```
base_flatten([[1,2,3],4]);
```

5.0.4 base_intersection

`base_intersection(A,B)`

: It returns the intersection of A and B as a set.

Example:

```
base_intersection([1,2,3],[2,3,5,[6,5]]);
```

5.0.5 base_makelist

`base_makelist(Obj,K,B,T)`

: `base_makelist` generate a list from `Obj` where K runs in $[B,T]$. Options are `qt=1` (keep quote data), `step` (step size). When B is a list, T is ignored and K runs in B .

Example 0:

```
base_makelist(k^2,k,1,10);
```

Example 1:

```
map(print_input_form,base_makelist(quote(x^2),x,1,10 | qt=1, step=0.5))
```

Example 2:

```
base_makelist(quote("the "+k),k,["cat","dog"],0);
```

5.0.6 base_memberq

`base_memberq(A,S)`

: It returns 1 if A is a member of the set S else returns 0.

Example:

```
base_memberq(2,[1,2,3]);
```

5.0.7 base_permutation

`base_permutation(L)`

: It outputs all permutations of L . BUG; it uses a slow algorithm.

Example:

```
base_permutation([1,2,3,4]);
```

5.0.8 base_position

`base_position(A,S)`

: It returns the position of A in S .

Example:

```
base_position("cat",["dog","cat","monkey"]);
```

5.0.9 base_product

`base_product(Obj,K,B,T)`

: `base_product` returns the product of Obj where K runs in $[B,T]$. Options are `qt=1` (keep quote data), `step` (step size). When B is a list, K runs in B and T is ignored.

Example 0:

```
base_product(k^2,k,1,10);
```

Example 1:

```
base_product(quote(x^2),x,1,10 | qt=1, step=0.5);
```

Example 2:

```
base_product(quote(x^2),x,[a,b,c],0 | qt=1);
```

5.0.10 base_prune

`base_prune(A,S)`

: It returns a list in which A is removed from S .

Example:

```
base_prune("cat",["dog","cat","monkey"]);
```

5.0.11 base_rebuild_opt

`base_rebuild_opt(Opt)`

: It rebuilt the option list Opt

Example:

```
base_rebuild_opt([[key1,1],[key2,3]] | remove_keys=["key2"]);
```

it returns `[[key1,1]]`

5.0.12 base_replace**base_replace(*S*,*Rule*)**: It rewrites *S* by using the rule *Rule*

Example:

`base_replace(x^2+y^2, [[x,a+1],[y,b]]);`x is replaced by a+1 and y is replaced by b in x^2+y^2 .**5.0.13 base_replace_n****base_replace_n(*S*,*Rule*)**: It rewrites *S* by using the rule *Rule*. It is used only for specializing variables to numbers and faster than base_replace.

Example:

`base_replace_n(x^2+y^2, [[x,1/2],[y,2.0+3*i]]);`x is replaced by 1/2 and y is replaced by $2.0+3*i$ in x^2+y^2 .**5.0.14 base_set_minus****base_set_minus(*A*,*B*)**: $A \setminus B$

Example:

`base_set_minus([1,2,3],[3,4,5]);`**5.0.15 base_set_union****base_set_union(*A*,*B*)**: $A \cup B$

Example:

`base_set_union([1,2,3],[3,4,5]);`**5.0.16 base_subsetq****base_subsetq(*A*,*B*)**: if $A \subseteq B$, then it returns 1 else 0.

Example:

`base_subsetq([1,2],[1,2,3,4,5]);`**5.0.17 base_subsets_of_size****base_subsets_of_size(*K*,*S*)**: It outputs all subsets of *S* of the size *K*. BUG; it uses a slow algorithm. Do not input a large *S*.

Example:

`base_subsets_of_size(2,[3,5,3,2]);`

5.0.18 base_sum

`base_sum(Obj, K, B, T)`

: `base_sum` returns the sum of `Obj` where `K` runs in `[B,T]`. Options are `qt=1` (keep quote data), `step` (step size). When `B` is a list, `K` runs in `B` and `T` is ignored. When `K` is 0, then `Obj` is assumed to be a list or vector and `Obj[B]+...+Obj[T]` is returned.

Example 0:

```
base_sum(k^2,k,1,10);
```

Example 1:

```
base_sum(quote(x^2),x,1,10 | qt=1, step=0.5);
```

Example 2:

```
base_sum(quote(x^2),x,[a,b,c],0 | qt=1);
```

5.0.19 base_var_list

`base_var_list(Name, B, T)`

: `base_var_list` generate a list of variables `Name+Index` where `Index` runs on `[B,T]`.

Example 0:

```
base_var_list(x,0,10);
```

Example 1:

```
base_var_list(x,1,4 | d = 1);
```

Options are `d=1` (add `d` before the name).

6 Numbers (Standard Mathematical Functions)

6.0.1 number_abs

`number_abs(X)`
 :

Example:

```
number_abs(-3);
```

6.0.2 number_ceiling

`number_ceiling(X)`
 :

Example:

```
number_abs(1.5);
```

6.0.3 number_eval

`number_eval(X)`
 :

Example:

```
number_eval([1/10^10,@pi,exp(1)]);
```

6.0.4 number_factor

`number_factor(X)`
 : It factors the given integer X .

Example:

```
number_factor(20);
```

6.0.5 number_float_to_rational

`number_float_to_rational(X)`
 :

Example:

```
number_float_to_rational(1.5234);
number_float_to_rational(1.5234 | prec=14);
```

6.0.6 number_floor

`number_floor(X)`
 :

Example:

```
number_floor(1.5);
```

6.0.7 `number_imaginary_part`

`number_imaginary_part(X)`
:

Example:

```
number_imaginary_part(1+2*@i);
```

6.0.8 `number_is_integer`

`number_is_integer(X)`
:

Example:

```
number_is_integer(2/3);
```

6.0.9 `number_real_part`

`number_real_part(X)`
:

Example:

```
number_real_part(1+2*@i);
```

7 Calculus (Standard Mathematical Functions)

8 Series (Standard Mathematical Functions)

9 Special Functions (Standard Mathematical Functions)

Not yet written

10 Matrix (Standard Mathematical Functions)

10.0.1 matrix_adjugate

`matrix_adjugate(M)`
: It generates the adjugate matrix of the matrix M .

Example:

```
matrix_adjugate(matrix_list_to_matrix([[a,b],[c,d]]));
```

10.0.2 matrix_clone

`matrix_clone(M)`
: It generates the clone of the matrix M .

Example:

```
matrix_clone(matrix_list_to_matrix([[1,1],[0,1]]));
```

10.0.3 matrix_det

`matrix_det(M)`
: It returns the determinant of the matrix M .

Example:

```
poly_factor(matrix_det([[1,x,x^2],[1,y,y^2],[1,z,z^2]]));
```

10.0.4 matrix_diagonal_matrix

`matrix_diagonal_matrix(L)`
: It returns the diagonal matrix with diagonal entries L .

Example:

```
matrix_diagonal_matrix([1,2,3]);
```

References:

```
matrix_list_to_matrix
```

10.0.5 matrix_eigenvalues

`matrix_eigenvalues(M)`
: It returns the eigenvalues of the matrix M . if the option `num=1`, it returns the numerical approximate eigenvalues.

Example:

```
matrix_eigenvalues([[x,1],[0,y]]);
```

10.0.6 matrix_gauge_transformation

`matrix_gauge_transformation(M, T, V)`
: It returns $T^{-1} M T - T^{-1} dT/dV$

Example:

```
matrix_gauge_transformation([[0,x],[1,x]], [[x,0],[0,1]], x);
```


10.0.7 matrix_identity_matrix**matrix_identity_matrix(*N*)**: It returns the identity matrix of the size *N*.

Example:

`matrix_identity_matrix(5);`

References:

`matrix_diagonal_matrix`**10.0.8 matrix_ij****matrix_ij(*N*, *II*, *JJ*)**: It returns the matrix for exchanging *II*-th row(col) and *JJ*-th row(col).

Example:

`matrix_ij(4,0,2);`**10.0.9 matrix_image****matrix_image(*M*)**: It computes the image of *M*. Redundant vectors are removed.

Example:

`matrix_image([[1,2,3],[2,4,6],[1,0,0]]);`

References:

`matrix_kernel`**10.0.10 matrix_inner_product****matrix_inner_product(*A*, *B*)**: It returns the inner product of two vectors *A* and *B*.

Example:

`matrix_inner_product([1,2],[x,y]);`**10.0.11 matrix_inverse****matrix_inverse(*M*)**: It returns the inverse of the matrix *M*.

Example:

`matrix_inverse([[1,2],[0,1]]);`**10.0.12 matrix_inverse_singular****matrix_inverse_singular(*Mat*)**: It returns a quasi-inverse matrix of *Mat* when it has 0-row and 0-column.

Example:

`matrix_inverse_singular(newmat(3,3,[[1,0,2],[0,0,0],[3,0,4]]));`

10.0.13 matrix_kernel`matrix_kernel(M)`: It returns the basis of the kernel of the matrix *M*.

Example:

`matrix_kernel([[1,1,1,1],[0,1,3,4]]);`**10.0.14 matrix_list_to_matrix**`matrix_list_to_matrix(M)`: It translates the list *M* to a matrix.

Example:

`print_xdvi_form(matrix_list_to_matrix([[1,1],[0,2]]));`

References:

`matrix_matrix_to_list`**10.0.15 matrix_matrix_to_list**`matrix_matrix_to_list(M)`: It translates the matrix *M* to a list.

References:

`matrix_list_to_matrix`**10.0.16 matrix_rank**`matrix_rank(M)`: It returns the rank of the matrix *M*.

Example:

`matrix_rank([[1,1,1,1],[0,1,3,4]]);`**10.0.17 matrix_solve_linear**`matrix_solve_linear(M,X,B)`: It solves the system of linear equations $M X = B$

Example:

`matrix_solve_linear([[1,2],[0,1]],[x,y],[1,2]);`**10.0.18 matrix_submatrix**`matrix_submatrix(M,Ind)`: It returns the submatrix of *M* defined by the index set *Ind*.

Example:

`matrix_submatrix([[0,1],[2,3],[4,5]],[1,2]);`

10.0.19 `matrix_transpose``matrix_transpose(M)`: It returns the transpose of the matrix M .

References:

`matrix_list_to_matrix`

11 Graphic (Standard Mathematical Functions)

Not yet written.

12 Print (Standard Mathematical Functions)

12.0.1 print_dvi_form

`print_dvi_form(S)`
 : It outputs *S* to a dvi file.

Example:

```
print_dvi_form(x^2-1);
```

References:

```
print_xdvi_form , print_tex_form
```

12.0.2 print_em

`print_em(S)`
 : It outputs *S* by a font to emphasize it.

Example:

```
print_em(x^2-1);
```

12.0.3 print_gif_form

`print_gif_form(S)`
 : It outputs *S* to a file of the gif format.

`print_gif_form(S | table=key0)`
 : This function allows optional variables *table*

Example:

```
print_gif_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));
```

References:

```
print_tex_form
```

12.0.4 print_input_form

`print_input_form(S)`
 : It transforms *S* to a string which can be parsed by asir.

Example:

```
print_input_form(quote(x^3-1));
```

12.0.5 print_open_math_tfb_form

`print_open_math_tfb_form(S)`
 : It transforms *S* to a tfb format of OpenMath XML.

Description:

It is experimental. You need to load `taka_print_tfb.rr` to call it.

Example:

```
print_open_math_tfb_form(quote(f(x,1/(y+1))+2));
```

12.0.6 `print_open_math_xml_form`

`print_open_math_xml_form(S)`

: It transforms S to a string which is compliant to OpenMath(1999).

Example:

```
print_open_math_xml_form(x^3-1);
```

References:

www.openmath.org

12.0.7 `print_output`

`print_output(Obj)`

: It outputs the object Obj to a file. If the optional variable *file* is set, then it outputs the Obj to the specified file, else it outputs it to "asir_output_tmp.txt". If the optional variable *mode* is set to "w", then the file is newly created. If the optional variable is not set, the Obj is appended to the file.

`print_output(Obj | file=key0, mode=key1)`

: This function allows optional variables *file*, *mode*

Example:

```
print_output("Hello"|file="test.txt");
```

References:

`glib_tops` , (,)

12.0.8 `print_ox_rfc100_xml_form`

`print_ox_rfc100_xml_form(S)`

: It transforms S to a string which is compliant to OpenXM RFC 100.

Example:

```
print_ox_rfc100_xml_form(x^3-1);
```

References:

www.openxm.org

12.0.9 `print_png_form`

`print_png_form(S)`

: It transforms S to a file of the format png. dvi2png should be installed.

Example:

```
print_png_form(x^3-1);
```

References:

`print_tex_form`

12.0.10 `print_terminal_form`

`print_terminal_form(S)`

: It transforms S to the terminal form???

12.0.11 print_tex_form

`print_tex_form(S)`

: It transforms S to a string of the LaTeX format.

`print_tex_form(S | table=key0,raw=key1)`

: This function allows optional variables *table*, *raw*

Description:

The global variable `Print_tex_form_fraction_format` takes the values "auto", "frac", or "/". The global variable `Print_tex_form_no_automatic_subscript` takes the values 0 or 1. BUG; A large input S cannot be translated.

Example:

```
print_tex_form(x*dx+1 | table=[["dx","\partial_x"]]);
```

The optional variable *table* is used to give a translation table of asir symbols and tex symbols. when `AMSTeX = 1`, "begin pmatrix" and "end pmatrix" will be used to output matrix.

References:

`print_xdvi_form`

12.0.12 print_tfb_form

`print_tfb_form(S)`

: It transforms S to the tfb format.

Example:

```
print_tfb_form(x+1);
```

12.0.13 print_xdvi_form

`print_xdvi_form(S)`

: It transforms S to a xdvi file and previews the file by xdvi.

Example 0:

```
print_xdvi_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));
```

Example 1:

```
print_xdvi_form(print_tex_form(1/2));
```

References:

`print_tex_form`, `print_dvi_form`

12.0.14 print_xv_form

`print_xv_form(S)`

: It transforms S to a gif file and previews the file by xv.

`print_xv_form(S | input=key0,format=key1)`

: This function allows optional variables *input*, *format*

Example 0:

```
print_xv_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));
```

Example 1:

```
print_xv_form(x+y | format="png");
```

If the optional variable `format="png"` is set, png format will be used to generate an input for xv.

References:

```
print_tex_form , print_gif_form
```


13 Polynomials (Standard Mathematical Functions)

13.0.1 poly_coefficient

`poly_coefficient(F, Deg, V)`

: It returns the coefficient of V^{Deg} in F . F may be rational or list or vector.

Example:

```
F=[(x+y+z)^10/z^2,(x-y+z)^10/z^3]$
poly_coefficient(F,10,x);
```

13.0.2 poly_degree

`poly_degree(F)`

: It returns the degree of F with respect to the given weight vector.

`poly_degree(F | weight=key0, v=key1)`

: This function allows optional variables *weight*, *v*

Description:

The weight is given by the optional variable *weight* w . It returns $\text{ord}_w(F)$

Example:

```
poly_degree(x^2+y^2-4 |weight=[100,1],v=[x,y]);
```

13.0.3 poly_elimination_ideal

`poly_elimination_ideal(I, VV)`

: It computes the intersection of the ideal I and the subring $K[VV]$.

`poly_elimination_ideal(I, VV |`

`grobner_basis=key0, v=key1, homo=key2, grace=key3, strategy=key4)`

: This function allows optional variables *grobner_basis*, *v*, *homo*, *grace*, *strategy*

Description:

If *grobner_basis* is "yes", I is assumed to be a Grobner basis. The optional variable *v* is a list of variables which defines the ring of polynomials.

Example 0:

```
poly_elimination_ideal([x^2+y^2-4,x*y-1],[x]);
```

Example 1:

```
A = poly_grobner_basis([x^2+y^2-4,x*y-1]|order=2,v=[y,x]);
poly_elimination_ideal(A,[x]|grobner_basis="yes");
```

When *strategy*=1(default),

nd_gr is used when *trace*=0(default),

nd_gr_trace is used when *trace*=1.

References:

gr , *hgr* , *gr_mod* , *dp_**

13.0.4 poly_expand`poly_expand(F)`: This is an alias of `poly_sort`.

References:

`poly_sort`**13.0.5 poly_factor**`poly_factor(F)`: It factorizes the polynomial F .

Example:

`poly_factor(x^10-y^10);`**13.0.6 poly_gcd**`poly_gcd(F,G)`: It computes the polynomial GCD of F and G .

Example:

`poly_gcd(x^10-y^10,x^25-y^25);`**13.0.7 poly_gr_w**`poly_gr_w(F,V,W)`: It returns the Grobner basis of F for the weight vector W . It is the second interface for `poly_grobner_basis`.

Example:

`poly_gr_w([x^2+y^2-1,x*y-1],[x,y],[1,0]);`

References:

`poly_in_w`, `poly_grobner_bais`**13.0.8 poly_grobner_basis**`poly_grobner_basis(I)`: It returns the Grobner basis of I .`poly_grobner_basis(I | order=key0,v=key1)`: This function allows optional variables *order*, *v*

Description:

The optional variable *v* is a list of variables which defines the ring of polynomials.

Example:

```
A = poly_grobner_basis([x^2+y^2-4,x*y-1]|order=2,v=[y,x],str=1);
A->Generators;
A->Ring->Variables;
A->Ring->Order;
B = poly_grobner_basis([x^2+y^2-4,x*y-1]|order=[[10,1]],v=[y,x]);
C = poly_grobner_basis([x^2+y^2-4,x*y-1]|order=[block,[0,1],[0,1]],v=[y,x]);
```

13.0.9 poly_hilbert_polynomial

`poly_hilbert_polynomial(I)`
 : It returns the Hilbert polynomial of the ideal I .

`poly_hilbert_polynomial(I | s=key0, v=key1)`
 : This function allows optional variables s , v

Description:

The optional variable v is a list of variables.

Example:

```
poly_hilbert_polynomial([x1*y1,x1*y2,x2*y1,x2*y2] | s=k, v=[x1,x2,y1,y2]);
```

13.0.10 poly_ideal_colon

`poly_ideal_colon(I, J, V)`
 : It computes the colon ideal of I by J V is the list of variables.

Example:

```
B=[(x+y+z)^50, (x-y+z)^50]$
V=[x,y,z]$
B=poly_ideal_colon(B, [(x+y+z)^49, (x-y+z)^49], V);
```

13.0.11 poly_ideal_intersection

`poly_ideal_intersection(I, J, V, Ord)`
 : It computes the intersection of the ideal I and J V is the list of variables.
 Ord is the order.

Example:

```
A=[j*h*g*f*e*d*b, j*i*g*d*c*b, j*i*h*g*d*b, j*i*h*e*b, i*e*c*b, z]$
B=[a*d-j*c, b*c, d*e-f*g*h]$
V=[a,b,c,d,e,f,g,h,i,j,z]$
poly_ideal_intersection(A,B,V,0);
```

13.0.12 poly_ideal_saturation

`poly_ideal_saturation(I, J, V)`
 : It computes the saturation ideal of I by J . V is the list of variables.

Example:

```
B=[(x+y+z)^50, (x-y+z)^50]$
V=[x,y,z]$
B=poly_ideal_saturation(B, [(x+y+z)^49, (x-y+z)^49], V);
```

13.0.13 poly_in**poly_in(*I*)**: It is an alias of `poly_initial()`.**poly_in(*I* | *order*=key0, *v*=key1)**: This function allows optional variables *order*, *v*

Example:

`poly_in([x^2+y^2-4,x*y-1]|order=0,v=[x,y]);`**13.0.14 poly_in_w****poly_in_w(*F*, *V*, *W*)**: It returns the initial term or the initial ideal `in_w(F)` for the weight vector given by *order*. *F* is a single polynomial or a list of polynomials.**poly_in_w(*F*, *V*, *W* | *gb*=key0)**: This function allows optional variables *gb*

Example:

`poly_in_w([x^2+y^2-1,x*y-x] , [x,y] , [1,0]);`

References:

`poly_weight_to_omatrix , (, W , V ,) , poly_grobner_basis , poly_gr_w ,
poly_in_w_`**13.0.15 poly_in_w_****poly_in_w_(*F*)**: It returns the initial term or the initial ideal `in_w(F)` for the weight vector given by *order*. *F* is a single polynomial or a list of polynomials. This is a new interface of `poly_in_w` with shorter args.**poly_in_w_(*F* | *v*=key0, *weight*=key1, *gb*=key2)**: This function allows optional variables *v*, *weight*, *gb*

Example:

`poly_in_w_([x^2+y^2-1,x*y-x] | v=[x,y],weight=[1,0]);`

References:

`poly_weight_to_omatrix , (, W , V ,) , poly_grobner_basis , poly_gr_w`**13.0.16 poly_initial****poly_initial(*I*)**: It returns the initial ideal of *I* with respect to the given order.**poly_initial(*I* | *order*=key0, *v*=key1)**: This function allows optional variables *order*, *v*

Description:

The optional variable *v* is a list of variables. This function computes `in_<(I)`

Example:

`poly_initial([x^2+y^2-4,x*y-1]|order=0,v=[x,y]);
poly_initial([x^2+y^2-4,x*y-1]|order=0,v=[x,y],gb=1);`

13.0.17 poly_initial_coefficients

`poly_initial_coefficients(I)`
 : It computes the coefficients of the initial ideal of I with respect to the given order.

`poly_initial_coefficients(I | order=key0, v=key1)`
 : This function allows optional variables *order*, *v*

Description:

The optional variable *v* is a list of variables. The order is specified by the optional variable *order*

Example:

```
poly_initial_coefficients([x^2+y^2-4,x*y-1]|order=0,v=[x,y]);
```

13.0.18 poly_initial_term

`poly_initial_term(F)`
 : It returns the initial term of a polynomial F with respect to the given weight vector.

`poly_initial_term(F | weight=key0, order=key1, v=key2)`
 : This function allows optional variables *weight*, *order*, *v*

Description:

The weight is given by the optional variable *weight* *w*. It returns $\text{in}_w(F)$

Example:

```
poly_initial_term( x^2+y^2-4 |weight=[100,1],v=[x,y]);
```

13.0.19 poly_ord_w

`poly_ord_w(F, V, W)`
 : It returns the order with respect to W of F .

Example:

```
poly_ord_w(x^2+y^2-1,[x,y],[1,3]);
```

References:

`poly_in_w`

13.0.20 poly_prime_dec

`poly_prime_dec(I, V)`
 : It computes the prime ideal decomposition of the radical of I . V is a list of variables.

Example:

```
B=[x00*x11-x01*x10,x01*x12-x02*x11,x02*x13-x03*x12,x03*x14-x04*x13,
  -x11*x20+x21*x10,-x21*x12+x22*x11,-x22*x13+x23*x12,-x23*x14+x24*x13];
V=[x00,x01,x02,x03,x04,x10,x11,x12,x13,x14,x20,x21,x22,x23,x24];
poly_prime_dec(B,V | radical=1);
```

13.0.21 poly_r_omatrix`poly_r_omatrix(N)`

: It gives a weight matrix, which is used to compute a Grobner basis in $K(x)\langle dx \rangle$, $|x|=|dx|=N$.

Example:

```
poly_r_omatrix(3);
```

References:

```
poly_weight_to_omatrix, (, W, V, ), ;
```

13.0.22 poly_solve_linear`poly_solve_linear(Eqs,V)`

: It solves the system of linear equations *Eqs* with respect to the set of variables *V*.

Example:

```
poly_solve_linear([2*x+3*y-z-2, x+y+z-1], [x,y,z]);
```

13.0.23 poly_sort`poly_sort(F)`

: It expands *F* with a given variables *v*=*V* and a given weight *w*=*W*. It returns a quote object. If *truncate* option is set, the expansion is truncated at the given degree.

`poly_sort(F | v=key0,w=key1,truncate=key2)`

: This function allows optional variables *v*, *w*, *truncate*

Example:

```
poly_sort((x-y-a)^3 | v=[x,y], w=[-1,-1])
returns a series expansion in terms of x and y.
```

13.0.24 poly_toric_ideal`poly_toric_ideal(A,V)`

: It returns generators of the affine toric ideal defined by the matrix(list) *A*. *V* is the list of variables.

Example:

```
poly_toric_ideal([[1,1,1,1],[0,1,2,3]],base_var_list(x,0,3));
```

13.0.25 poly_weight_to_omatrix`poly_weight_to_omatrix(W,V)`

: It translates the weight vector *W* into a matrix, which is used to set the order in asir Grobner basis functions. *V* is the list of variables.

Example:

```
M=poly_weight_to_omatrix([2,1,0],[x,y,z]);
nd_gr([x^3+z^3-1,x*y*z-1,y^2+z^2-1,[x,y,z],0,M);
```

14 Complex (Standard Mathematical Functions)

15 Graphic Library (2 dimensional)

The library `glib` provides a simple interface like old BASIC to the graphic primitive (`draw_obj`) of Risa/Asir.

15.0.1 `glib_clear`

`glib_clear()`
: Clear the screen.

15.0.2 `glib_flush`

`glib_flush()`
: ; Flush the output. (Cfep only. It also set `initGL` to 1.).

15.0.3 `glib_line`

`glib_line(X0,Y0,X1,Y1)`
: It draws the line $[X0,Y0]$ – $[X1,Y1]$ with *color* and *shape*
`glib_line(X0,Y0,X1,Y1 | color=key0,shape=key1)`
: This function allows optional variables *color*, *shape*

Example:

```
glib_line(0,0,5,3/2 | color=0xff00ff);
glib_line(0,0,10,0 | shape=arrow);
```

15.0.4 `glib_open`

`glib_open()`
: It starts the `ox_plot` server and opens a canvas. The canvas size is set to `Glib_canvas_x` X `Glib_canvas_y` (the default value is 400). This function is automatically called when the user calls `glib` functions.

15.0.5 `glib_plot`

`glib_plot(F)`
: It plots an object *F* on the `glib` canvas.

Example 0:

```
glib_plot([[0,1],[0.1,0.9],[0.2,0.7],[0.3,0.5],[0.4,0.8]]);
```

Example 1:

```
glib_plot(tan(x));
```

15.0.6 `glib_print`

`glib_print(X,Y,Text)`
: It put a string *Text* at $[X,Y]$ on the `glib` canvas.

`glib_print(X,Y,Text | color=key0)`
: This function allows optional variables *color*

Example:

```
glib_print(100,100,"Hello Worlds" | color=0xff0000);
```


15.0.7 glib_ps_form

`glib_ps_form(S)`

: It returns the PS code generated by executing *S* (experimental).

Example 0:

```
glib_ps_form(quote( glib_line(0,0,100,100) ));
```

Example 1:

```
glib_ps_form(quote([glib_line(0,0,100,100),glib_line(100,0,0,100)]));
```

References:

`glib_tops`

15.0.8 glib_putpixel

`glib_putpixel(X,Y)`

: It puts a pixel at [*X*,*Y*] with *color*

`glib_putpixel(X,Y | color=key0)`

: This function allows optional variables *color*

Example:

```
glib_putpixel(1,2 | color=0xffff00);
```

15.0.9 glib_remove_last

`glib_remove_last()`

: Remove the last object. `glib_flush()` should also be called to remove the last object. (cfep only).

15.0.10 glib_set_pixel_size

`glib_set_pixel_size(P)`

: Set the size of putpixel to *P*. 1.0 is the default. (cfep only).

15.0.11 glib_tops

`glib_tops()`

: If `Glib_ps` is set to 1, it returns a postscript program to draw the picture on the canvas.

References:

`print_output`

15.0.12 glib_window

`glib_window(Xmin,Ymin,Xmax,Ymax)`

: It generates a window with the left top corner [*Xmin*,*Ymin*] and the right bottom corner [*Xmax*,*Ymax*]. If the global variable *Glib_math_coordinate* is set to 1, mathematical coordinate system will be employed, i.e., the left top corner will have the coordinate [*Xmin*,*Ymax*].

Example:

```
glib_window(-1,-1,10,10);
```

16 OpenXM-Contrib General Functions

16.1 Functions

16.1.1 ox_check_errors2

`ox_check_errors2(p)`

:: get a list of error objects on the stack of the server *p*.

return List

p Number

- It gets a list of error objects on the server stack.
- It does not pop the error objects.

```
[219] P=sm1.start();
```

```
0
```

```
[220] sm1.sm1(P," 0 get ");
```

```
0
```

```
[221] ox_check_errors2(P);
```

```
[error([7,4294967295,executeString: Usage:get])]
```

```
Error on the server of the process number = 1
```

```
To clean the stack of the ox server,
```

```
type in ox_pops(P,N) (P: process number, N: the number of data you need to pop)
out of the debug mode.
```

```
If you like to automatically clean data on the server stack,
```

```
set XM_debug=0;
```

17 OXshell Functions

OXshell is a system to execute system commands from ox servers. As to details, see the files OpenXM/src/kan96xx/Doc/oxshell.oxw and OpenXM/doc/Papers/rims-2003-12-16-ja.tex.

17.0.1 oxshell.get_value

`oxshell.get_value(NAME, V)`

: It get the value of the variable *NAME* on the server *ox_shell*.

Example:

```
oxshell.set_value("abc", "Hello world!");
oxshell.oxshell(["cp", "stringIn://abc", "stringOut://result"]);
oxshell.get_value("result");
```

What we do is a file \$TMP/abc* is generated with the contents Hello world! and copi

The contents of the file is stored in the variable result on *ox_sm1*.

References:

oxshell.oxshell , *oxshell.set_value*

17.0.2 oxshell.oxshell

`oxshell.oxshell(L)`

: It executes command *L* on a *ox_shell* server. *L* must be an array. The result is the outputs to stdout and stderr. A temporary file will be generated under \$TMP. cf. *oxshell.keep_tmp()*

Example:

```
oxshell.oxshell(["ls"]);
```

References:

ox_shell , *oxshell.set_value* , *oxshell.get_value* , *oxshell* , *of* , *sm1*.

17.0.3 oxshell.set_value

`oxshell.set_value(NAME, V)`

: It set the value *V* to the variable *Name* on the server *ox_shell*.

Example:

```
oxshell.set_value("abc", "Hello world!");
oxshell.oxshell(["cat", "stringIn://abc"]);
```

References:

oxshell.oxshell , *oxshell.get_value*

18 Asir System Utility Functions

18.0.1 asir_contrib_update

`asir_contrib_update()`

: It updates the asir-contrib library and/or some other files to the HEAD branch. The usage will be shown by `asir_contrib_update()` without the option `update`. Options are `update`, `clean`, `url`, `install_dir`, `zip_files`, `tmp`. Default values `update=0`, `clean=0`, `url="http://www.math.kobe-u.ac.jp/OpenXM/Current"`, `install_dir=%APPDATA%/OpenXM` (win) or `install_dir=$OpenXM_tmp/OpenXM` (others) `zip_files=["lib-asir-contrib.zip"]`

Example:

```
asir_contrib_update();
asir_contrib_update(|update=1);    update the library
asir_contrib_update(|update=3);    update the library and the documents
asir_contrib_update(|clean=1);
asir_contrib_update(|zip_files=["lib-asir-contrib.zip","doc-asir2000.zip","doc-asir
```

19 Utility Functions

Utility functions provide some useful functions to access to the system and to process strings.

19.0.1 util_damepathq

`util_damepathq(S)`

: When *S* is a string by the ShiftJIS code and *S* contains dame-moji with respect to \, it returns [a non-zero number, the string].

Example:

```
T = [0x5c,0xe4,0x5c,0x41,0x42]$
T2=asciitostr(T)$
util_damepathq(T2);
```

19.0.2 util_file_exists

`util_file_exists(Fname)`

: It returns 1 when *Fname* exists. It returns 0 when *Fname* does not exist.

19.0.3 util_filter

`util_filter(Command,Input)`

: It executes the filter program *Command* with the *Input* and returns the output of the filter as a string.

`util_filter(Command,Input | env=key0)`

: This function allows optional variables *env*

Example:

```
util_filter("sort","cat\ndog\ncentipede\n");
```

19.0.4 util_find_and_replace

`util_find_and_replace(W,S,Wnew)`

: It replaces *W* in *S* by *Wnew*. Arguments must be a list of ascii codes.

19.0.5 util_find_start

`util_find_start()`

: It tries to find the gnome-open command or an installed browser in unix systems. It returns "open" on MacOS X and returns "start" on Windows.

`util_find_start(| browser=key0)`

: This function allows optional variables *browser*

19.0.6 util_find_substr

`util_find_substr(W,S)`

: It returns the position of *W* in *S*. If *W* cannot be found, it returns -1. Arguments must be a list of ascii codes.

19.0.7 util_index

`util_index(V)`

: It returns the name part and the index part of V .

Example:

```
util_index(x_2_3)
```

References:

`util_v`

19.0.8 util_load_file_as_a_string

`util_load_file_as_a_string(F)`

: It reads a file F as a string.

19.0.9 util_part

`util_part(S,P,Q)`

: It returns from P th element to Q th element of S .

19.0.10 util_read_file_as_a_string

`util_read_file_as_a_string(F)`

: It reads a file F as a string.

19.0.11 util_remove_cr

`util_remove_cr(S)`

: It removes `cr`/`lf`/`tabs` from S . Arguments must be a list of ascii codes.

19.0.12 util_timing

`util_timing(Q)`

: Show the timing data to execute Q .

Example:

```
util_timing( quote( fctr(x^50-y^50) ));
```

19.0.13 util_v

`util_v(V,L)`

: It returns a variable indexed by L .

Example:

```
util_v("x",[1,3]);
```

References:

`util_index`

19.0.14 util_write_string_to_a_file

`util_write_string_to_a_file(Fname,S)`

: It writes a string S to a file $Fname$.

20 Other Manuals

This section introduces other manuals in the asir-contrib project.

This section also describes functions that have not yet been classified. These will be moved to independent sections in a future.

20.0.1 dsolv (Solving the initial ideal for holonomic systems)

`../dsolv-html/dsolv-en.html`

20.0.2 ok_diff (Okutani's library for differential operators)

`../ok_diff-html/ok_diff-en.html`

20.0.3 ok_dmodule (Okutani's library for D-modules)

`../ok_dmodule-html/ok_dmodule-en.html`

20.0.4 (Plucker relations)

`../plucker-html/plucker-en.html`

20.0.5 pfpcoh (Ohara's library for homology/cohomology groups for $p \leq q$)

`../pfpcoh-html/pfpcoh-en.html`

20.0.6 (gnuplot ox server for graphics)

`../gnuplot-html/gnuplot-en.html`

20.0.7 mathematica (Mathematica (TM) ox server)

`../mathematica-html/mathematica-en.html`

20.0.8 om (om (java) ox server for translating CMO and OpenMath)

`../om-html/om-en.html`

20.0.9 phc (PHC ox server for solving systems of algebraic equations by the homotopy method)

`../phc-html/phc-en.html`

20.0.10 sm1 (Kan/sm1 ox server for the ring of differential operators)

`../sm1-html/sm1-en.html`

20.0.11 tigers (tigers ox server for toric universal Grobner bases)

`../tigers-html/tigers-en.html`

20.0.12 f_res (Comuting resultant)

../f_res-html/f_res-en.html

20.0.13 mt_graph (3D grapher)

../mk_graph-html/mk_graph-en.html

20.0.14 noro_mwl (Mordel Weil Lattice)

../noro_mwl-html/noro_mwl-en.html

20.0.15 nn_ndbf (local b-function)

../nn_ndbf-html/nn_ndbf-en.html

20.0.16 ns_twistedlog (twisted logarithmic cohomology group)

../ns_twistedlog-html/ns_twistedlog-en.html

20.0.17 nk_fb_gen_c (Fisher Bingham MLE)

../nk_fb_gen_c-html/nk_fb_gen_c-en.html

20.0.18 gtt_ekn (Two way contingency tables by HGM)

../gtt_ekn-html/gtt_ekn-en.html

20.0.19 noro_module_syz (syzygies for modules)

../noro_module_syz-html/noro_module_syz-en.html

20.0.20 n_wishartd (restriction of matrix 1F1)

../n_wishartd-html/n_wishartd-en.html

20.0.21 [[todo_parametrize]]

todo_parametrize/todo_parametrize-toc

With loading the file `todo_parametrize/todo_parametrize.rr` the function `parametrize` is installed. The function finds a parametric expression of a given rational curve. As to details, see *See A package for algebraic curves* (in Japanese).

```
[1205] load("todo_parametrize/todo_parametrize.rr");
1
[1425] parametrize(y^2-x^3);
[155*t^2+20*t+1,720*t^4+1044*t^3+580*t^2,155*t^4+20*t^3+t^2,(-x)/(y)]
[1426] parametrize(y^2+x^3);
[-t,1,t^3,(-x)/(y)]
```

20.0.22 taji_alc

With loading the file `taji_alc.rr` functions for algebraic local cohomology groups in one variable are imported.

```
import("taji_alc.rr");
taji_alc.laurent_expansion(x,(x-1)^3);
```


20.0.23 Manual and papers which are not written in texinfo.

Links to manuals and papers related to files and commands in asir-contrib are at OpenXM documents (<http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/index-doc-en.html>).

Index

(Index is nonexistent)

(Index is nonexistent)

Short Contents

1	Introduction.....	1
2	How to load Asir/Contrib.....	3
3	Function Names in Asir Contrib.....	4
4	Asir-contrib for Windows	5
5	Basic (Standard Functions)	6
6	Numbers (Standard Mathematical Functions).....	10
7	Calculus (Standard Mathematical Functions)	12
8	Series (Standard Mathematical Functions)	13
9	Special Functions (Standard Mathematical Functions).....	14
10	Matrix (Standard Mathematical Functions)	15
11	Graphic (Standard Mathematical Functions)	19
12	Print (Standard Mathematical Functions).....	20
13	Polynomials (Standard Mathematical Functions)	24
14	Complex (Standard Mathematical Functions).....	30
15	Graphic Library (2 dimensional)	31
16	OpenXM-Contrib General Functions	33
17	OXshell Functions	34
18	Asir System Utility Functions.....	35
19	Utility Functions	36
20	Other Manuals.....	38
	Index	41

Table of Contents

1	Introduction	1
2	How to load Asir/Contrib	3
3	Function Names in Asir Contrib	4
4	Asir-contrib for Windows	5
5	Basic (Standard Functions)	6
5.0.1	base_cancel	6
5.0.2	base_choose	6
5.0.3	base_flatten	6
5.0.4	base_intersection	6
5.0.5	base_makelist	6
5.0.6	base_memberq	7
5.0.7	base_permutation	7
5.0.8	base_position	7
5.0.9	base_product	7
5.0.10	base_prune	7
5.0.11	base_rebuild_opt	7
5.0.12	base_replace	8
5.0.13	base_replace_n	8
5.0.14	base_set_minus	8
5.0.15	base_set_union	8
5.0.16	base_subsetq	8
5.0.17	base_subsets_of_size	8
5.0.18	base_sum	9
5.0.19	base_var_list	9
6	Numbers (Standard Mathematical Functions) ..	10
6.0.1	number_abs	10
6.0.2	number_ceiling	10
6.0.3	number_eval	10
6.0.4	number_factor	10
6.0.5	number_float_to_rational	10
6.0.6	number_floor	10
6.0.7	number_imaginary_part	11
6.0.8	number_is_integer	11
6.0.9	number_real_part	11
7	Calculus (Standard Mathematical Functions) ..	12

8	Series (Standard Mathematical Functions)...	13
9	Special Functions (Standard Mathematical Functions)	14
10	Matrix (Standard Mathematical Functions) ..	15
10.0.1	matrix_adjugate	15
10.0.2	matrix_clone	15
10.0.3	matrix_det	15
10.0.4	matrix_diagonal_matrix	15
10.0.5	matrix_eigenvalues	15
10.0.6	matrix_gauge_transformation	15
10.0.7	matrix_identity_matrix	16
10.0.8	matrix_ij	16
10.0.9	matrix_image	16
10.0.10	matrix_inner_product	16
10.0.11	matrix_inverse	16
10.0.12	matrix_inverse_singular	16
10.0.13	matrix_kernel	17
10.0.14	matrix_list_to_matrix	17
10.0.15	matrix_matrix_to_list	17
10.0.16	matrix_rank	17
10.0.17	matrix_solve_linear	17
10.0.18	matrix_submatrix	17
10.0.19	matrix_transpose	18
11	Graphic (Standard Mathematical Functions) ..	19
12	Print (Standard Mathematical Functions) ..	20
12.0.1	print_dvi_form	20
12.0.2	print_em	20
12.0.3	print_gif_form	20
12.0.4	print_input_form	20
12.0.5	print_open_math_tfb_form	20
12.0.6	print_open_math_xml_form	21
12.0.7	print_output	21
12.0.8	print_ox_rfc100_xml_form	21
12.0.9	print_png_form	21
12.0.10	print_terminal_form	21
12.0.11	print_tex_form	22
12.0.12	print_tfb_form	22
12.0.13	print_xdvi_form	22
12.0.14	print_xv_form	22

13	Polynomials (Standard Mathematical Functions) ..	24
13.0.1	poly_coefficient	24
13.0.2	poly_degree	24
13.0.3	poly_elimination_ideal	24
13.0.4	poly_expand	25
13.0.5	poly_factor	25
13.0.6	poly_gcd	25
13.0.7	poly_gr_w	25
13.0.8	poly_grobner_basis	25
13.0.9	poly_hilbert_polynomial	26
13.0.10	poly_ideal_colon	26
13.0.11	poly_ideal_intersection	26
13.0.12	poly_ideal_saturation	26
13.0.13	poly_in	27
13.0.14	poly_in_w	27
13.0.15	poly_in_w_	27
13.0.16	poly_initial	27
13.0.17	poly_initial_coefficients	28
13.0.18	poly_initial_term	28
13.0.19	poly_ord_w	28
13.0.20	poly_prime_dec	28
13.0.21	poly_r_omatrix	29
13.0.22	poly_solve_linear	29
13.0.23	poly_sort	29
13.0.24	poly_toric_ideal	29
13.0.25	poly_weight_to_omatrix	29
14	Complex (Standard Mathematical Functions) ..	30
15	Graphic Library (2 dimensional)	31
15.0.1	glib_clear	31
15.0.2	glib_flush	31
15.0.3	glib_line	31
15.0.4	glib_open	31
15.0.5	glib_plot	31
15.0.6	glib_print	31
15.0.7	glib_ps_form	32
15.0.8	glib_putpixel	32
15.0.9	glib_remove_last	32
15.0.10	glib_set_pixel_size	32
15.0.11	glib_tops	32
15.0.12	glib_window	32
16	OpenXM-Contrib General Functions	33
16.1	Functions	33
16.1.1	ox_check_errors2	33

17	OXshell Functions	34
17.0.1	oxshell.get_value	34
17.0.2	oxshell.oxshell	34
17.0.3	oxshell.set_value	34
18	Asir System Utility Functions	35
18.0.1	asir_contrib_update	35
19	Utility Functions	36
19.0.1	util_damepathq	36
19.0.2	util_file_exists	36
19.0.3	util_filter	36
19.0.4	util_find_and_replace	36
19.0.5	util_find_start	36
19.0.6	util_find_substr	36
19.0.7	util_index	37
19.0.8	util_load_file_as_a_string	37
19.0.9	util_part	37
19.0.10	util_read_file_as_a_string	37
19.0.11	util_remove_cr	37
19.0.12	util_timing	37
19.0.13	util_v	37
19.0.14	util_write_string_to_a_file	37
20	Other Manuals	38
20.0.1	dsolv (Solving the initial ideal for holonomic systems)	38
20.0.2	ok_diff (Okutani's library for differential operators)	38
20.0.3	ok_dmodule (Okutani's library for D-modules)	38
20.0.4	(Plucker relations)	38
20.0.5	pfpcoh (Ohara's library for homology/cohomology groups for $p \mid F_q$)	38
20.0.6	(gnuplot ox server for graphics)	38
20.0.7	mathematica (Mathematica (TM) ox server)	38
20.0.8	om (om (java) ox server for translating CMO and OpenMath)	38
20.0.9	phc (PHC ox server for solving systems of algebraic equations by the homotopy method)	38
20.0.10	sm1 (Kan/sm1 ox server for the ring of differential operators)	38
20.0.11	tigers (tigers ox server for toric universal Grobner bases)	38
20.0.12	f_res (Comuting resultant)	39
20.0.13	mt_graph (3D grapher)	39
20.0.14	noro_mwl (Mordel Weil Lattice)	39
20.0.15	nn_ndbf (local b-function)	39
20.0.16	ns_twistedlog (twisted logarithmic cohomology group)	39
20.0.17	nk_fb_gen_c (Fisher Bingham MLE)	39
20.0.18	gtt_ekn (Two way contingency tables by HGM)	39

20.0.19	<code>noromodule-syz</code> (syzygies for modules).....	39
20.0.20	<code>n-wishartd</code> (restriction of matrix 1F1)	39
20.0.21	<code>[[todo-parametrize]]</code>	39
20.0.22	<code>taji-alc</code>	39
20.0.23	Manual and papers which are not written in texinfo.	40
Index		41

