

PHC OX server Manual

Edition : auto generated by oxgentexi on 29 August 2011

1 PHC Functions

This chapter describes interface functions for PHC pack ox server `ox_sm1_phc`. These interface functions are defined in the file `'phc.rr'`. The file `phc` is at `'$(OpenXM_HOME)/lib/asir-contrib'`.

```
[255] phc.start();
0
[257] phc.phc([x^2+y^2-4,x*y-1]);
The detailed output is in the file tmp.output.*
The answer is in the variable Phc.
0
[260] Phc ;
[[[-0.517638,0],[-1.93185,0]],
[[1.93185,0],[0.517638,0]],
[[-1.93185,0],[-0.517638,0]],
[[0.517638,0],[1.93185,0]]]
[261]
```

Author of PHC pack: Jan Verschelde. <http://www2.math.uic.edu/~jan/download.html>
 Reference 1: Jan Verschelde, PHCpack: A general-purpose solver for polynomial systems by homotopy continuation". ACM Transaction on Mathematical Softwares, 25(2): 251-276, 1999.

Reference 2: Cox, D., O'Shea, Little, J., Using Algebraic Geometry, Springer. See the chapter on mixed volumes.

1.1 Functions

1.1.1 `phc.start`

`phc.start()`
 :: Start `ox_sm1_phc` on the localhost.

return Integer

- Start `ox_sm1_phc` on the localhost. It returns the descriptor of `ox_sm1_phc`.
- Set `Xm_noX = 1` to start `ox_sm1_phc` without a debug window.
- The descriptor is stored in `Phc_proc`.

`P = phc.start()`

Reference

`ox_launch, phc`

1.1.2 `phc.phc`

`phc.phc(s|proc=p)`
 :: Ask PHC pack to find all the roots in the complex torus of the given systems of polynomials `s`

return Void

p Number

s List

- The server calls PHC pack to solve a system of algebraic equations S by homotopy methods. PHC pack has been developed by Jan Verschelde. See www.mth.msu.edu/~jan for the original distribution. The original PHC pack can choose several strategies to solve, but our phc interface uses only black-box solver, which is general and automatic but is not efficient. So, if you fails by our interface, try the other strategies via the original user interface.
- phc generates working files `tmp.phc.out.pid`, `tmp.input.*`, `tmp.output.*`. Here, `pid` the process number of the server. The file `tmp.output.*` contains details informations on how PCH pack solves the system.
- The number of variables and the number of equations `length(s)` must agree.

Algorithm: Jan Verschelde, PHCpack: A general-purpose solver for polynomial systems by homotopy continuation". ACM Transaction on Mathematical Softwares, 25(2): 251-276, 1999.

```
[232] P = phc.start();
0
[233] phc.phc([x^2+y^2-4,x*y-1]|proc=P);
The detailed output is in the file tmp.output.*
The answer is in the variable Phc.
0
[234] Phc;
[[-1.93185,0],[-0.517638,0]],
[0.517638,0],[1.93185,0]],
[[-0.517638,0],[-1.93185,0]],
[[1.93185,0],[0.517638,0]]

[[x=[real, imaginary], y=[real,imaginary]], the first solution
[x=[real, imaginary], y=[real,imaginary]], the second solution
...
```

Reference

`ox_launch`, `phc.start`, `'$(OpenXM_HOME)/bin/lin_phcv2'`(original PHC pack binary for linux)

Index

(Index is nonexistent)

(Index is nonexistent)

Short Contents

1	PHC Functions	1
	Index	3

Table of Contents

1	PHC Functions	1
1.1	Functions	1
1.1.1	<code>phc.start</code>	1
1.1.2	<code>phc.phc</code>	1
	Index	3