

Fisher-Bingham MLE

Edition : auto generated by oxgentexi on 27 March 2025

0.0.1 nk_fb_gen_c.gen_c

nk_fb_gen_c.gen_c(N)

: N Fisher-Bingham HGD (holonomic gradient descent) C .

Description:

, testN.c, testN.h C . testN.c , .

gcc testN.c \$OpenXM_HOME/lib/libko_fb.a -lgsl -lblas

.
libko_fb.a OpenXM/src/hgm/fisher-bingham/src/ make install . gsl .
OpenXM/src/hgm/fisher-bingham/src/Testdata , .
testN.h #define MULTIMIN_FDFMINIMIZER_TYPE gsl . testN.h #define
ODEIV_STEP_TYPE gsl .

, T. Koyama, H. Nakayama, K. Nishiyama, N. Takayama, Holonomic
Gradient Descent for the Fisher-Bingham Distribution on the d -dimensional
Sphere, Computational Statistics (2013), <http://dx.doi.org/10.1007/s00180-013-0456-z> .

Authors; T.Koyama, H.Nakayama, K.Nishiyama, N.Takayama.

Example:

```
[1854] load("nk_fb_gen_c.rr");
[2186] nk_fb_gen_c.gen_c(1);      S^1 program .
generate test1.h
generate test1.c
1
[2187] quit;
$ emacs test1.c &
```

Write data here.

\$(OpenXM_HOME)/src/hgm/fisher-bingham/Testdata/s1_wind_data.h .

```
$ gcc test1.c $OpenXM_HOME/lib/libko_fb.a -lgsl -lblas
$ ./a.out
--- snip
points = [1.11945, 3.33044, -0.469454, 0.904504, -0.770373]
values = [3.4421, 1.13891, -0.0217944, 2.28474]
grad ; 0.005644 -0.033429 -0.005644 0.045820 0.047695
norm(grad) ; 0.074535
--- snip

, points parameter x11,x12,x22,y1,y2 .
Value 3.4421 , .
```

Index

(Index is nonexistent)

(Index is nonexistent)

Short Contents

Index	2
-------------	---

Table of Contents

0.0.1 nk_fb_gen_c.gen_c	1
Index	2

