

OpenXM/Risa/Asir-Contrib

OpenXM/Risa/Asir-Contrib User's Manual (English Edition)

Edition 1.3.2-3 for OpenXM/Asir2000

March 2017 (minor update on 27 July 2021)

by OpenXM Developing Team

1 Introduction

The computer algebra system `asir` can use servers, which support the `OpenXM` protocols (Open message eXchange for Mathematics, <http://www.openxm.org>), as components. The interface functions to call these servers are loaded by loading the file `OpenXM/rc/asirrc`. This file is automatically loaded in "Risa/Asir(OpenXM distribution)", which we call `OpenXM/Risa/Asir` in this document. This document explains these interface functions for `asir` and several mathematical and utility functions written in the user languages of Risa/Asir. These mathematical and utility functions are outcome of the Asir-contrib project.

The latest asir-contrib manual of the HEAD branch is at <http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/index-doc.html>

As to technical details on the `OpenXM` protocols, see `openxm-en.tex` at `$(OpenXM_HOME)/doc/OpenXM-specs`.

Enjoy mathematics on your computer.

List of contributors:

- Maekawa, Masahide (Oct., 1999 – : CVS server)
- Noro, Masayuki (Jan., 1996 – : OpenXM Protocol OXRFC-100, asir2000)
- Ohara, Katsuyoshi (Jan., 1998 – : ox-math, oxc OXRFC-101)
- Takayama, Nobuki (Jan., 1996 – : OpenXM Protocol OXRFC-100, kan/sm1, asir-contrib)
- Tamura, Yasushi (Nov., 1998 – : OpenMath proxy, tfb)
- Fujimoto, Mitsushi (Windows)
- Iwane, Hidenao (Knapsack factorizer)
- Nakayama, Hiromasa (Gaussian elimination)
- Okutani, Yukio (Oct., 1999 – Feb., 2000 : matrix, diff, ...)
- Stillman, Mike (Macaulay 2 client and server)
- Tsai, Harrison (Macaulay 2 client and server)

See `OpenXM/Copyright` for the copyright notice.

2 How to load Asir/Contrib

With loading `OpenXM/rc/asirrc`, we can use most functions in Asir/Contrib. The `OpenXM/Risa/Asir` reads this file, which is specified by the `ASIR_CONFIG` environmental variable, when it starts. The file `names.rr` is the top level file of the Asir/Contrib. Most other files are loaded from `names.rr`. Some packages are not loaded from `names.rr` and they must be loaded individually.

A sample of `asirrc` to use Asir/Contrib.

```
load("gr")$
load("primdec")$
load("katsura")$
load("bfct")$
load("names.rr")$
load("oxrfc103.rr")$
User_asirrc=which(getenv("HOME")+"/.asirrc")$
if (type(User_asirrc)!=0)
  if (!ctrl("quiet_mode")) print("Loading ~/.asirrc")$
  load(User_asirrc)$
else $
end$
```

3 Function Names in Asir Contrib

Not yet written.

Not yet written.

4 Asir-contrib for Windows

A part of Asir-contrib works on Windows. The following functions and components work on windows; the outer component sm1 and functions in asir-contrib which do not call outer components. In the cygwin environment, the outer components sm1, phc work. The other outer components do not work.

The following functions do not work on Windows. Some of them work in the cygwin environment of Windows.

- gnuplot.*
- om.*
- mathematica.*
- phc.*
- print_dvi_form
- print_gif_form
- print_open_math_xml_form
- print_png_form
- print_xdvi_form
- print_xv_form
- tigers_xv_form

5 Basic (Standard Functions)

5.0.1 base_cancel

`base_cancel(S)`

: It simplifies *S* by canceling the common factors of denominators and numerators.

Example:

```
base_cancel([(x-1)/(x^2-1), (x-1)/(x^3-1)]);
```

5.0.2 base_choose

`base_choose(L,M)`

: It returns the list of the order *M* subsets of *L*.

Example:

```
base_choose([1,2,3],2);
```

It outputs all the order 2 subsets of the set $\{1, 2, 3\}$

5.0.3 base_f_definedp

`base_f_definedp(Func)`

: returns 1 if the function *Func* is defined.

5.0.4 base_flatten

`base_flatten(S)`

: It flattens a nested list *S*.

Example:

```
base_flatten([[1,2,3],4]);
```

5.0.5 base_intersection

`base_intersection(A,B)`

: It returns the intersection of *A* and *B* as a set.

Example:

```
base_intersection([1,2,3],[2,3,5,[6,5]]);
```

5.0.6 base_is_asir2018

`base_is_asir2018()`

: returns 1 if the system is asir2018.

5.0.7 base_is_equal

`base_is_equal(L1,L2)`

: returns 1 if the objects *L1* and *L2* are equal else return 0

5.0.8 base_makelist

`base_makelist(Obj,K,B,T)`

: `base_makelist` generate a list from `Obj` where `K` runs in `[B,T]`. Options are `qt=1` (keep quote data), `step` (step size). When `B` is a list, `T` is ignored and `K` runs in `B`.

Example 0:

```
base_makelist(k^2,k,1,10);
```

Example 1:

```
map(print_input_form,base_makelist(quote(x^2),x,1,10 | qt=1, step=0.5))
```

Example 2:

```
base_makelist(quote("the "+k),k,["cat","dog"],0);
```

5.0.9 base_memberq

`base_memberq(A,S)`

: It returns 1 if `A` is a member of the set `S` else returns 0.

Example:

```
base_memberq(2,[1,2,3]);
```

5.0.10 base_permutation

`base_permutation(L)`

: It outputs all permutations of `L`. BUG; it uses a slow algorithm.

Example:

```
base_permutation([1,2,3,4]);
```

5.0.11 base_position

`base_position(A,S)`

: It returns the position of `A` in `S`.

Example:

```
base_position("cat",["dog","cat","monkey"]);
```

5.0.12 base_preplace

`base_preplace(S,Rule)`

: It rewrites `S` by using the rule `Rule`. `psubst` is used instead of `subst`. The replacement is not performed for function arguments.

Example:

```
base_preplace(exp(x)+x^2,[[x,a+1],[exp(x),b]]);
```

`x` is replaced by `a+1` and `exp(x)` is replaced by `b` in `exp(x)+x^2`.

5.0.13 base_product

`base_product(Obj, K, B, T)`

: `base_product` returns the product of `Obj` where `K` runs in `[B,T]`. Options are `qt=1` (keep quote data), `step` (step size). When `B` is a list, `K` runs in `B` and `T` is ignored.

Example 0:

```
base_product(k^2,k,1,10);
```

Example 1:

```
base_product(quote(x^2),x,1,10 | qt=1, step=0.5);
```

Example 2:

```
base_product(quote(x^2),x,[a,b,c],0 | qt=1);
```

5.0.14 base_prune

`base_prune(A,S)`

: It returns a list in which `A` is removed from `S`.

Example:

```
base_prune("cat",["dog","cat","monkey"]);
```

5.0.15 base_rebuild_opt

`base_rebuild_opt(Opt)`

: It rebuilt the option list `Opt`

Example:

```
base_rebuild_opt([[key1,1],[key2,3]] | remove_keys=["key2"]);
```

it returns `[[key1,1]]`

5.0.16 base_replace

`base_replace(S,Rule)`

: It rewrites `S` by using the rule `Rule`

Example:

```
base_replace(x^2+y^2,[[x,a+1],[y,b]]);
```

`x` is replaced by `a+1` and `y` is replaced by `b` in `x^2+y^2`.

5.0.17 base_replace_n

`base_replace_n(S,Rule)`

: It rewrites `S` by using the rule `Rule`. It is used only for specializing variables to numbers and faster than `base_replace`.

Example:

```
base_replace_n(x^2+y^2,[[x,1/2],[y,2.0+3*@i]]);
```

`x` is replaced by `1/2` and `y` is replaced by `2.0+3*i` in `x^2+y^2`.

5.0.18 base_set_minus

`base_set_minus(A,B)`
 : $A \setminus B$

Example:

```
base_set_minus([1,2,3],[3,4,5]);
```

5.0.19 base_set_union

`base_set_union(A,B)`
 : $A \cup B$

Example:

```
base_set_union([1,2,3],[3,4,5]);
```

5.0.20 base_subsequenceq

`base_subsequenceq(A,B)`
 : if A is a subsequence B, then it returns 1 else 0.

Example:

```
base_subsequence([3,2,5],[1,2,3,4,5]);
```

5.0.21 base_subsetq

`base_subsetq(A,B)`
 : if $A \subseteq B$, then it returns 1 else 0.

Example:

```
base_subsetq([1,2],[1,2,3,4,5]);
```

5.0.22 base_subsets_of_size

`base_subsets_of_size(K,S)`
 : It outputs all subsets of S of the size K. BUG; it uses a slow algorithm. Do not input a large S.

Example:

```
base_subsets_of_size(2,[3,5,3,2]);
```

5.0.23 base_sum

`base_sum(Obj,K,B,T)`
 : `base_sum` returns the sum of Obj where K runs in [B,T]. Options are `qt=1` (keep quote data), `step` (step size). When B is a list, K runs in B and T is ignored. When K is 0, then Obj is assumed to be a list or vector and `Obj[B]+...+Obj[T]` is returned.

Example 0:

```
base_sum(k^2,k,1,10);
```

Example 1:

```
base_sum(quote(x^2),x,1,10 | qt=1, step=0.5);
```

Example 2:

```
base_sum(quote(x^2),x,[a,b,c],0 | qt=1);
```

5.0.24 base_var_list

`base_var_list(Name,B,T)`

: `base_var_list` generate a list of variables `Name+Index` where `Index` runs on `[B,T]`.

Example 0:

```
base_var_list(x,0,10);
```

Example 1:

```
base_var_list(x,1,4 | d = 1);
```

Options are `d=1` (add `d` before the name).

6 Numbers (Standard Mathematical Functions)

6.0.1 number_abs

`number_abs(X)`
 :

Example:

```
number_abs(-3);
```

6.0.2 number_ceiling

`number_ceiling(X)`
 :

Example:

```
number_abs(1.5);
```

6.0.3 number_eval

`number_eval(X)`
 :

Example:

```
number_eval([1/10^10,@pi,exp(1)]);
```

6.0.4 number_factor

`number_factor(X)`
 : It factors the given integer X .

Example:

```
number_factor(20);
```

6.0.5 number_float_to_rational

`number_float_to_rational(X)`
 :

Example:

```
number_float_to_rational(1.5234);
number_float_to_rational(1.5234 | prec=14);
```

6.0.6 number_floor

`number_floor(X)`
 :

Example:

```
number_floor(1.5);
```

6.0.7 `number_imaginary_part`

```
number_imaginary_part(X)  
:
```

Example:

```
number_imaginary_part(1+2*@i);
```

6.0.8 `number_is_integer`

```
number_is_integer(X)  
:
```

Example:

```
number_is_integer(2/3);
```

6.0.9 `number_real_part`

```
number_real_part(X)  
:
```

Example:

```
number_real_part(1+2*@i);
```

7 Calculus (Standard Mathematical Functions)

8 Series (Standard Mathematical Functions)

9 Special Functions (Standard Mathematical Functions)

Not yet written

10 Matrix (Standard Mathematical Functions)

10.0.1 matrix_adjugate

`matrix_adjugate(M)`
: It generates the adjugate matrix of the matrix M .

Example:

```
matrix_adjugate(matrix_list_to_matrix([[a,b],[c,d]]));
```

10.0.2 matrix_clone

`matrix_clone(M)`
: It generates the clone of the matrix M .

Example:

```
matrix_clone(matrix_list_to_matrix([[1,1],[0,1]]));
```

10.0.3 matrix_det

`matrix_det(M)`
: It returns the determinant of the matrix M .

Example:

```
poly_factor(matrix_det([[1,x,x^2],[1,y,y^2],[1,z,z^2]]));
```

10.0.4 matrix_diagonal_matrix

`matrix_diagonal_matrix(L)`
: It returns the diagonal matrix with diagonal entries L .

Example:

```
matrix_diagonal_matrix([1,2,3]);
```

References:

```
matrix_list_to_matrix
```

10.0.5 matrix_eigenvalues

`matrix_eigenvalues(M)`
: It returns the eigenvalues of the matrix M . if the option `num=1`, it returns the numerical approximate eigenvalues.

Example:

```
matrix_eigenvalues([[x,1],[0,y]]);
```

10.0.6 matrix_gauge_transformation

`matrix_gauge_transformation(M, T, V)`
: It returns $T^{-1} M T - T^{-1} dT/dV$

Example:

```
matrix_gauge_transformation([[0,x],[1,x]], [[x,0],[0,1]], x);
```

10.0.7 `matrix_identity_matrix`

`matrix_identity_matrix(N)`

: It returns the identity matrix of the size *N*.

Example:

```
matrix_identity_matrix(5);
```

References:

`matrix_diagonal_matrix`

10.0.8 `matrix_ij`

`matrix_ij(N, II, JJ)`

: It returns the matrix for exchanging *II*-th row(col) and *JJ*-th row(col).

Example:

```
matrix_ij(4,0,2);
```

10.0.9 `matrix_image`

`matrix_image(M)`

: It computes the image of *M*. Redundant vectors are removed.

Example:

```
matrix_image([[1,2,3],[2,4,6],[1,0,0]]);
```

References:

`matrix_kernel`

10.0.10 `matrix_inner_product`

`matrix_inner_product(A, B)`

: It returns the inner product of two vectors *A* and *B*.

Example:

```
matrix_inner_product([1,2],[x,y]);
```

10.0.11 `matrix_inverse`

`matrix_inverse(M)`

: It returns the inverse of the matrix *M*.

Example:

```
matrix_inverse([[1,2],[0,1]]);
```

10.0.12 `matrix_inverse_singular`

`matrix_inverse_singular(Mat)`

: It returns a quasi-inverse matrix of *Mat* when it has 0-row and 0-column.

Example:

```
matrix_inverse_singular(newmat(3,3,[[1,0,2],[0,0,0],[3,0,4]]));
```

10.0.13 matrix_kernel`matrix_kernel(M)`: It returns the basis of the kernel of the matrix *M*.

Example:

`matrix_kernel([[1,1,1,1],[0,1,3,4]]);`**10.0.14 matrix_list_to_matrix**`matrix_list_to_matrix(M)`: It translates the list *M* to a matrix.

Example:

`print_xdvi_form(matrix_list_to_matrix([[1,1],[0,2]]));`

References:

`matrix_matrix_to_list`**10.0.15 matrix_matrix_to_list**`matrix_matrix_to_list(M)`: It translates the matrix *M* to a list.

References:

`matrix_list_to_matrix`**10.0.16 matrix_poly_to_matrix**`matrix_poly_to_matrix(Poly,Rule)`: Replace variables in the polynomial *Poly* by matrices in the *Rule*.

Example:

`matrix_poly_to_matrix(x^2-1,[[x,newmat(2,2,[[2,0],[0,3]])]]);`**10.0.17 matrix_rank**`matrix_rank(M)`: It returns the rank of the matrix *M*.

Example:

`matrix_rank([[1,1,1,1],[0,1,3,4]]);`**10.0.18 matrix_solve_linear**`matrix_solve_linear(M,X,B)`: It solves the system of linear equations $M X = B$

Example:

`matrix_solve_linear([[1,2],[0,1]], [x,y], [1,2]);`

10.0.19 `matrix_submatrix``matrix_submatrix(M , Ind)`: It returns the submatrix of M defined by the index set Ind .

Example:

`matrix_submatrix([[0,1],[2,3],[4,5]],[1,2]);`**10.0.20** `matrix_transpose``matrix_transpose(M)`: It returns the transpose of the matrix M .

References:

`matrix_list_to_matrix`

11 Graphic (Standard Mathematical Functions)

Not yet written.

12 Print (Standard Mathematical Functions)

12.0.1 print_c_form

`print_c_form(S)`

: It transforms S to the C format or python format string.

Example 0:

```
print_c_form(x^2+1);
```

Example 1:

```
print_c_form(x^2+1 | mode=python);
```

Example 2:

```
print_c_form(sin(x^2+1)/5 | mode=c);
```

12.0.2 print_dvi_form

`print_dvi_form(S)`

: It outputs S to a dvi file.

Example:

```
print_dvi_form(x^2-1);
```

References:

```
print_xdvi_form , print_tex_form
```

12.0.3 print_em

`print_em(S)`

: It outputs S by a font to emphasize it.

Example:

```
print_em(x^2-1);
```

12.0.4 print_gif_form

`print_gif_form(S)`

: It outputs S to a file of the gif format.

`print_gif_form(S | table=key0)`

: This function allows optional variables *table*

Example:

```
print_gif_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));
```

References:

```
print_tex_form
```

12.0.5 print_input_form

`print_input_form(S)`

: It transforms S to a string which can be parsed by asir.

Example:

```
print_input_form(quote(x^3-1));
```

12.0.6 `print_open_math_tfb_form`

`print_open_math_tfb_form(S)`
 : It transforms S to a tfb format of OpenMath XML.

Description:

It is experimental. You need to load `taka_print_tfb.rr` to call it.

Example:

```
print_open_math_tfb_form(quote(f(x,1/(y+1))+2));
```

12.0.7 `print_open_math_xml_form`

`print_open_math_xml_form(S)`
 : It transforms S to a string which is compliant to OpenMath(1999).

Example:

```
print_open_math_xml_form(x^3-1);
```

References:

www.openmath.org

12.0.8 `print_output`

`print_output(Obj)`
 : It outputs the object Obj to a file. If the optional variable *file* is set, then it outputs the Obj to the specified file, else it outputs it to "asir_output.tmp.txt". If the optional variable *mode* is set to "w", then the file is newly created. If the optional variable is not set, the Obj is appended to the file.

`print_output(Obj | file=key0,mode=key1)`
 : This function allows optional variables *file*, *mode*

Example:

```
print_output("Hello"|file="test.txt");
```

References:

`glib_tops`, (,)

12.0.9 `print_ox_rfc100_xml_form`

`print_ox_rfc100_xml_form(S)`
 : It transforms S to a string which is compliant to OpenXM RFC 100.

Example:

```
print_ox_rfc100_xml_form(x^3-1);
```

References:

www.openxm.org

12.0.10 print_pdf_form`print_pdf_form(S)`: It transforms S to a pdf file and previews the file.

Example 0:

`print_pdf_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));`

Example 1:

`print_pdf_form(poly_factor(x^10-1));`

References:

`print_tex_form`, `print_xdvi_form`**12.0.11 print_png_form**`print_png_form(S)`: It transforms S to a file of the format png. dvi2png should be installed.

Example:

`print_png_form(x^3-1);`

References:

`print_tex_form`**12.0.12 print_terminal_form**`print_terminal_form(S)`: It transforms S to the terminal form???**12.0.13 print_tex_form**`print_tex_form(S)`: It transforms S to a string of the LaTeX format.`print_tex_form(S | table=key0,row=key1)`: This function allows optional variables *table*, *row*

Description:

The global variable `Print_tex_form_fraction_format` takes the values "auto", "frac", or "/". The global variable `Print_tex_form_no_automatic_subscript` takes the values 0 or 1. BUG; A large input S cannot be translated.

Example:

`print_tex_form(x*dx+1 | table=[["dx","\partial_x"]]);`

The optional variable *table* is used to give a translation table of asir symbols and tex symbols. when `AMSTeX = 1`, "begin pmatrix" and "end pmatrix" will be used to output matrix.

References:

`print_xdvi_form`

12.0.14 print_tfb_form`print_tfb_form(S)`: It transforms *S* to the tfb format.

Example:

`print_tfb_form(x+1);`**12.0.15 print_xdvi_form**`print_xdvi_form(S)`: It transforms *S* to a xdvi file and previews the file by xdvi.

Example 0:

`print_xdvi_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));`

Example 1:

`print_xdvi_form(print_tex_form(1/2));`

References:

`print_tex_form` , `print_dvi_form`**12.0.16 print_xv_form**`print_xv_form(S)`: It transforms *S* to a gif file and previews the file by xv.`print_xv_form(S | input=key0,format=key1)`: This function allows optional variables *input*, *format*

Example 0:

`print_xv_form(newmat(2,2,[[x^2,x],[y^2-1,x/(x-1)]]));`

Example 1:

`print_xv_form(x+y | format="png");`

If the optional variable `format="png"` is set, png format will be used to generate an input for xv.

References:

`print_tex_form` , `print_gif_form`

13 Polynomials (Standard Mathematical Functions)

13.0.1 poly_coefficient

`poly_coefficient(F, Deg, V)`

: It returns the coefficient of V^{Deg} in F . F may be rational or list or vector.

Example:

```
F=[(x+y+z)^10/z^2, (x-y+z)^10/z^3]$
poly_coefficient(F,10,x);
```

13.0.2 poly_degree

`poly_degree(F)`

: It returns the degree of F with respect to the given weight vector.

`poly_degree(F | weight=key0, v=key1)`

: This function allows optional variables *weight*, *v*

Description:

The weight is given by the optional variable *weight* w . It returns $\text{ord}_w(F)$

Example:

```
poly_degree(x^2+y^2-4 |weight=[100,1],v=[x,y]);
```

13.0.3 poly_denominator

`poly_denominator(L)`

: It returns the denominator of L . L may be a list.

Example:

```
poly_denominator([1/(x^2-1),1/(x^3-1)]);
```

13.0.4 poly_elimination_ideal

`poly_elimination_ideal(I, VV)`

: It computes the intersection of the ideal I and the subring $K[VV]$.

`poly_elimination_ideal(I, VV |`

`grobner_basis=key0, v=key1, homo=key2, grace=key3, strategy=key4)`

: This function allows optional variables *grobner_basis*, *v*, *homo*, *grace*, *strategy*

Description:

If *grobner_basis* is "yes", I is assumed to be a Grobner basis. The optional variable *v* is a list of variables which defines the ring of polynomials.

Example 0:

```
poly_elimination_ideal([x^2+y^2-4,x*y-1],[x]);
```

Example 1:

```
A = poly_grobner_basis([x^2+y^2-4,x*y-1] |order=2,v=[y,x]);
```

```

        poly_elimination_ideal(A,[x]|grobner_basis="yes");
When strategy=1(default),
    nd_gr is used when trace=0(default),
    nd_gr_trace is used when trace=1.

```

References:

```
gr , hgr , gr_mod , dp_*
```

13.0.5 poly_expand

```
poly_expand(F)
    : This is an alias of poly_sort.
```

References:

```
poly_sort
```

13.0.6 poly_factor

```
poly_factor(F)
    : It factorizes the polynomial  $F$ .
```

Example:

```
poly_factor(x^10-y^10);
```

13.0.7 poly_gcd

```
poly_gcd(F,G)
    : It computes the polynomial GCD of  $F$  and  $G$ .
```

Example:

```
poly_gcd(x^10-y^10,x^25-y^25);
```

13.0.8 poly_gr_w

```
poly_gr_w(F,V,W)
    : It returns the Grobner basis of  $F$  for the weight vector  $W$ . It is the second
    interface for poly_grobner_basis.
```

Example:

```
poly_gr_w([x^2+y^2-1,x*y-1],[x,y],[1,0]);
```

References:

```
poly_in_w , poly_grobner_bais
```

13.0.9 poly_grobner_basis

```
poly_grobner_basis(I)
    : It returns the Grobner basis of  $I$ .
```

```
poly_grobner_basis(I | order=key0,v=key1)
    : This function allows optional variables  $order$ ,  $v$ 
```

Description:

The optional variable v is a list of variables which defines the ring of polynomials.

Example:

```
A = poly_grobner_basis([x^2+y^2-4,x*y-1]|order=2,v=[y,x],str=1);
    A->Generators;
    A->Ring->Variables;
    A->Ring->Order;
B = poly_grobner_basis([x^2+y^2-4,x*y-1]|order=[[10,1]],v=[y,x]);
C = poly_grobner_basis([x^2+y^2-4,x*y-1]|order=[block,[0,1],[0,1]],v=[y,x]);
```

13.0.10 poly_hilbert_polynomial

`poly_hilbert_polynomial(I)`

: It returns the Hilbert polynomial of the `poly_init(I)`.

`poly_hilbert_polynomial(I | s=key0,v=key1,sm1=key2)`

: This function allows optional variables s , v , $sm1$

Description:

The optional variable v is a list of variables. $sm1=1$ forces to call `sm1`. $[\text{sum}(H(k),k,0,h), H(h)]$ where $H(h)$ is the number of degree h monomials when $h \gg 0$. On asir2018, it returns $[\text{sum}(H(k),k,0,h), H(h), [H[0], H[1], \dots], F, d]$ where $F/(1-h)^d$ is the Poincare series.

Example:

```
poly_hilbert_polynomial([x1*y1,x1*y2,x2*y1,x2*y2]|s=k,v=[x1,x2,y1,y2]);
```

13.0.11 poly_ideal_colon

`poly_ideal_colon(I,J,V)`

: It computes the colon ideal of I by J V is the list of variables.

Example:

```
B=[(x+y+z)^50,(x-y+z)^50]$
V=[x,y,z]$
B=poly_ideal_colon(B,[(x+y+z)^49,(x-y+z)^49],V);
```

13.0.12 poly_ideal_intersection

`poly_ideal_intersection(I,J,V,Ord)`

: It computes the intersection of the ideal I and J V is the list of variables. Ord is the order.

Example:

```
A=[j*h*g*f*e*d*b,j*i*g*d*c*b,j*i*h*g*d*b,j*i*h*e*b,i*e*c*b,z]$
B=[a*d-j*c,b*c,d*e-f*g*h]$
V=[a,b,c,d,e,f,g,h,i,j,z]$
poly_ideal_intersection(A,B,V,0);
```

13.0.13 poly_ideal_saturation`poly_ideal_saturation(I, J, V)`

: It computes the saturation ideal of I by J. V is the list of variables.

Example:

```

B=[(x+y+z)^50,(x-y+z)^50]$
V=[x,y,z]$
B=poly_ideal_saturation(B,[(x+y+z)^49,(x-y+z)^49],V);

```

13.0.14 poly_in`poly_in(I)`: It is an alias of `poly_initial()`.`poly_in(I | order=key0, v=key1)`: This function allows optional variables *order*, *v*

Example:

```

poly_in([x^2+y^2-4,x*y-1]|order=0,v=[x,y]);

```

13.0.15 poly_in_w`poly_in_w(F, V, W)`: It returns the initial term or the initial ideal `in_w(F)` for the weight vector given by *order*. F is a single polynomial or a list of polynomials.`poly_in_w(F, V, W | gb=key0)`: This function allows optional variables *gb*

Example:

```

poly_in_w([x^2+y^2-1,x*y-x] , [x,y] , [1,0]);

```

References:

```

poly_weight_to_omatrix , ( , W , V , ) , poly_grobner_basis , poly_gr_w ,
poly_in_w_

```

13.0.16 poly_in_w_`poly_in_w_(F)`: It returns the initial term or the initial ideal `in_w(F)` for the weight vector given by *order*. F is a single polynomial or a list of polynomials. This is a new interface of `poly_in_w` with shorter args.`poly_in_w_(F | v=key0, weight=key1, gb=key2)`: This function allows optional variables *v*, *weight*, *gb*

Example:

```

poly_in_w_([x^2+y^2-1,x*y-x] | v=[x,y],weight=[1,0]);

```

References:

```

poly_weight_to_omatrix , ( , W , V , ) , poly_grobner_basis , poly_gr_w

```

13.0.17 poly_initial`poly_initial(I)`: It returns the initial ideal of I with respect to the given order.`poly_initial(I | order=key0, v=key1)`: This function allows optional variables $order$, v

Description:

The optional variable v is a list of variables. This function computes $\text{in}_{\prec}(I)$

Example:

```
poly_initial([x^2+y^2-4,x*y-1] | order=0, v=[x,y]);
poly_initial([x^2+y^2-4,x*y-1] | order=0, v=[x,y], gb=1);
```

13.0.18 poly_initial_coefficients`poly_initial_coefficients(I)`: It computes the coefficients of the initial ideal of I with respect to the given order.`poly_initial_coefficients(I | order=key0, v=key1)`: This function allows optional variables $order$, v

Description:

The optional variable v is a list of variables. The order is specified by the optional variable $order$

Example:

```
poly_initial_coefficients([x^2+y^2-4,x*y-1] | order=0, v=[x,y]);
```

13.0.19 poly_initial_term`poly_initial_term(F)`: It returns the initial term of a polynomial F with respect to the given weight vector.`poly_initial_term(F | weight=key0, order=key1, v=key2)`: This function allows optional variables $weight$, $order$, v

Description:

The weight is given by the optional variable $weight$ w . It returns $\text{in}_w(F)$

Example:

```
poly_initial_term(x^2+y^2-4 | weight=[100,1], v=[x,y]);
```

13.0.20 poly_lcm`poly_lcm(L)`: It returns the LCM of $L[0]$, $L[1]$, ...

Example:

```
poly_lcm([x^2-1,x^3-1]);
```

13.0.21 poly_ord_w`poly_ord_w(F, V, W)`: It returns the order with respect to W of F .

Example:

`poly_ord_w(x^2+y^2-1, [x,y], [1,3]);`

References:

`poly_in_w`**13.0.22 poly_prime_dec**`poly_prime_dec(I, V)`: It computes the prime ideal decomposition of the radical of I . V is a list of variables.

Example:

```

B=[x00*x11-x01*x10,x01*x12-x02*x11,x02*x13-x03*x12,x03*x14-x04*x13,
   -x11*x20+x21*x10,-x21*x12+x22*x11,-x22*x13+x23*x12,-x23*x14+x24*x13];
V=[x00,x01,x02,x03,x04,x10,x11,x12,x13,x14,x20,x21,x22,x23,x24];
poly_prime_dec(B,V | radical=1);

```

13.0.23 poly_r_omatrix`poly_r_omatrix(N)`: It gives a weight matrix, which is used to compute a Grobner basis in $K(x)\langle dx \rangle$, $|x|=|dx|=N$.

Example:

`poly_r_omatrix(3);`

References:

`poly_weight_to_omatrix, (, W, V,) , ;`**13.0.24 poly_solve_linear**`poly_solve_linear(Eqs, V)`: It solves the system of linear equations Eqs with respect to the set of variables V .

Example:

`poly_solve_linear([2*x+3*y-z-2, x+y+z-1], [x,y,z]);`**13.0.25 poly_sort**`poly_sort(F)`: It expands F with a given variables $v=V$ and a given weight $w=W$. It returns a quote object. If *truncate* option is set, the expansion is truncated at the given degree.`poly_sort(F | v=key0,w=key1,truncate=key2)`: This function allows optional variables v , w , *truncate*

Example:

```
poly_sort((x-y-a)^3 | v=[x,y], w=[-1,-1])
returns a series expansion in terms of x and y.
```

13.0.26 poly_toric_ideal

```
poly_toric_ideal(A,V)
: It returns generators of the affine toric ideal defined by the matrix(list) A. V
is the list of variables.
```

Example:

```
poly_toric_ideal([[1,1,1,1],[0,1,2,3]],base_var_list(x,0,3));
```

13.0.27 poly_weight_to_omatrix

```
poly_weight_to_omatrix(W,V)
: It translates the weight vector W into a matrix, which is used to set the order
in asir Grobner basis functions. V is the list of variables.
```

Example:

```
M=poly_weight_to_omatrix([2,1,0],[x,y,z]);
nd_gr([x^3+z^3-1,x*y*z-1,y^2+z^2-1,[x,y,z],0,M);
```


14 Complex (Standard Mathematical Functions)

15 Graphic Library (2 dimensional)

The library `glib` provides a simple interface like old BASIC to the graphic primitive (`draw_obj`) of Risa/Asir.

15.0.1 `glib_clear`

`glib_clear()`
: Clear the screen.

15.0.2 `glib_flush`

`glib_flush()`
: ; Flush the output. (Cfep only. It also set `initGL` to 1.).

15.0.3 `glib_line`

`glib_line(X0,Y0,X1,Y1)`
: It draws the line $[X0,Y0]$ – $[X1,Y1]$ with *color* and *shape*
`glib_line(X0,Y0,X1,Y1 | color=key0,shape=key1)`
: This function allows optional variables *color*, *shape*

Example:

```
glib_line(0,0,5,3/2 | color=0xff00ff);
glib_line(0,0,10,0 | shape=arrow);
```

15.0.4 `glib_open`

`glib_open()`
: It starts the `ox_plot` server and opens a canvas. The canvas size is set to *Glib_canvas_x* X *Glib_canvas_y* (the default value is 400). This function is automatically called when the user calls `glib` functions.

15.0.5 `glib_plot`

`glib_plot(F)`
: It plots an object *F* on the `glib` canvas.

Example 0:

```
glib_plot([[0,1],[0.1,0.9],[0.2,0.7],[0.3,0.5],[0.4,0.8]]);
```

Example 1:

```
glib_plot(tan(x));
```

15.0.6 `glib_print`

`glib_print(X,Y,Text)`
: It put a string *Text* at $[X,Y]$ on the `glib` canvas.
`glib_print(X,Y,Text | color=key0)`
: This function allows optional variables *color*

Example:

```
glib_print(100,100,"Hello Worlds" | color=0xff0000);
```

15.0.7 glib_ps_form

`glib_ps_form(S)`

: It returns the PS code generated by executing *S* (experimental).

Example 0:

```
glib_ps_form(quote( glib_line(0,0,100,100) ));
```

Example 1:

```
glib_ps_form(quote([glib_line(0,0,100,100),glib_line(100,0,0,100)]));
```

References:

`glib_tops`

15.0.8 glib_putpixel

`glib_putpixel(X,Y)`

: It puts a pixel at [*X*,*Y*] with *color*

`glib_putpixel(X,Y | color=key0)`

: This function allows optional variables *color*

Example:

```
glib_putpixel(1,2 | color=0xffff00);
```

15.0.9 glib_remove_last

`glib_remove_last()`

: Remove the last object. `glib_flush()` should also be called to remove the last object. (cfep only).

15.0.10 glib_set_pixel_size

`glib_set_pixel_size(P)`

: Set the size of putpixel to *P*. 1.0 is the default. (cfep only).

15.0.11 glib_tops

`glib_tops()`

: If `Glib_ps` is set to 1, it returns a postscript program to draw the picture on the canvas.

References:

`print_output`

15.0.12 glib_window

`glib_window(Xmin,Ymin,Xmax,Ymax)`

: It generates a window with the left top corner [*Xmin*,*Ymin*] and the right bottom corner [*Xmax*,*Ymax*]. If the global variable *Glib_math_coordinate* is set to 1, mathematical coordinate system will be employed, i.e., the left top corner will have the coordinate [*Xmin*,*Ymax*].

Example:

```
glib_window(-1,-1,10,10);
```

16 OpenXM-Contrib General Functions

16.1 Functions

16.1.1 ox_check_errors2

`ox_check_errors2(p)`

:: get a list of error objects on the stack of the server *p*.

return List

p Number

- It gets a list of error objects on the server stack.
- It does not pop the error objects.

```
[219] P=sm1.start();
```

```
0
```

```
[220] sm1.sm1(P," 0 get ");
```

```
0
```

```
[221] ox_check_errors2(P);
```

```
[error([7,4294967295,executeString: Usage:get])]
```

```
Error on the server of the process number = 1
```

```
To clean the stack of the ox server,
```

```
type in ox_pops(P,N) (P: process number, N: the number of data you need to pop)
out of the debug mode.
```

```
If you like to automatically clean data on the server stack,
```

```
set XM_debug=0;
```

17 OXshell Functions

OXshell is a system to execute system commands from ox servers. As to details, see the files OpenXM/src/kan96xx/Doc/oxshell.oxw and OpenXM/doc/Papers/rims-2003-12-16-ja.tex.

17.0.1 oxshell.get_value

`oxshell.get_value(NAME, V)`

: It get the value of the variable *NAME* on the server *ox_shell*.

Example:

```
oxshell.set_value("abc", "Hello world!");
oxshell.oxshell(["cp", "stringIn://abc", "stringOut://result"]);
oxshell.get_value("result");
```

What we do is a file \$TMP/abc* is generated with the contents Hello world! and copi

The contents of the file is stored in the variable result on *ox_sm1*.

References:

oxshell.oxshell , *oxshell.set_value*

17.0.2 oxshell.oxshell

`oxshell.oxshell(L)`

: It executes command *L* on a *ox_shell* server. *L* must be an array. The result is the outputs to stdout and stderr. A temporary file will be generated under \$TMP. cf. *oxshell.keep_tmp()*

Example:

```
oxshell.oxshell(["ls"]);
```

References:

ox_shell , *oxshell.set_value* , *oxshell.get_value* , *oxshell* , *of* , *sm1*.

17.0.3 oxshell.set_value

`oxshell.set_value(NAME, V)`

: It set the value *V* to the variable *Name* on the server *ox_shell*.

Example:

```
oxshell.set_value("abc", "Hello world!");
oxshell.oxshell(["cat", "stringIn://abc"]);
```

References:

oxshell.oxshell , *oxshell.get_value*

18 Asir System Utility Functions

18.0.1 asir_contrib_update

`asir_contrib_update()`

: It updates the asir-contrib library and/or some other files to the HEAD branch. The usage will be shown by `asir_contrib_update()` without the option `update`. Options are `update`, `clean`, `url`, `install_dir`, `zip_files`, `tmp`. Default values `update=0`, `clean=0`, `url="http://www.math.kobe-u.ac.jp/OpenXM/Current"`, `install_dir=%APPDATA%/OpenXM` (win) or `install_dir=$OpenXM_tmp/OpenXM` (others) `zip_files=["lib-asir-contrib.zip"]`

Example:

```
asir_contrib_update();
asir_contrib_update(|update=1);    update the library
asir_contrib_update(|update=3);    update the library and the documents
asir_contrib_update(|clean=1);
asir_contrib_update(|zip_files=["lib-asir-contrib.zip","doc-asir2000.zip","doc-asir
```

19 Utility Functions

Utility functions provide some useful functions to access to the system and to process strings.

19.0.1 util_damepathq

`util_damepathq(S)`

: When *S* is a string by the ShiftJIS code and *S* contains dame-moji with respect to \, it returns [a non-zero number, the string].

Example:

```
T = [0x5c,0xe4,0x5c,0x41,0x42]$
T2=asciitostr(T)$
util_damepathq(T2);
```

19.0.2 util_file_exists

`util_file_exists(Fname)`

: It returns 1 when *Fname* exists. It returns 0 when *Fname* does not exist.

19.0.3 util_filter

`util_filter(Command,Input)`

: It executes the filter program *Command* with the *Input* and returns the output of the filter as a string.

`util_filter(Command,Input | env=key0)`

: This function allows optional variables *env*

Example:

```
util_filter("sort","cat\ndog\ncentipede\n");
```

19.0.4 util_find_and_replace

`util_find_and_replace(W,S,Wnew)`

: It replaces *W* in *S* by *Wnew*. Arguments must be lists of ascii codes or strings.

19.0.5 util_find_start

`util_find_start()`

: It tries to find the gnome-open command or an installed browser in unix systems. It returns "open" on MacOS X and returns "start" on Windows.

`util_find_start(| browser=key0)`

: This function allows optional variables *browser*

19.0.6 util_find_substr

`util_find_substr(W,S)`

: It returns the position of *W* in *S*. If *W* cannot be found, it returns -1. Arguments must be lists of ascii codes or strings.

19.0.7 util_index

`util_index(V)`

: It returns the name part and the index part of V .

Example:

```
util_index(x_2_3)
```

References:

`util_v`

19.0.8 util_load_file_as_a_string

`util_load_file_as_a_string(F)`

: It reads a file F as a string.

19.0.9 util_part

`util_part(S,P,Q)`

: It returns from P th element to Q th element of S .

19.0.10 util_read_file_as_a_string

`util_read_file_as_a_string(F)`

: It reads a file F as a string.

19.0.11 util_remove_cr

`util_remove_cr(S)`

: It removes `cr`/`lf`/`tabs` from S . Arguments must be a list of ascii codes.

19.0.12 util_timing

`util_timing(Q)`

: Show the timing data to execute Q .

Example:

```
util_timing( quote( fctr(x^50-y^50) ));
```

19.0.13 util_v

`util_v(V,L)`

: It returns a variable indexed by L .

Example:

```
util_v("x",[1,3]);
```

References:

`util_index`

19.0.14 util_write_string_to_a_file

`util_write_string_to_a_file(Fname,S)`

: It writes a string S to a file $Fname$.

20 Other Manuals

This section introduces other manuals in the asir-contrib project.

This section also describes functions that have not yet been classified. These will be moved to independent sections in a future.

20.0.1 dsolv (Solving the initial ideal for holonomic systems)

`../dsolv-html/dsolv-en.html`

20.0.2 gtt_ekn (Two way contingency tables by HGM)

`../gtt_ekn-html/gtt_ekn-en.html`

20.0.3 f_res (Comuting resultant)

`../f_res-html/f_res-en.html`

20.0.4 (gnuplot ox server for graphics)

`../gnuplot-html/gnuplot-en.html`

20.0.5 mathematica (Mathematica (TM) ox server)

`../mathematica-html/mathematica-en.html`

20.0.6 mt_graph (3D grapher)

`../mk_graph-html/mk_graph-en.html`

20.0.7 mt_gkz (Intersection matrix of GKZ systems)

`../mt_gkz-html/mt_gkz-en.html`

20.0.8 n_wishartd (restriction of matrix 1F1)

`../n_wishartd-html/n_wishartd-en.html`

20.0.9 nn_ndbf (local b-function)

`../nn_ndbf-html/nn_ndbf-en.html`

20.0.10 noro_mwl (Mordel Weil Lattice)

`../noro_mwl-html/noro_mwl-en.html`

20.0.11 noro_module_syz (syzygies for modules)

`../noro_module_syz-html/noro_module_syz-en.html`

20.0.12 ns_twistedlog (twisted logarithmic cohomology group)

`../ns_twistedlog-html/ns_twistedlog-en.html`

20.0.13 nk_fb_gen_c (Fisher Bingham MLE)

`../nk_fb_gen_c-html/nk_fb_gen_c-en.html`

20.0.14 ok_diff (Okutani's library for differential operators)

`../ok_diff-html/ok_diff-en.html`

20.0.15 ok_dmodule (Okutani's library for D-modules)

`../ok_dmodule-html/ok_dmodule-en.html`

20.0.16 om (om (java) ox server for translating CMO and OpenMath)

`../om-html/om-en.html`

20.0.17 ox_pari (OpenXM pari server)

`../ox_pari-html/ox_pari-en.html`

20.0.18 (Plucker relations)

`../plucker-html/plucker-en.html`

20.0.19 pfpcoh (Ohara's library for homology/cohomology groups for $p \nmid q$)

`../pfpcoh-html/pfpcoh-en.html`

20.0.20 phc (PHC ox server for solving systems of algebraic equations by the homotopy method)

`../phc-html/phc-en.html`

20.0.21 sm1 (Kan/sm1 ox server for the ring of differential operators)

`../sm1-html/sm1-en.html`

20.0.22 tigers (tigers ox server for toric universal Grobner bases)

`../tigers-html/tigers-en.html`

20.0.23 tk_ode_by_mpfr (Generating C codes for numerical analysis of ODE by MPFR, document in Japanese)

`../tk_ode_by_mpfr-html/tk_ode_by_mpfr-ja.html`

20.0.24 [[todo_parametrize]]

`todo_parametrize/todo_parametrize_toc`

With loading the file `todo_parametrize/todo_parametrize.rr` the function `parametrize` is installed. The function finds a parametric expression of a given rational curve. As to details, see *See A package for algebraic curves* (in Japanese).

```
[1205] load("todo_parametrize/todo_parametrize.rr");
1
[1425] parametrize(y^2-x^3);
```

```
[155*t^2+20*t+1,720*t^4+1044*t^3+580*t^2,155*t^4+20*t^3+t^2,(-x)/(y)]
[1426] parametrize(y^2+x^3);
[-t,1,t^3,(-x)/(y)]
```

20.0.25 taji_alc

With loading the file `taji_alc.rr` functions for algebraic local cohomology groups in one variable are imported.

```
import("taji_alc.rr");
taji_alc.laurent_expansion(x,(x-1)^3);
```

20.0.26 Manual and papers which are not written in texinfo.

Links to manuals and papers related to files and commands in `asir-contrib` are at OpenXM documents (<http://www.math.kobe-u.ac.jp/OpenXM/Current/doc/index-doc-en.html>).

Index

(Index is nonexistent)

(Index is nonexistent)

Short Contents

1	Introduction.....	1
2	How to load Asir/Contrib.....	3
3	Function Names in Asir Contrib.....	4
4	Asir-contrib for Windows	5
5	Basic (Standard Functions)	6
6	Numbers (Standard Mathematical Functions).....	11
7	Calculus (Standard Mathematical Functions)	13
8	Series (Standard Mathematical Functions)	14
9	Special Functions (Standard Mathematical Functions).....	15
10	Matrix (Standard Mathematical Functions)	16
11	Graphic (Standard Mathematical Functions)	20
12	Print (Standard Mathematical Functions).....	21
13	Polynomials (Standard Mathematical Functions)	25
14	Complex (Standard Mathematical Functions).....	32
15	Graphic Library (2 dimensional)	33
16	OpenXM-Contrib General Functions	35
17	OXshell Functions	36
18	Asir System Utility Functions.....	37
19	Utility Functions	38
20	Other Manuals.....	40
	Index	43

Table of Contents

1	Introduction	1
2	How to load Asir/Contrib	3
3	Function Names in Asir Contrib	4
4	Asir-contrib for Windows	5
5	Basic (Standard Functions)	6
5.0.1	base_cancel	6
5.0.2	base_choose	6
5.0.3	base_f_definedp	6
5.0.4	base_flatten	6
5.0.5	base_intersection	6
5.0.6	base_is_asir2018	6
5.0.7	base_is_equal	6
5.0.8	base_makelist	7
5.0.9	base_memberq	7
5.0.10	base_permutation	7
5.0.11	base_position	7
5.0.12	base_preplace	7
5.0.13	base_product	8
5.0.14	base_prune	8
5.0.15	base_rebuild_opt	8
5.0.16	base_replace	8
5.0.17	base_replace_n	8
5.0.18	base_set_minus	9
5.0.19	base_set_union	9
5.0.20	base_subsequenceq	9
5.0.21	base_subsetq	9
5.0.22	base_subsets_of_size	9
5.0.23	base_sum	9
5.0.24	base_var_list	10
6	Numbers (Standard Mathematical Functions) ..	11
6.0.1	number_abs	11
6.0.2	number_ceiling	11
6.0.3	number_eval	11
6.0.4	number_factor	11
6.0.5	number_float_to_rational	11
6.0.6	number_floor	11

6.0.7	number_imaginary_part	12
6.0.8	number_is_integer	12
6.0.9	number_real_part	12
7	Calculus (Standard Mathematical Functions) ..	13
8	Series (Standard Mathematical Functions)...	14
9	Special Functions (Standard Mathematical Functions)	15
10	Matrix (Standard Mathematical Functions) ..	16
10.0.1	matrix_adjugate	16
10.0.2	matrix_clone	16
10.0.3	matrix_det	16
10.0.4	matrix_diagonal_matrix	16
10.0.5	matrix_eigenvalues	16
10.0.6	matrix_gauge_transformation	16
10.0.7	matrix_identity_matrix	17
10.0.8	matrix_ij	17
10.0.9	matrix_image	17
10.0.10	matrix_inner_product	17
10.0.11	matrix_inverse	17
10.0.12	matrix_inverse_singular	17
10.0.13	matrix_kernel	18
10.0.14	matrix_list_to_matrix	18
10.0.15	matrix_matrix_to_list	18
10.0.16	matrix_poly_to_matrix	18
10.0.17	matrix_rank	18
10.0.18	matrix_solve_linear	18
10.0.19	matrix_submatrix	19
10.0.20	matrix_transpose	19
11	Graphic (Standard Mathematical Functions) ..	20
12	Print (Standard Mathematical Functions) ..	21
12.0.1	print_c_form	21
12.0.2	print_dvi_form	21
12.0.3	print_em	21
12.0.4	print_gif_form	21
12.0.5	print_input_form	21
12.0.6	print_open_math_tfb_form	22
12.0.7	print_open_math_xml_form	22
12.0.8	print_output	22
12.0.9	print_ox_rfc100_xml_form	22

12.0.10	print_pdf_form	23
12.0.11	print_png_form	23
12.0.12	print_terminal_form	23
12.0.13	print_tex_form	23
12.0.14	print_tfb_form	24
12.0.15	print_xdvi_form	24
12.0.16	print_xv_form	24
13	Polynomials (Standard Mathematical Functions)	25
13.0.1	poly_coefficient	25
13.0.2	poly_degree	25
13.0.3	poly_denominator	25
13.0.4	poly_elimination_ideal	25
13.0.5	poly_expand	26
13.0.6	poly_factor	26
13.0.7	poly_gcd	26
13.0.8	poly_gr_w	26
13.0.9	poly_grobner_basis	26
13.0.10	poly_hilbert_polynomial	27
13.0.11	poly_ideal_colon	27
13.0.12	poly_ideal_intersection	27
13.0.13	poly_ideal_saturation	28
13.0.14	poly_in	28
13.0.15	poly_in_w	28
13.0.16	poly_in_w_	28
13.0.17	poly_initial	29
13.0.18	poly_initial_coefficients	29
13.0.19	poly_initial_term	29
13.0.20	poly_lcm	29
13.0.21	poly_ord_w	30
13.0.22	poly_prime_dec	30
13.0.23	poly_r_omatrix	30
13.0.24	poly_solve_linear	30
13.0.25	poly_sort	30
13.0.26	poly_toric_ideal	31
13.0.27	poly_weight_to_omatrix	31
14	Complex (Standard Mathematical Functions) ..	32
15	Graphic Library (2 dimensional)	33
15.0.1	glib_clear	33
15.0.2	glib_flush	33
15.0.3	glib_line	33
15.0.4	glib_open	33
15.0.5	glib_plot	33
15.0.6	glib_print	33

15.0.7	<code>glib_ps_form</code>	34
15.0.8	<code>glib_putpixel</code>	34
15.0.9	<code>glib_remove_last</code>	34
15.0.10	<code>glib_set_pixel_size</code>	34
15.0.11	<code>glib_tops</code>	34
15.0.12	<code>glib_window</code>	34
16	OpenXM-Contrib General Functions	35
16.1	Functions.....	35
16.1.1	<code>ox_check_errors2</code>	35
17	OXshell Functions	36
17.0.1	<code>oxshell.get_value</code>	36
17.0.2	<code>oxshell.oxshell</code>	36
17.0.3	<code>oxshell.set_value</code>	36
18	Asir System Utility Functions	37
18.0.1	<code>asir_contrib_update</code>	37
19	Utility Functions	38
19.0.1	<code>util_damepathq</code>	38
19.0.2	<code>util_file_exists</code>	38
19.0.3	<code>util_filter</code>	38
19.0.4	<code>util_find_and_replace</code>	38
19.0.5	<code>util_find_start</code>	38
19.0.6	<code>util_find_substr</code>	38
19.0.7	<code>util_index</code>	39
19.0.8	<code>util_load_file_as_a_string</code>	39
19.0.9	<code>util_part</code>	39
19.0.10	<code>util_read_file_as_a_string</code>	39
19.0.11	<code>util_remove_cr</code>	39
19.0.12	<code>util_timing</code>	39
19.0.13	<code>util_v</code>	39
19.0.14	<code>util_write_string_to_a_file</code>	39
20	Other Manuals	40
20.0.1	<code>dsolv</code> (Solving the initial ideal for holonomic systems)....	40
20.0.2	<code>gtt_ekn</code> (Two way contingency tables by HGM).....	40
20.0.3	<code>f_res</code> (Comuting resultant).....	40
20.0.4	(gnuplot ox server for graphics).....	40
20.0.5	<code>mathematica</code> (Mathematica (TM) ox server).....	40
20.0.6	<code>mt_graph</code> (3D grapher).....	40
20.0.7	<code>mt_gkz</code> (Intersection matrix of GKZ systems).....	40
20.0.8	<code>n_wishartd</code> (restriction of matrix 1F1).....	40
20.0.9	<code>nn_ndbf</code> (local b-function).....	40
20.0.10	<code>noro_mwl</code> (Mordel Weil Lattice).....	40

20.0.11	noro_module_syz (syzygies for modules).....	40
20.0.12	ns_twistedlog (twisted logarithmic cohomology group) ...	40
20.0.13	nk_fb_gen_c (Fisher Bingham MLE)	40
20.0.14	ok_diff (Okutani's library for differential operators)	41
20.0.15	ok_dmodule (Okutani's library for D-modules)	41
20.0.16	om (om (java) ox server for translating CMO and OpenMath)	41
20.0.17	ox_pari (OpenXM pari server)	41
20.0.18	(Plucker relations)	41
20.0.19	pfpcoh (Ohara's library for homology/cohomology groups for $p \mid F \mid q$)	41
20.0.20	phc (PHC ox server for solving systems of algebraic equations by the homotopy method)	41
20.0.21	sm1 (Kan/sm1 ox server for the ring of differential operators)	41
20.0.22	tigers (tigers ox server for toric universal Grobner bases) ..	41
20.0.23	tk_ode_by_mpfir (Generating C codes for numerical analysis of ODE by MPFR, document in Japanese)	41
20.0.24	[[todo_parametrize]]	41
20.0.25	taji_alc	42
20.0.26	Manual and papers which are not written in texinfo.	42
Index		43

