

# OpenMath XML Translation Server Manual

---

Edition : auto generated by oxgentexi on 27 July 2021

# 1 OpenMath Functions(Version 1999)

The functions in this section is defined in the file `om.rr`. An environment to execute Java codes must be set to call the functions described in this section.

Author of OMproxy : Yasushi Tamura.

## 1.0.1 om\_start

```
om_start()
    :: Start OMproxy server to make a translation between CMO and OpenMath
    XML (CD's in 1999) expressions.

return    Number
[155] load("om.rr");
1
[160] om_start();
control: wait OX
Trying to connect to the server... Done.
0
[161] om_xml(<<1,0>>+2*<<0,1>>);
<OMOBJ><OMA><OMS name="DMP" cd="poly"/>
<OMA><OMS name="PolyRing" cd="poly"/>
  <OMI>2</OMI></OMA><OMA>
  <OMS name="SDMP" cd="poly"/>
  <OMA><OMS name="Monom" cd="poly"/><OMI>1</OMI><OMI>1</OMI><OMI>0</OMI></OMA>
  <OMA><OMS name="Monom" cd="poly"/><OMI>2</OMI><OMI>0</OMI><OMI>1</OMI></OMA>
</OMA></OMA></OMOBJ>
[162] om_xml_to_cmo(@);
(1)*<<1,0>>+(2)*<<0,1>>
```

## 1.0.2 om\_xml

```
om_xml(s|proc=p)
    :: Translate CMO expression of s to a XML expression of OpenMath(CD's in
    1999).

return    String
p        Number
s        Object

• Translate CMO s to a XML expression of OpenMath(CD's in 1999).
  For (I=0; I<10; I++) {
    A = 2^I;
    B = om_xml(A);
    C = om_xml_to_cmo(B);
    print(A == C);
  }
```

### 1.0.3 om\_xml\_to\_cmo

`om_xml_to_cmo(s|proc=p)`

*::* Translate XML expression (CD's in 1999) *s* of OpenMath to a CMO.

*return*      Object

*p*            Number

*s*            String

- Translate XML expression (CD's in 1999) *s* of OpenMath to a CMO.

# Index

(Index is nonexistent)

(Index is nonexistent)

## Short Contents

1	OpenMath Functions (Version 1999) . . . . .	1
	Index . . . . .	3

## Table of Contents

<b>1</b>	<b>OpenMath Functions(Version 1999)</b>	<b>1</b>
1.0.1	om_start	1
1.0.2	om_xml	1
1.0.3	om_xml_to_cmo	2
	<b>Index</b>	<b>3</b>

